



Welcome to [E-XFL.COM](https://www.e-xfl.com)

### What is "[Embedded - Microcontrollers](#)"?

"[Embedded - Microcontrollers](#)" refer to small, integrated circuits designed to perform specific tasks within larger systems. These microcontrollers are essentially compact computers on a single chip, containing a processor core, memory, and programmable input/output peripherals. They are called "embedded" because they are embedded within electronic devices to control various functions, rather than serving as standalone computers. Microcontrollers are crucial in modern electronics, providing the intelligence and control needed for a wide range of applications.

### Applications of "[Embedded - Microcontrollers](#)"

#### Details

|                            |   |
|----------------------------|---|
| Product Status             | Active  |
| Core Processor             | PIC   |
| Core Size                  | 8-Bit   |
| Speed                      | 20MHz   |
| Connectivity               | -   |
| Peripherals                | Brown-out Detect/Reset, POR, PWM, WDT   |
| Number of I/O              | 5   |
| Program Memory Size        | 1.75KB (1K x 14)  |
| Program Memory Type        | FLASH   |
| EEPROM Size                | -   |
| RAM Size                   | 64 x 8  |
| Voltage - Supply (Vcc/Vdd) | 2V ~ 5V   |
| Data Converters            | A/D 4x10b; D/A 1x5b   |
| Oscillator Type            | Internal  |
| Operating Temperature      | -40°C ~ 85°C (TA)   |
| Mounting Type              | Surface Mount   |
| Package / Case             | 8-VDFN Exposed Pad  |
| Supplier Device Package    | 8-DFN (3x3)   |
| Purchase URL               | <a href="https://www.e-xfl.com/product-detail/microchip-technology/pic12hv752t-i-mf">https://www.e-xfl.com/product-detail/microchip-technology/pic12hv752t-i-mf</a> |

---

## 14-Pin Flash-Based, 8-Bit CMOS Microcontrollers with Intelligent Analog

---

### High-Performance RISC CPU:

- Only 35 Instructions to Learn
- All Single-Cycle Instructions except Branches
- Operating Speed:
  - DC – 20 MHz clock input
  - DC – 200 ns instruction cycle
- 2048 x 14 On-Chip Flash Program Memory
- Self Read/Write Program Memory
- Interrupt Capability with Automatic Context Saving
- 8-Level Deep Hardware Stack
- Direct, Indirect and Relative Addressing modes

### Special Microcontroller Features:

- Precision Internal Oscillator:
  - Factory calibrated to  $\pm 1\%$ , typical
  - Software selectable frequency:  
8 MHz, 4 MHz, 1 MHz, or 31 kHz
- Power-Saving Sleep mode
- Operating Voltage Range (PIC16F753):
  - 2.0V-5.5V
- Shunt Voltage Regulator (PIC16HV753):
  - 5.0V regulation
  - 1 mA to 50 mA shunt range
  - 2.0V to user defined
- Multiplexed Master Clear with Pull-up/Input Pin
- Interrupt-on-Change Pins
- Individually Programmable Weak Pull-ups
- Power-on Reset (POR)
- Power-up Timer (PWRT)
- Brown-out Reset (BOR)
- Watchdog Timer (WDT) with Internal Oscillator for Reliable Operation
- Industrial and Extended Temperature Range
- High Endurance Flash/EEPROM Cell:
  - 100,000 write Flash endurance
  - Flash retention: >40 years
- Programmable Code Protection
- In-Circuit Serial Programming™ (ICSP™) via Two Pins
- In-Circuit Debug (ICD) via Two Pins

### Low-Power Features:

- Standby Current:
  - 50 nA @ 2.0V, typical
- Operating Current:
  - 11  $\mu$ A @ 32 kHz, 2.0V, typical
  - 260  $\mu$ A @ 4 MHz, 2.0V, typical
- Watchdog Timer Current:
  - <1  $\mu$ A @ 2.0V, typical

### Peripheral Features:

- 11 I/O Pins (1 input-only pin):
- High Current Sink/Source:
  - 50 mA I/O (2 pins)
  - 25 mA I/O (9 pins)
- Two High-Speed Analog Comparator Modules:
  - 50 ns response time
  - Fixed Voltage Reference (FVR)
  - Programmable on-chip voltage reference via integrated 9-bit DAC
  - Internal/external inputs and outputs (selectable)
  - Built-in Hysteresis (software selectable)
- Analog-to-Digital Converter (ADC):
  - 10-bit resolution
  - Eight external channels
  - Two internal reference voltage channels
- Operational Amplifier:
  - Three terminal operation
  - Internal connections to DAC and FVR
- Digital-to-Analog Converter (DAC):
  - 9-bit resolution
  - Full range resolution
  - 4 mV steps at 2.0V
- Fixed Voltage Reference (FVR), 1.2V Reference
- Capture, Compare, PWM (CCP) Module:
  - 16-bit Capture, max. resolution 12.5 ns
  - 16-bit Compare, max. resolution 200 ns
  - 10-bit PWM, max. frequency 20 kHz
- Timer0: 8-Bit Timer/Counter with 8-Bit Programmable Prescaler
- Enhanced Timer1:
  - 16-bit timer/counter with prescaler
  - External Timer1 gate (count enable)
  - Four selectable clock sources
- Timer2: 8-Bit Timer/Counter with 8-Bit Period Register, Prescaler and Postscaler

# PIC16F753/HV753

## Peripheral Features (Continued):

- Complementary Output Generator (COG):
  - Slope Compensation Circuit for use with SMPS power supplies
  - Complementary Waveforms for Full and Half-Bridge topologies
  - Two I/O (50 mA) for direct MOSFET drive
  - Rising and/or Falling edge input sources for flexible control topologies
  - Phase, Blanking dead-band control
  - Auto-shutdown
  - Hardware Limit Timer (HLT)
  - 8-bit Timer with prescaler
  - 8-bit period register and postscaler
  - Asynchronous H/W Reset sources

## PIC12F752/HV752/PIC16F753/HV753 Family Types

| Device     | Data Sheet Index | Program Memory Flash (words) | Self Read/Write Flash Memory | Data SRAM (bytes) | I/O's <sup>(2)</sup> | 10-bit ADC (ch) | Comparators | Timers (8/16-bit) | CCP | Complementary Output Generator (COG) | DAC   | Operational Amplifiers | Shunt Regulator | Debug <sup>(1)</sup> |
|------------|------------------|------------------------------|------------------------------|-------------------|----------------------|-----------------|-------------|-------------------|-----|--------------------------------------|-------|------------------------|-----------------|----------------------|
| PIC12F752  | (1)              | 1K                           | Y                            | 64                | 6                    | 4               | 2           | 3/1               | 1   | Y                                    | 5-bit | N                      | N               | H                    |
| PIC12HV752 | (1)              | 1K                           | Y                            | 64                | 6                    | 4               | 2           | 3/1               | 1   | Y                                    | 5-bit | N                      | Y               | H                    |
| PIC16F753  | (2)              | 2K                           | Y                            | 128               | 12                   | 8               | 2           | 3/1               | 1   | Y                                    | 9-bit | Y                      | N               | I/H                  |
| PIC16HV753 | (2)              | 2K                           | Y                            | 128               | 12                   | 8               | 2           | 3/1               | 1   | Y                                    | 9-bit | Y                      | Y               | I/H                  |

**Note 1:** I - Debugging, Integrated on Chip; H – Debugging, Available using Debug Header


**2:** One pin is input-only.

### Data Sheet Index:


- 1: DS41576 [PIC12F752/HV752 Data Sheet, 8-Pin, Flash-Based 8-Bit CMOS Microcontrollers.](#)
- 2: Future Release [PIC16F753/HV753 Data Sheet, 14-Pin, Flash-Based 8-Bit CMOS Microcontrollers with Intelligent Analog.](#)

**Note:** For other small form-factor package availability and marking information, please visit <http://www.microchip.com/packaging> or contact your local sales office.

**FIGURE 1: 14-PIN PDIP, SOIC, TSSOP DIAGRAM FOR PIC16F753/HV753**



**FIGURE 2: 16-PIN QFN DIAGRAM FOR PIC16F753/HV753**



# PIC16F753/HV753

**TABLE 1: 14-PIN ALLOCATION TABLE (PIC16F753/HV753)**

| I/O | 14-Pin PDIP/SOIC/TSSOP | 16-Pin QFN | ADC | Reference        | Op Amp  | Comparator       | Timer              | CCP  | Interrupt  | Pull-Up | Basic   |
|-----|------------------------|------------|-----|------------------|---------|------------------|--------------------|------|------------|---------|---------|
| RA0 | 13                     | 12         | AN0 | FVROUT<br>DACOUT | —       | C1IN0+           | —                  | —    | IOC        | Y       | ICSPDAT |
| RA1 | 12                     | 11         | AN1 | VREF<br>FVRIN    | —       | C1IN0-<br>C2IN0- | —                  | —    | IOC        | Y       | ICSPCLK |
| RA2 | 11                     | 10         | AN2 | C0G1FLT          | —       | C1OUT            | T0CKI              | —    | INT<br>IOC | Y       | —       |
| RA3 | 4                      | 3          | —   | —                | —       | —                | T1G <sup>(2)</sup> | —    | IOC        | Y       | MCLR    |
| RA4 | 3                      | 2          | AN3 | —                | —       | —                | T1G <sup>(1)</sup> | —    | IOC        | Y       | CLKOUT  |
| RA5 | 2                      | 1          | —   | —                | —       | —                | T1CKI              | —    | IOC        | Y       | —       |
| RC0 | 10                     | 9          | AN4 | —                | OPA1IN+ | C2IN0+           | —                  | —    | IOC        | —       | —       |
| RC1 | 9                      | 8          | AN5 | —                | OPA1IN- | C1IN1-<br>C2IN1- | —                  | —    | IOC        | —       | —       |
| RC2 | 8                      | 7          | AN6 | —                | OPA1OUT | C1IN2-<br>C2IN2- | —                  | —    | IOC        | —       | —       |
| RC3 | 7                      | 6          | AN7 | —                | —       | C1IN3-<br>C2IN3- | —                  | —    | IOC        | —       | —       |
| RC4 | 6                      | 5          | —   | COG1OUT1         | —       | C2OUT            | —                  | —    | IOC        | —       | —       |
| RC5 | 5                      | 4          | —   | COG1OUT0         | —       | —                | —                  | CCP1 | IOC        | —       | —       |
| VDD | 1                      | 16         | —   | —                | —       | —                | —                  | —    | —          | —       | VDD     |
| VSS | 14                     | 13         | —   | —                | —       | —                | —                  | —    | —          | —       | VSS     |

**Note 1:** Default location for peripheral pin function. Alternate location can be selected using the APFCON register.

**Note 2:** Alternate location for peripheral pin function selected by the APFCON register.

---

**Note the following details of the code protection feature on Microchip devices:**

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

---

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights.

#### **Trademarks**

The Microchip name and logo, the Microchip logo, dsPIC, FlashFlex, KEELOQ, KEELOQ logo, MPLAB, PIC, PICmicro, PICSTART, PIC<sup>32</sup> logo, rPIC, SST, SST Logo, SuperFlash and UNI/O are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

FilterLab, Hampshire, HI-TECH C, Linear Active Thermistor, MTP, SEEVAL and The Embedded Control Solutions Company are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Silicon Storage Technology is a registered trademark of Microchip Technology Inc. in other countries.

Analog-for-the-Digital Age, Application Maestro, BodyCom, chipKIT, chipKIT logo, CodeGuard, dsPICDEM, dsPICDEM.net, dsPICworks, dsSPEAK, ECAN, ECONOMONITOR, FanSense, HI-TIDE, In-Circuit Serial Programming, ICSP, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, mTouch, Omniclient Code Generation, PICC, PICC-18, PICDEM, PICDEM.net, PICkit, PICTail, REAL ICE, rLAB, Select Mode, SQI, Serial Quad I/O, Total Endurance, TSHARC, UniWinDriver, WiperLock, ZENA and Z-Scale are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

GestIC and ULPP are registered trademarks of Microchip Technology Germany II GmbH & Co. & KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2012, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.



Printed on recycled paper.

ISBN: 9781620766514

**QUALITY MANAGEMENT SYSTEM**  
**CERTIFIED BY DNV**  
**== ISO/TS 16949 ==**

*Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELOQ® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.*

## Worldwide Sales and Service

### AMERICAS

**Corporate Office**  
2355 West Chandler Blvd.  
Chandler, AZ 85224-6199  
Tel: 480-792-7200  
Fax: 480-792-7277  
Technical Support:  
<http://www.microchip.com/support>  
Web Address:  
[www.microchip.com](http://www.microchip.com)

**Atlanta**  
Duluth, GA  
Tel: 678-957-9614  
Fax: 678-957-1455

**Boston**  
Westborough, MA  
Tel: 774-760-0087  
Fax: 774-760-0088

**Chicago**  
Itasca, IL  
Tel: 630-285-0071  
Fax: 630-285-0075

**Cleveland**  
Independence, OH  
Tel: 216-447-0464  
Fax: 216-447-0643

**Dallas**  
Addison, TX  
Tel: 972-818-7423  
Fax: 972-818-2924

**Detroit**  
Farmington Hills, MI  
Tel: 248-538-2250  
Fax: 248-538-2260

**Indianapolis**  
Noblesville, IN  
Tel: 317-773-8323  
Fax: 317-773-5453

**Los Angeles**  
Mission Viejo, CA  
Tel: 949-462-9523  
Fax: 949-462-9608

**Santa Clara**  
Santa Clara, CA  
Tel: 408-961-6444  
Fax: 408-961-6445

**Toronto**  
Mississauga, Ontario,  
Canada  
Tel: 905-673-0699  
Fax: 905-673-6509

### ASIA/PACIFIC

**Asia Pacific Office**  
Suites 3707-14, 37th Floor  
Tower 6, The Gateway  
Harbour City, Kowloon  
Hong Kong  
Tel: 852-2401-1200  
Fax: 852-2401-3431

**Australia - Sydney**  
Tel: 61-2-9868-6733  
Fax: 61-2-9868-6755

**China - Beijing**  
Tel: 86-10-8569-7000  
Fax: 86-10-8528-2104

**China - Chengdu**  
Tel: 86-28-8665-5511  
Fax: 86-28-8665-7889

**China - Chongqing**  
Tel: 86-23-8980-9588  
Fax: 86-23-8980-9500

**China - Hangzhou**  
Tel: 86-571-2819-3187  
Fax: 86-571-2819-3189

**China - Hong Kong SAR**  
Tel: 852-2401-1200  
Fax: 852-2401-3431

**China - Nanjing**  
Tel: 86-25-8473-2460  
Fax: 86-25-8473-2470

**China - Qingdao**  
Tel: 86-532-8502-7355  
Fax: 86-532-8502-7205

**China - Shanghai**  
Tel: 86-21-5407-5533  
Fax: 86-21-5407-5066

**China - Shenyang**  
Tel: 86-24-2334-2829  
Fax: 86-24-2334-2393

**China - Shenzhen**  
Tel: 86-755-8203-2660  
Fax: 86-755-8203-1760

**China - Wuhan**  
Tel: 86-27-5980-5300  
Fax: 86-27-5980-5118

**China - Xian**  
Tel: 86-29-8833-7252  
Fax: 86-29-8833-7256

**China - Xiamen**  
Tel: 86-592-2388138  
Fax: 86-592-2388130

**China - Zhuhai**  
Tel: 86-756-3210040  
Fax: 86-756-3210049

### ASIA/PACIFIC

**India - Bangalore**  
Tel: 91-80-3090-4444  
Fax: 91-80-3090-4123

**India - New Delhi**  
Tel: 91-11-4160-8631  
Fax: 91-11-4160-8632

**India - Pune**  
Tel: 91-20-2566-1512  
Fax: 91-20-2566-1513

**Japan - Osaka**  
Tel: 81-66-152-7160  
Fax: 81-66-152-9310

**Japan - Yokohama**  
Tel: 81-45-471-6166  
Fax: 81-45-471-6122

**Korea - Daegu**  
Tel: 82-53-744-4301  
Fax: 82-53-744-4302

**Korea - Seoul**  
Tel: 82-2-554-7200  
Fax: 82-2-558-5932 or  
82-2-558-5934

**Malaysia - Kuala Lumpur**  
Tel: 60-3-6201-9857  
Fax: 60-3-6201-9859

**Malaysia - Penang**  
Tel: 60-4-227-8870  
Fax: 60-4-227-4068

**Philippines - Manila**  
Tel: 63-2-634-9065  
Fax: 63-2-634-9069

**Singapore**  
Tel: 65-6334-8870  
Fax: 65-6334-8850

**Taiwan - Hsin Chu**  
Tel: 886-3-5778-366  
Fax: 886-3-5770-955

**Taiwan - Kaohsiung**  
Tel: 886-7-213-7828  
Fax: 886-7-330-9305

**Taiwan - Taipei**  
Tel: 886-2-2508-8600  
Fax: 886-2-2508-0102

**Thailand - Bangkok**  
Tel: 66-2-694-1351  
Fax: 66-2-694-1350

### EUROPE

**Austria - Wels**  
Tel: 43-7242-2244-39  
Fax: 43-7242-2244-393

**Denmark - Copenhagen**  
Tel: 45-4450-2828  
Fax: 45-4485-2829

**France - Paris**  
Tel: 33-1-69-53-63-20  
Fax: 33-1-69-30-90-79

**Germany - Munich**  
Tel: 49-89-627-144-0  
Fax: 49-89-627-144-44

**Italy - Milan**  
Tel: 39-0331-742611  
Fax: 39-0331-466781

**Netherlands - Drunen**  
Tel: 31-416-690399  
Fax: 31-416-690340

**Spain - Madrid**  
Tel: 34-91-708-08-90  
Fax: 34-91-708-08-91

**UK - Wokingham**  
Tel: 44-118-921-5869  
Fax: 44-118-921-5820