## E·XFL



Welcome to E-XFL.COM

## What is "Embedded - Microcontrollers"?

"Embedded - Microcontrollers" refer to small, integrated circuits designed to perform specific tasks within larger systems. These microcontrollers are essentially compact computers on a single chip, containing a processor core, memory, and programmable input/output peripherals. They are called "embedded" because they are embedded within electronic devices to control various functions, rather than serving as standalone computers. Microcontrollers are crucial in modern electronics, providing the intelligence and control needed for a wide range of applications.

Applications of "<u>Embedded -</u> <u>Microcontrollers</u>"

## Details

Product Status	Obsolete
Core Processor	8051
Core Size	8-Bit
Speed	50MHz
Connectivity	EBI/EMI, SMBus (2-Wire/I <sup>2</sup> C), SPI, UART/USART
Peripherals	Brown-out Detect/Reset, POR, PWM, Temp Sensor, WDT
Number of I/O	64
Program Memory Size	128KB (128K x 8)
Program Memory Type	FLASH
EEPROM Size	-
RAM Size	8.25K x 8
Voltage - Supply (Vcc/Vdd)	2.7V ~ 3.6V
Data Converters	A/D 8x8b, 8x12b; D/A 2x12b
Oscillator Type	Internal
Operating Temperature	-40°C ~ 85°C (TA)
Mounting Type	Surface Mount
Package / Case	100-TQFP
Supplier Device Package	100-TQFP (14x14)
Purchase URL	https://www.e-xfl.com/product-detail/silicon-labs/c8051f124r

Email: info@E-XFL.COM

Address: Room A, 16/F, Full Win Commercial Centre, 573 Nathan Road, Mongkok, Hong Kong

## List of Figures

1.	System Overview	
	Figure 1.1. C8051F120/124 Block Diagram	21
	Figure 1.2. C8051F121/125 Block Diagram	22
	Figure 1.3. C8051F122/126 Block Diagram	23
	Figure 1.4. C8051F123/127 Block Diagram	24
	Figure 1.5. C8051F130/132 Block Diagram	25
	Figure 1.6. C8051F131/133 Block Diagram	26
	Figure 1.7. On-Board Clock and Reset	28
	Figure 1.8. On-Chip Memory Map	
	Figure 1.9. Development/In-System Debug Diagram	30
	Figure 1.10. MAC0 Block Diagram	31
	Figure 1.11. Digital Crossbar Diagram	32
	Figure 1.12. PCA Block Diagram	33
	Figure 1.13. 12-Bit ADC Block Diagram	34
	Figure 1.14. 8-Bit ADC Diagram	35
	Figure 1.15. DAC System Block Diagram	36
	Figure 1.16. Comparator Block Diagram	37
	Absolute Maximum Ratings	
3.	Global DC Electrical Characteristics	
4.	Pinout and Package Definitions	
	Figure 4.1. C8051F120/2/4/6 Pinout Diagram (TQFP-100)	
	Figure 4.2. C8051F130/2 Pinout Diagram (TQFP-100)	
	Figure 4.3. TQFP-100 Package Drawing	
	Figure 4.4. C8051F121/3/5/7 Pinout Diagram (TQFP-64)	
	Figure 4.5. C8051F131/3 Pinout Diagram (TQFP-64)	
	Figure 4.6. TQFP-64 Package Drawing	54
5.	ADC0 (12-Bit ADC, C8051F120/1/4/5 Only)	
	Figure 5.1. 12-Bit ADC0 Functional Block Diagram	
	Figure 5.2. Typical Temperature Sensor Transfer Function	
	Figure 5.3. ADC0 Track and Conversion Example Timing	
	Figure 5.4. ADC0 Equivalent Input Circuits	
	Figure 5.5. ADC0 Data Word Example	65
	Figure 5.6. 12-Bit ADC0 Window Interrupt Example:	
	Right Justified Single-Ended Data	68
	Figure 5.7. 12-Bit ADC0 Window Interrupt Example:	
	Right Justified Differential Data	69
	Figure 5.8. 12-Bit ADC0 Window Interrupt Example:	
	Left Justified Single-Ended Data	70
	Figure 5.9. 12-Bit ADC0 Window Interrupt Example:	
	Left Justified Differential Data	71

