



Welcome to [E-XFL.COM](#)

What is "[Embedded - Microcontrollers](#)"?

"[Embedded - Microcontrollers](#)" refer to small, integrated circuits designed to perform specific tasks within larger systems. These microcontrollers are essentially compact computers on a single chip, containing a processor core, memory, and programmable input/output peripherals. They are called "embedded" because they are embedded within electronic devices to control various functions, rather than serving as standalone computers. Microcontrollers are crucial in modern electronics, providing the intelligence and control needed for a wide range of applications.

Applications of "[Embedded - Microcontrollers](#)"

Details

Product Status	Obsolete
Core Processor	F ² MC-8FX
Core Size	8-Bit
Speed	16MHz
Connectivity	I ² C, LINbus, SIO, UART/USART
Peripherals	LVD, POR, PWM, WDT
Number of I/O	21
Program Memory Size	36KB (36K x 8)
Program Memory Type	FLASH
EEPROM Size	-
RAM Size	1K x 8
Voltage - Supply (Vcc/Vdd)	1.8V ~ 5.5V
Data Converters	A/D 6x8/12b
Oscillator Type	External
Operating Temperature	-40°C ~ 85°C (TA)
Mounting Type	Surface Mount
Package / Case	24-TSSOP (0.173", 4.40mm Width)
Supplier Device Package	24-TSSOP
Purchase URL	https://www.e-xfl.com/product-detail/infineon-technologies/mb95f656epft-g-snere2

Consumer and Industrial MCU Family




FM4 FAMILY

Cypress ARM® Cortex®-M4F microcontroller family is a high range line providing maximum CPU frequency of 200MHz, a high speed flash memory with DSP and FPU hardware instructions. Customers can select the best fitting device from a range of products, coming in packages from 48 pin to 216 pin and flash memory densities between 256KB and 2MB. The wide operation supply voltage range up to 5.5V which improves the signal to noise ratio, results in a robust design and is unique among Cortex-M4F microcontroller families. The MCUs are designed for applications that require advanced, high-speed computing performance such as general-purpose inverters, servomotors, PLCs and other industrial equipment, as well as inverter-based home appliances such as washing machines and air conditioners.



FM3 FAMILY

Cypress ARM Cortex-M3 microcontroller family is a scalable platform for many industrial applications. Customers can select the best fitting device from a range of products, coming in packages from 32 pin to 176 pin and flash memory densities between 32KB and 1MB. With a maximum CPU frequency of 144MHz and high speed flash memory, FM3 supports the fastest ARM Cortex-M3 devices on the market. The wide operation supply voltage range up to 5.5V, which improves the signal to noise ratio, results in a robust design and is quite unique among Cortex-M3 microcontroller families. The FM3 MCU family is split into four groups: high performance, basic, low power and ultra low leakage groups. The main differences between the groups are CPU operation frequency and supply voltage. All products are based on the same architecture (software compatible), use the same peripherals and are pin compatible in most cases. The ultra low leakage line products are based on an optimized low leakage process technology. Development tools and evaluation boards are offered from different vendors and Cypress.



FM0+ FAMILY

The Cypress FM0+ family, which is based on the ARM Cortex-M0+ core, is designed for low power and cost-sensitive applications such as white goods, sensors, meters, HMI systems, power tools and Internet of Things (IoT) battery powered or energy harvesting wearable devices. These microcontrollers can be easily embedded into systems adopting 8-, 16- or 32-bit MCUs, accelerating product development and reducing development costs. The FM0+ family includes two groups for ultra-low-power and cost-effective applications. The devices in the ultra-low-power group have an operating voltage range of 1.65V to 3.6V, and a maximum CPU clock frequency of 40MHz, a RUN mode current of 70 μ A/MHz, an RTC mode current of 0.7 μ A and wake-up time of approximately 40 μ s.

8FX FAMILY

Cypress 8FX MCU family is a high-performance 8-bit microcontroller utilizing a different embedded flash memory size. This series uses the F2MC-8FX CISC CPU, which offers industry leading class performance of an 8-bit microcontroller unit enabling more instructions to be executed per cycle. On top of delivering industry class performance MCUs, the 8FX family also delivers low power efficient MCU products for the customer's usage. This series also features a variety of on-chip timers, A/D converters, analog and digital peripheral and communication interfaces such as LIN-UART (Local Interconnect Network Universal Asynchronous Receiver-Transmitter), CAN (controller area network) and I2C (Inter-Integrated Circuit) interface for various application usages. For easy development, the 8FX family also employs a 1-line on-chip debug that uses only one pin on the microcontroller, thereby minimizing the number of pins used for debugging in product development. Cypress also provides easy to use and cost competitive development starter kits and development environments for this MCU series.

Automotive MCU Family

TRAVEO FAMILY

The Cypress Traveo™ family expands the company's automotive application coverage, scalability and high performance into one line-up and at the same time adds new features to fulfill the latest requirements of the automotive industry. Based on the powerful ARM® Cortex®-R5 and R5F core in single and dual core operations, it offers state-of-the-art real-time performance, safety and security features.

The family supports the latest in-car networks and offers high performance graphics engines optimized for a minimum memory footprint and embeds dedicated features to increase data security in the car.

High-level Traveo Features

- ARM Cortex-R5 core
- Dual core
- Embedded twin-motor control with internal R/D converter
- Embedded 2D and 3D graphics engines
- High performance embedded flash memory
- Cypress HyperBus™: High speed serial interfaces to connect external memory
- Qualified for automotive use (AEC-Q100)
- Software support for Autosar, graphics drivers and more

FR FAMILY

Cypress 32bit MCU families have been designed in close co-operation with major automotive customers worldwide and inherit the high-performance core of Cypress's proprietary FR MCU architecture. They support communication interfaces such as CAN, FlexRay and LIN as well as up to 2MB on-chip memory capacity. The latest members (MB915xx) also include a single precision Floating Point Unit (FPU) providing additional computing power required by complex control algorithms.

This high computing performance combined with powerful peripheral functions such as on-chip graphics controller and motor control macros, offers a higher grade of flexibility and lower cost for automotive as well as industrial applications.

Many devices offer an external bus interface which can be connected to Cypress's stand alone FlexRay controller or to the latest generation of graphics controllers in order to build full-featured dashboards, driver information systems or advanced body systems.

FCR4 FAMILY

The FCR4 family has been specifically designed to offer an innovative, scalable solution for hybrid instrument clusters, which combine traditional meters and graphical displays. The devices offer a powerful architecture based on the ARM Cortex-R4 core and Cypress's 2D graphics engine.

High-level FCR4 Features

- ARM Cortex-R4 core
- Embedded 2D graphics engine
- 2MB flash, 64KB E2Flash
- Up to 208KB RAM
- Features including real-time clock/auto calibration, sound generator and I2S

F2MC-16FX FAMILY

Cypress 16-bit flexible microcontroller series offers a scalable family concept approach to a variety of automotive and industrial applications. The scalable flash/ROM/RAM sizes with different mixtures of peripherals saves development time and costs. CAN and LIN support, on-chip LCD controller, SMC (stepper motor controller), I²C bus interface, analog input channels, external bus interface, selectable port levels for CMOS, TTL and Automotive Levels are some of the enhanced features. A security feature is incorporated, preventing unauthorized reading of the contents of the flash memory.



FM4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer									Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device						
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]					USB-Function [ch]					
S6E2CC-V	S6E2CCAJGA	200	LQFP-176 BGA-192	2.7 to 5.5	✓	Main Flash +Main Flash	2M	256K	-	8	32	✓	152	-	32 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	3 (2 x CAN + CAN FD)	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC, Eth1ch, Chipher, Voice	On-Chip Debug (SWJ-DP/ETM/ HTM)														
	S6E2CC8JGA		1M				128K																																		
	S6E2CCAJFA		2M				256K																																		
	S6E2CC8JFA		1M				128K																																		
S6E2CC w/ Security	S6E2CCAHHA	200	LQFP-144	2.7 to 5.5	✓	Main Flash +Main Flash	2M	256K	-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	3 (2 x CAN + CAN FD)	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC, Eth1ch, Chipher	On-Chip Debug (SWJ-DP/ETM/ HTM)														
	S6E2CCAJHA		LQFP-176 BGA-192										152																												
	S6E2CCALHA		LQFP-216										190																												
	S6E2CC9HHA		LQFP-144										120																												
	S6E2CC9JHA		LQFP-176 BGA-192				1.5M	192K					152																												
	S6E2CC9LHA		LQFP-216				190																																		
	S6E2CC8HHA		LQFP-144				120																																		
	S6E2CC8JHA		LQFP-176 BGA-192				1M	128K					152																												
S6E2CC8LHA	LQFP-216	190																																							
S6E2CC	S6E2CCAH0A	200	LQFP-144	2.7 to 5.5	✓	Main Flash +Main Flash	2M	256K	-	8	32	✓	120															-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	3 (2 x CAN + CAN FD)	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC, Eth1ch	On-Chip Debug (SWJ-DP/ETM/ HTM)
	S6E2CCAJ0A		LQFP-176 BGA-192										152																												
	S6E2CCAL0A		LQFP-216										190																												
	S6E2CC9H0A		LQFP-144										120																												
	S6E2CC9J0A		LQFP-176 BGA-192				1.5M	196K					152																												
	S6E2CC9L0A		LQFP-216				190																																		
	S6E2CC8H0A		LQFP-144				120																																		
	S6E2CC8J0A		LQFP-176 BGA-192				1M	128K					152																												
S6E2CC8L0A	LQFP-216	190																																							
S6E2C5	S6E2C5AH0A	200	LQFP-144	2.7 to 5.5	✓	Main Flash +Main Flash	2M	256K	-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	3 (2 x CAN + CAN FD)	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC	On-Chip Debug (SWJ-DP/ETM/ HTM)														
	S6E2C5AJ0A		LQFP-176 BGA-192										152																												
	S6E2C5AL0A		LQFP-216										190																												
	S6E2C59H0A		LQFP-144										120																												
	S6E2C59J0A		LQFP-176 BGA-192				1.5M	192K					152																												
	S6E2C59L0A		LQFP-216				190																																		
	S6E2C58H0A		LQFP-144				120																																		
	S6E2C58J0A		LQFP-176 BGA-192				1M	128K					152																												
	S6E2C58L0A		LQFP-216				190																																		

FM4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch](unit)	12bit AD Converter [ch](unit)	DA Converter [bit x ch]	Timer									Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]				
MB9B160R	MB9BF166M	160	LQFP-80	2.7 to 5.5	✓	Main Flash +Work Flash	512K +32K	64K	-	8	16	✓	63	-	16(3)	12 x 2	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	-	-	-	-	✓	Dual Timer, Real Time Clock, DSTC x 128ch, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)							
	80		24(3)																																
	100		16(3)																																
	MB9BF166R		LQFP-120 BGA-144				63	16(3)																											
	MB9BF167M		LQFP-80				80	24(3)																											
	MB9BF167N		LQFP-100 QFP-100 BGA-112				100	16(3)																											
	MB9BF167R		LQFP-120 BGA-144				63	24(3)																											
	MB9BF168M		LQFP-80				80	24(3)																											
	MB9BF168N		LQFP-100 QFP-100 BGA-112				100	24(3)																											
MB9BF168R	LQFP-120 BGA-144	100	24(3)																																
MB9B560L	MB9BF564K	160	LQFP-48 QFN-48	2.7 to 5.5	✓	Main Flash +Work Flash	256K +32K	32K	-	8	15	-	33	-	8(2)	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I ² C/LIN Selectable)	1	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)								
	48		15(2)																																
	MB9BF564L		LQFP-64 QFN-64				16	48			15(2)																								
	MB9BF565K		LQFP-48 QFN-48				15	33			8(2)																								
	MB9BF565L	LQFP-64 QFN-64	16	48	15(2)																														
	MB9BF566K	160	LQFP-48 QFN-48	2.7 to 5.5	✓	Main Flash +Work Flash	512K +32K	64K	-	8	15	-	33	-	8(2)	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I ² C/LIN Selectable)	1	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)								
	48		15(2)																																
	MB9BF566L	LQFP-64 QFN-64	16	48	15(2)																														

FM4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch(unit)]	12bit AD Converter [ch(unit)]	DA Converter [bit x ch]	Timer								Serial				Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device															
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]					USB-Function [ch]														
MB9B460L	MB9BF464K	160	LQFP-48 QFN-48	2.7 to 5.5	✓	Main Flash +Work Flash	256K +32K	32K	-	8	-	-	-	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)								Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	1	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)																	
	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																																																	
	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																																																	
	MB9BF464L		LQFP-64 QFN-64				Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																																											
	MB9BF465K		LQFP-48 QFN-48				384K +32K	48K							-	8	-	-	-	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)													Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	1	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)						
	MB9BF465L		LQFP-64 QFN-64																		Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																													
MB9BF466K	LQFP-48 QFN-48	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																																																
MB9BF466L	LQFP-64 QFN-64	512K +32K	64K	-	8	-	-	-	12 x 2	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)											Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	1	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)																			
Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																																																		
Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																																																		

FM4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer								Serial				Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]				
MB9B360L	MB9BF364K	160	LQFP-48 QFN-48	2.7 to 5.5 2.7 to 5.5	✓	Main Flash +Work Flash	256K +32K	32K	-	8	-	-	-	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)								Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)			
	MB9BF364L		LQFP-64 QFN-64												Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																				
	MB9BF365K		LQFP-48 QFN-48				384K +32K	48K							Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																				
	MB9BF365L		LQFP-64 QFN-64												Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																				
	MB9BF366K		LQFP-48 QFN-48				512K +32K	64K							Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																				
	MB9BF366L		LQFP-64 QFN-64												Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																				

FM4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch(unit)]	12bit AD Converter [ch(unit)]	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device																																	
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]					USB-Host [ch]	USB-Function [ch]																															
MB9B160L	MB9BF164K	160	LQFP-48 QFN-48	2.7 to 5.5	✓	Main Flash +Work Flash	256K +32K	32K	-	8	-	-	-	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)								Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	-	-	-	-	✓	Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)																																		
	MB9BF164L		LQFP-64 QFN-64																																																																
	MB9BF165K		LQFP-48 QFN-48				384K +32K	48K							-	8	-	-	-	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)													Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	-	-	-	-	✓	Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)																							
	MB9BF165L		LQFP-64 QFN-64																																																																
	MB9BF166K		LQFP-48 QFN-48				512K +32K	64K													-	8																							-	-	-	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)								Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	-	-	-	-	✓	Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)
	MB9BF166L		LQFP-64 QFN-64																																																																
MB9BF166L	LQFP-64 QFN-64																																																																		

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [bit]	Ext. Interrupt [bit]	External Bus	Maximum I/O port [bit]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer							Serial				Communication			Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [bit]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [bit]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LN/UART/SIO [ch]	CAN [ch]		
HIGH-PERFORMANCE GROUP																																
MB9B510R	MB9BF512N	144	QFP-100 LQFP-100 BGA-112	2.7 to 5.5	✓	Main Flash +Work Flash	128K +32K	16K	-	8	16	✓	-	16(3)	-	Multi-Function Timer x 3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 3	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	2	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer	On-chip Debug (SWJ-DP/ETM)						
	MB9BF512R		LQFP-120				103																									
	MB9BF514N		QFP-100 LQFP-100 BGA-112				256K +32K	32K																			83					
	MB9BF514R		LQFP-120				103																									
	MB9BF515N		QFP-100 LQFP-100 BGA-112				384K +32K	48K																			83					
	MB9BF515R		LQFP-120				103																									
	MB9BF516N		QFP-100 LQFP-100 BGA-112				512K +32K	64K																			83					
	MB9BF516R		LQFP-120				103																									
MB9B410R	MB9BF412N	144	QFP-100 LQFP-100 BGA-112	2.7 to 5.5	✓	Main Flash +Work Flash	128K +32K	16K	-	8	16	✓	-	16(3)	-	Multi-Function Timer x 3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 3	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	2	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer	On-chip Debug (SWJ-DP/ETM)					
	MB9BF412R		LQFP-120				103																									
	MB9BF414N		QFP-100 LQFP-100 BGA-112				256K +32K	32K																				83				
	MB9BF414R		LQFP-120				103																									
	MB9BF415N		QFP-100 LQFP-100 BGA-112				384K +32K	48K																				83				
	MB9BF415R		LQFP-120				103																									
	MB9BF416N		QFP-100 LQFP-100 BGA-112				512K +32K	64K																				83				
	MB9BF416R		LQFP-120				103																									
MB9B310R	MB9BF312N	144	QFP-100 LQFP-100 BGA-112	2.7 to 5.5	✓	Main Flash +Work Flash	128K +32K	16K	-	8	16	✓	-	16(3)	-	Multi-Function Timer x 3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 3	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer	On-chip Debug (SWJ-DP/ETM)						
	MB9BF312R		LQFP-120				103																									
	MB9BF314N		QFP-100 LQFP-100 BGA-112				256K +32K	32K																			83					
	MB9BF314R		LQFP-120				103																									
	MB9BF315N		QFP-100 LQFP-100 BGA-112				384K +32K	48K																			83					
	MB9BF315R		LQFP-120				103																									
	MB9BF316N		QFP-100 LQFP-100 BGA-112				512K +32K	64K																			83					
	MB9BF316R		LQFP-120				103																									
MB9B110R	MB9BF112N	144	QFP-100 LQFP-100 BGA-112	2.7 to 5.5	✓	Main Flash +Work Flash	128K +32K	16K	-	8	16	✓	-	16(3)	-	Multi-Function Timer x 3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 3	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	-	-	-	-	✓	Dual Timer	On-chip Debug (SWJ-DP/ETM)					
	MB9BF112R		LQFP-120				103																									
	MB9BF114N		QFP-100 LQFP-100 BGA-112				256K +32K	32K																				83				
	MB9BF114R		LQFP-120				103																									
	MB9BF115N		QFP-100 LQFP-100 BGA-112				384K +32K	48K																				83				
	MB9BF115R		LQFP-120				103																									
	MB9BF116N		QFP-100 LQFP-100 BGA-112				512K +32K	64K																				83				

FM3 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [bit]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer								Serial				Communication			Note	Evaluation Device	
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/ISI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]			USB-Function [ch]
BASIC GROUP																																		
MB9B320M	MB9BF321K	72	LQFP-48 QFN-48	2.7 to 5.5	✓	Dual Op. Flash (Main area + Work area)	64K +32K	16K	-	8	14	-	35	-	14(2)	10bit x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	1	QPRC x 1	Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)				-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Unique ID, Real Time Clock	On-chip Debug (SWJ-DP)				
	MB9BF321L		LQFP-64 QFN-64																		19	50	23(2)	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF321M		LQFP-80 BGA-96																		23	65	26(2)	Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF322K		LQFP-48 QFN-48																		14	35	14(2)	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF322L		LQFP-64 QFN-64				19	50			23(2)		256K +32K		32K					14	35	14(2)	QPRC x 1	Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF322M		LQFP-80 BGA-96				23	65			26(2)													Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF324K		LQFP-48 QFN-48				14	35			14(2)													Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF324L		LQFP-64 QFN-64				19	50			23(2)													Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF324M		LQFP-80 BGA-96				23	65			26(2)		Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)																					
MB9B120M	MB9BF121K	72	LQFP-48 QFN-48	2.7 to 5.5	✓	Dual Op. Flash (Main area + Work area)	64K +32K	16K	-	8	14	-	35	-	14(2)	10bit x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	1	QPRC x 1	Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)				-	-	-	-	✓	Dual Timer, Unique ID, Real Time Clock	On-chip Debug (SWJ-DP)			
	MB9BF121L		LQFP-64 QFN-64																		19	50	23(2)	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF121M		LQFP-80 BGA-96																		23	65	26(2)	Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF122K		LQFP-48 QFN-48																		14	35	14(2)	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF122L		LQFP-64 QFN-64				19	50			23(2)		256K +32K		32K					14	35	14(2)	QPRC x 1	Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF122M		LQFP-80 BGA-96				23	65			26(2)													Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF124K		LQFP-48 QFN-48				14	35			14(2)													Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF124L		LQFP-64 QFN-64				19	50			23(2)													Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)										
	MB9BF124M		LQFP-80 BGA-96				23	65			26(2)		Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)																					
MB9B120J	MB9BF121J	72	LQFP-32 QFN-32	2.7 to 5.5	✓	FLASH	64K	8K	-	4	7	-	23	-	8(1)	-	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)				-	-	-	-	✓	Dual Timer, Real Time Clock, Unique ID	On-chip Debug (SW-DP)			
MB9B520T	MB9BF528S*	60	LQFP-144	2.7 to 5.5	✓	Dual Op. Flash (Main area + Work area)	1M +64K	160K	-	8	32	✓	122	-	24(2)	10bit x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)				1	1ch (USB-Host/ USB-Function Selectable)			-	✓	CAN: 32Msg-buffer, Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP/ETM)		
	MB9BF528T*		LQFP-176 BGA-192				154	QPRC x 2																										
	MB9BF529S*		LQFP-144				122	QPRC x 1																										
	MB9BF529T*		LQFP-176 BGA-192				154	QPRC x 2																										
MB9B420T	MB9BF428S*	60	LQFP-144	2.7 to 5.5	✓	Dual Op. Flash (Main area + Work area)	1M +64K	160K	-	8	32	✓	122	-	24(2)	10bit x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)				1	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP/ETM)			
	MB9BF428T*		LQFP-176 BGA-192				154	QPRC x 2																										
	MB9BF429S*		LQFP-144				122	QPRC x 1																										
	MB9BF429T*		LQFP-176 BGA-192				154	QPRC x 2																										

FM3 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAc [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch(unit)]	12bit AD Converter [ch(unit)]	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device			
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]					USB-Host [ch]	USB-Function [ch]	
BASIC GROUP																																					
MB9A310A	MB9AF311LA	40	LQFP-64 QFN-64	2.7 to 5.5	✓	FLASH	64K	16K	-	8	-	51		9(2)	-	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)								Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)				-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer	On-chip Debug (SWJ-DP)	
	MB9AF311MA		LQFP-80								11	66				12(3)	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)																				
	MB9AF311NA		LQFP-100 QFP-100 BGA-112								16	✓				83	16(3)	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)																			
	MB9AF312LA		LQFP-64 QFN-64								8	-				51	9(2)	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)																			
	MB9AF312MA		LQFP-80								11	66				12(3)	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)																				
	MB9AF312NA		LQFP-100 QFP-100 BGA-112								16	✓				83	16(3)	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)																			
	MB9AF314LA		LQFP-64 QFN-64				256K	32K			7	-				51	9(2)	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)																			
	MB9AF314MA		LQFP-80								11	66				12(3)	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)																				
	MB9AF314NA		LQFP-100 QFP-100 BGA-112								16	83				16(3)																					
	MB9AF315MA		LQFP-80								11	66				12(3)																					
	MB9AF315NA		LQFP-100 QFP-100 BGA-112**								16	✓				83																			16(3)		
	MB9AF316MA		LQFP-80								11	66				12(3)																					
	MB9AF316NA		LQFP-100 QFP-100 BGA-112**								512K	16				83	16(3)																				

FM3 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit/AD Converter [ch/unit]	12bit/AD Converter [ch/unit]	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device																	
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]					USB-Host [ch]	USB-Function [ch]															
LOW-POWER GROUP																																																			
MB9A340NA	MB9AF341LB	40	LQFP-64 QFN-64	1.65 to 3.6	✓	Dual Op. Flash (Main area + Work area)	64K +32K	16K	-	8	8	-	51	-	12(2)	-	-	-	-	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I ² C Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	-	-	-	-	Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP)																			
	MB9AF341MB		LQFP-80 BGA-96								11	-	66		17(2)																																				
	MB9AF341NB		LQFP-100 QFP-100 BGA-112								16	✓	83		24(2)																																				
	MB9AF342LB		LQFP-64 QFN-64								8	-	51		12(2)																																				
	MB9AF342MB		LQFP-80 BGA-96				128K +32K	32K			11	-	66	17(2)	-																	-	-	-	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I ² C Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	-	-	-	-	-	-	-	-	Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP/ETM)
	MB9AF342NB		LQFP-100 QFP-100 BGA-112				16				✓	83	24(2)																																						
	MB9AF344LB		LQFP-64 QFN-64				8				-	51	12(2)																																						
	MB9AF344MB		LQFP-80 BGA-96				11				-	66	17(2)																																						
MB9AF344NB	LQFP-100 QFP-100 BGA-112	16	✓	83	24(2)	-	-	-	-	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I ² C Selectable)	-		-	-	-	-	-	-	-	-	-	-	-	Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP/ETM)																							
MB9AF141LB	LQFP-64 QFN-64	8	-	51	12(2)																																														
MB9AF141MB	LQFP-80 BGA-96	11	-	66	17(2)																																														
MB9AF141NB	LQFP-100 QFP-100 BGA-112	16	✓	83	24(2)																																														
MB9AF142LB	LQFP-64 QFN-64	8	-	51	12(2)										-													-	-	-	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I ² C Selectable)	-	-	-	-	-	-	-	-	-	-	-	-	Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP)			
MB9AF142MB	LQFP-80 BGA-96	11	-	66	17(2)																																														
MB9AF142NB	LQFP-100 QFP-100 BGA-112	16	✓	83	24(2)																																														
MB9AF144LB	LQFP-64 QFN-64	8	-	51	12(2)																																														
MB9AF144MB	LQFP-80 BGA-96	11	-	66	17(2)	-	-	-	-	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I ² C Selectable)	-		-	-	-	-	-	-	-	-	-	-	-	Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID																					On-chip Debug (SWJ-DP/ETM)			
MB9AF144NB	LQFP-100 QFP-100 BGA-112	16	✓	83	24(2)																																														

FM3 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [bit]	Ext. Interrupt [bit]	External Bus	Maximum I/O port [bit]	10bit AD Converter [bit(unif)]	12bit AD Converter [bit(unif)]	DA Converter [bit x bit]	Timer							Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [bit]	Free-Run Timer [bit]	Input Capture [bit]	Reload Timer [bit]	PWM Timer [bit]	PWC Timer [bit]	PPG Timer [bit]	Up/Down Counter [bit]	Other timers [bit]	i ² C [bit]	UART/S ⁱ [bit]	SIO [bit]	LIN/UART/SIO [bit]				
ULTRA LOW LEAK GROUP																																	
MB9AAA0N	MB9AFAA1L	20	LQFP-64 QFN-64	1.8 to 5.5	✓	FLASH	64K	12K	-	-	-	-	52	-	9(1)	10bit x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	-	Multi Function Serial x 8ch (UART/CSIO/I ² C Selectable)	-	-	-	24 x 4 or 20 x 8 37 x 4 or 33 x 8 44 x 4 or 40 x 8 24 x 4 or 20 x 8 37 x 4 or 33 x 8 44 x 4 or 40 x 8	✓	HDMI-CEC/Remote Control Reception x 2, Real Time Clock	On-chip Debug (SWJ-DP)					
	MB9AFAA1M		LQFP-80																														
	MB9AFAA1N		LQFP-100 QFP-100																														
	MB9AFAA2L		LQFP-64 QFN-64				128K	16K					11		67														84	9(1)			
	MB9AFAA2M		LQFP-80																														
	MB9AFAA2N		LQFP-100 QFP-100																														
MB9A1A0N	MB9AF1A1L	20	LQFP-64 QFN-64	1.8 to 5.5	✓	FLASH	64K	12K	-	-	-	-	52	-	9(1)	10bit x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	-	Multi Function Serial x 8ch (UART/CSIO/I ² C Selectable)	-	-	-	-	✓	HDMI-CEC/Remote Control Reception x 2, Real Time Clock	On-chip Debug (SWJ-DP)					
	MB9AF1A1M		LQFP-80																														
	MB9AF1A1N		LQFP-100 QFP-100																														
	MB9AF1A2L		LQFP-64 QFN-64				128K	16K					11		67														84	9(1)			
	MB9AF1A2M		LQFP-80																														
	MB9AF1A2N		LQFP-100 QFP-100																														
MB9A130LA	MB9AF131LB	20	LQFP-64 QFN-64	1.8 to 5.5	✓	FLASH	64K	8K	-	-	-	-	37	-	6(1)	-	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	-	Multi Function Serial x 8ch (UART/CSIO/I ² C Selectable)	-	-	-	-	✓	Real Time Clock	On-chip Debug (SWJ-DP)					
	MB9AF131KB		LQFP-48 QFN-48																														
	MB9AF132LB		LQFP-64 QFN-64				128K	6					37		8(1)																		
	MB9AF132KB		LQFP-48 QFN-48																														

FM0 + Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]				
S6E1A	S6E1A11B0A	40	LQFP-32 QFN-32	2.7 to 5.5	✓	Flash	56K	6K	-	2	8	-	23	-	5(1)	-	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 4ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 3ch (UART/CSIO/I ² C/LIN Selectable)	-	-	-	✓	Dual Timer, Real Time Clock, Unique ID, Fast I/O	On-chip Debug (SW-DP/MTB)							
	S6E1A11C0A		LQFP-48 QFN-52 QFN-48				37						8(1)																					
	S6E1A12B0A		LQFP-32 QFN-32				23						5(1)																					
	S6E1A12C0A		LQFP-48 QFP-52 QFN-48				37						8(1)																					
S6E1B8 w/security	S6E1B86GHA	40	LQFP-120	1.65 to 3.6	✓	Main Flash +Work Flash	512K + 40K	64K	-	-	24	-	102	-	24	-	Multi-Function Timer x 1units (Free-Run 3ch/Output Compare 6ch/Input Capture 4ch /PPG3ch/Waveform Generator 3ch /AD Activation Compare 6ch Selectable), PPG3ch	Base Timer x 8ch (Reload/PPG/PWM/PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I2C Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	40 SEG x 8 COM / 44 SEG x 4 COM	-	Dual Timer, Real Timer Clock, Unique ID, DSTC x 64ch, Tiny I2S, HDMI-CEC 2ch, CRC, Smart Card I/F, Chipper	On-Chip Debug (SWJ-DP/ Boundary SCAN)							
	S6E1B84GHA		256K + 40K				32K	32 SEG x 8 COM / 36 SEG x 4 COM																										
	S6E1B86FHA		512K + 40K				64K	20 SEG x 8 COM / 24 SEG x 4 COM																										
	S6E1B84FHA		256K + 40K				32K																											
	S6E1B86EHA		512K + 40K				64K																											
	S6E1B84EHA		256K + 40K				32K																											
S6E1B8	S6E1B86G0A	40	LQFP-120	1.65 to 3.6	✓	Main Flash +Work Flash	512K + 40K	64K	-	-	24	-	102	-	24	-	Multi-Function Timer x 1units (Free-Run 3ch/Output Compare 6ch/Input Capture 4ch /PPG3ch/Waveform Generator 3ch /AD Activation Compare 6ch Selectable), PPG3ch	Base Timer x 8ch (Reload/PPG/PWM/PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I2C Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	40 SEG x 8 COM / 44 SEG x 4 COM	-	Dual Timer, Real Timer Clock, Unique ID, DSTC x 64ch, Tiny I2S, HDMI-CEC 2ch, CRC, Smart Card I/F	On-Chip Debug (SWJ-DP/ Boundary SCAN)							
	S6E1B84G0A		256K + 40K				32K	32 SEG x 8 COM / 36 SEG x 4 COM																										
	S6E1B86F0A		512K + 40K				64K	20 SEG x 8 COM / 24 SEG x 4 COM																										
	S6E1B84F0A		256K + 40K				32K																											
	S6E1B86E0A		512K + 40K				64K																											
	S6E1B84E0A		256K + 40K				32K																											
S6E1B3	S6E1B36G0A	40	LQFP-120	1.65 to 3.6	✓	Main Flash +Work Flash	512K + 40K	64K	-	-	24	-	102	-	24	-	Multi-Function Timer x 1units (Free-Run 3ch/Output Compare 6ch/Input Capture 4ch /PPG3ch/Waveform Generator 3ch /AD Activation Compare 6ch Selectable), PPG3ch	Base Timer x 8ch (Reload/PPG/PWM/PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I2C Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	-	Dual Timer, Real Timer Clock, Unique ID, DSTC x 64ch, Tiny I2S, HDMI-CEC 2ch, CRC, Smart Card I/F	On-Chip Debug (SWJ-DP/ Boundary SCAN)							
	S6E1B34G0A		256K + 40K				32K	-																										
	S6E1B36F0A		512K + 40K				64K	-																										
	S6E1B34F0A		256K + 40K				32K	-																										
	S6E1B36E0A		512K + 40K				64K	-																										
	S6E1B34E0A		256K + 40K				32K	-																										
S6E1B1	S6E1B16G0A	40	LQFP-120	1.65 to 3.6	✓	Main Flash +Work Flash	512K + 40K	64K	-	-	24	-	102	-	24	-	Multi-Function Timer x 1units (Free-Run 3ch/Output Compare 6ch/Input Capture 4ch /PPG3ch/Waveform Generator 3ch /AD Activation Compare 6ch Selectable), PPG3ch	Base Timer x 8ch (Reload/PPG/PWM/PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I2C Selectable)	-	-	-	-	Dual Timer, Real Timer Clock, Unique ID, DSTC x 64ch, Tiny I2S, HDMI-CEC 2ch, CRC, Smart Card I/F	On-Chip Debug (SWJ-DP/ Boundary SCAN)							
	S6E1B14G0A		256K + 40K				32K	-																										
	S6E1B16F0A		512K + 40K				64K	-																										
	S6E1B14F0A		256K + 40K				32K	-																										
	S6E1B16E0A		512K + 40K				64K	-																										
	S6E1B14E0A		256K + 40K				32K	-																										

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [bit]	Ext. Interrupt [bit]	External Bus	Maximum I/O port [bit]	10bit AD Converter [bit(unif)]	12bit AD Converter [bit(unif)]	DA Converter [bit x ch]	Timer					Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device		
																	Output Compare [bit]	Free-Run Timer [bit]	Input Capture [bit]	Reload Timer [bit]	PWM Timer [bit]	PWC Timer [bit]	PPG Timer [bit]	Up/Down Counter [bit]	Other timers [bit]	I ² C [bit]	UART/SI [bit]					SIO [bit]	LINUART/SIO [bit]
LCD CONTROLLERS																																	
MB95610H	MB95F613H	16	LQFP-80	2.4 to 5.5	✓	Dual Op. Flash	12K	512					40	4(1)	-	-	-	Reload Timer x 1ch + 8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	2	-	-	1	2	-	-	-	-	-	-	52 x 4 or 48 x 8	-	Clock Supervisor	On-chip Debug
	MB95F613K								41																								
	MB95F614H						20K	1024	-	-	8	-	40																				
	MB95F614K								41																								
	MB95F616H						36K	1024			40																						
MB95710M	MB95F714J	16	LQFP-80	1.8 to 5.5	✓	Dual Op. Flash	20K	512					75	-	8(1)	-	-	Reload Timer x 1ch + 8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	2	-	-	1	3	-	-	-	-	-	40 x 4 or 36 x 8	-	Clock Supervisor	On-chip Debug	
	MB95F714M								74																								
	MB95F716J						36K	1K	-	-	8	-	75																				
	MB95F716M								74																								
	MB95F718J						60K	2K			75																						
MB95770M	MB95F774J	16	LQFP-64	1.8 to 5.5	✓	Dual Op. Flash	20K	512					59	-	8(1)	-	-	Reload Timer x 1ch + 8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	2	-	-	1	3	-	-	-	-	-	32 x 4 or 28 x 8	-	Clock Supervisor	On-chip Debug	
	MB95F774M								58																								
	MB95F776J						36K	1K	-	-	8	-	59																				
	MB95F776M								58																								
	MB95F778J						60K	2K			59																						
INVERTER																																	
MB95630H	MB95F632H	16	LQFP-32 SH-DIP-32 QFN-32	2.4 to 5.5	✓	Dual Op. Flash	8K	256					28	8(1)	-	-	-	Reload Timer x 1ch + 8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	3	-	1	1	1	-	1	-	-	-	-	-	✓	Low-voltage Detection Reset, Multi-pulse Generator (Reload/PPG/Waveform Sequencer), Clock Supervisor	On-chip Debug
	MB95F632K								29																								
	MB95F633H						12K	512			28																						
	MB95F633K								29																								
	MB95F634H						20K			28																							
	MB95F634K								29																								
	MB95F636H								28																								
MB95690K	MB95F636K			29																													
	MB95F694K	16	LQFP-44 LQFP-48 LQFP-52 QFN-48	2.88 to 5.5	✓	Dual Op. Flash	20K	512				45	12(1) LQFP44 only: 41	-	-	-	Reload Timer x 1ch + 8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	3	-	1	1	1	-	1	-	-	-	-	✓	Low-voltage Detection Reset, Multi-pulse Generator (Reload/PPG/Waveform Sequencer), Clock Supervisor	On-chip Debug		
	MB95F696K						36K	1K			45																						
	MB95F698K						60K	2K			45																						
STANDARD																																	
MB95560H	MB95F562H	16	SOP-20 TSSOP-20 QFN-32	2.4 to 5.5	✓	Dual Op. Flash	8K	240					16	6(1)	-	-	-	8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	-	-	-	-	-	-	1	-	-	-	-	-	-	Clock Supervisor	On-chip Debug
	MB95F562K								17																								
	MB95F563H						12K	496	-	-	6	-	16																				
	MB95F563K								17																								
	MB95F564H						20K			16																							
MB95570H	MB95F572H	16	SOP-8	2.4 to 5.5	✓	Dual Op. Flash	8K	240					4	2(1)	-	-	-	8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	-	-	-	-	-	-	-	-	-	-	-	-	-	Clock Supervisor	On-chip Debug
	MB95F572K								5																								
	MB95F573H						12K	496	-</																								

8FX – 8bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer								Serial		Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device	
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SO [ch]	LIN/UART/SO [ch]					CAN [ch]
STANDARD																																		
MB95650L	MB95F652E	16	TSSOP-24 SOP-24 QFN-32	1.8 to 5.5	✓	Dual Op. Flash	8K	256	-	-	6	-	21	-	6(1)	-	-	8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	-	-	-	-	2	1	-	1	-	-	-	-	-	-	Low-voltage Detection Reset, Clock Supervisor	On-chip Debug
	MB95F652L							20																										
	MB95F653E						12K	512					21																					
	MB95F653L							20																										
	MB95F654E							21																										
	MB95F654L						20K	20																										
	MB95F656E							21																										
	MB95F656L							20																										
MB95810K	MB95F814K	16	LQFP-64	2.88 to 5.5	✓	Dual Op. Flash	20K	512	-	-	12	-	58	12(1)	-	-	-	Reload Timer x 1ch + 8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	4	-	-	-	1	1	-	1	-	-	-	-	Low-voltage Detection Reset, Clock Supervisor	On-chip Debug		
	MB95F816K						36K	1K																										
	MB95F818K						60K	2K																										

Traveo Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	12bit AD Converter [ch/unit]	12bit AD Converter with 4ch sample & hold	DA Converter [bit x ch]	Timer										Serial		Communication		LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I2C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]				
CAN/AUTOMOTIVE																																		
S6J3110	S6J3118HA	96	TEQFP -144	4.5 to 5.25	-	Main Flash +Work Flash	576K + 48K	TC-RAM: 32KB System - RAM: 16KB Backup - RAM: 8KB	56(2)	Instruction: 16 Data: 16	16	16	-	116	-	-	12	6	12	16bit Base Timer x 30ch (PWM/PPG/Reload/PWC Selectable)	-	RTC x 1ch	Multi Function Serial x 4ch (LIN/UART/SIO Selectable)	CAN - FD x 1ch	-	-	-	-	ARM Cortex-R5, SHE(Secure Hardware Extension),	On-Chip Debug				
	S6J3119HA						832K + 48K	TC-RAM: 48KB System - RAM: 16KB Backup - RAM: 8KB																										
	S6J311AHA						1088K + 48K	TC-RAM: 64KB System - RAM: 16KB Backup - RAM: 8KB																										
	S6J311BHA	144	TEQFP -176				1600K + 112K	192K	64(2)					Multi Function Serial x 22ch (LIN/UART/SIO Selectable)									CAN - FD x 2ch											
	S6J311CHA						2112K + 112K	256K																										
	S6J311DHA						3136K + 112K	320K																										
	S6J311EHA						4160K + 112K	TC-RAM: 64KB System - RAM: 256KB Backup - RAM: 64KB																										
	S6J311BJA	1600K + 112K	192K				150																											
	S6J311CJA	2112K + 112K	256K																															
	S6J311DJA	3136K + 112K	320K																															
	S6J311EJA	4160K + 112K	TC-RAM: 64KB System - RAM: 256KB Backup - RAM: 64KB																															

FCR4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer										Serial		Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I2C [ch]	UART/SPI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]				
HYBRID AUTOMOTIVE INSTRUMENTS CLUSTER																																			
MB9DF125	MB9DF125PMC	128	LQFP-176	1.1 to 1.3 3.0 to 5.5	✓	FLASH	1088	128	8	8	32	-	123	50(1)	-	-	8	8	8	10	-	-	24	2	-	1	2	3	2	2	-	-	-	ARM Cortex R4, SHE (Secure Hardware Extension), Real Time Clock, Stepper Motor Controller (SMC): 4 ch, Data Flash: 48KB, Windows Watchdog, Clock supervisor, Sound Generator, I2S: 2 ch, Quad SPI Flash Interface: 1 ch, NMI (intern/extern): 32/1 ch, CRC Hardware Module: 1 ch, Protection Unit: MPU, PPU, TPU, various Power Down modes	On-chip Debug
	MB9DF125EPMC																																ARM Cortex R4, SHE (Secure Hardware Extension), Real Time Clock, Stepper Motor Controller (SMC): 6 ch, Data Flash: 48KB, Windows Watchdog, Clock supervisor, Sound Generator, I2S: 2 ch, Quad SPI Flash Interface: 1 ch, NMI (intern/extern): 32/1 ch, CRC Hardware Module: 1 ch, Protection Unit: MPU, PPU, TPU, various Power Down modes	On-chip Debug	
MB9DF126	MB9DF126BPMC	128	LQFP-176	1.1 to 1.3 3.0 to 5.5	✓	FLASH	2176	208	16	8	32	-	110	50(1)	-	-	8	8	8	10	-	-	24	2	-	1	2	3	2	3	-	-	-	ARM Cortex R4, APIX Remote handler with 2 ch AIC (APIX Inter Connect), APIX1 Phy: 1 ch, Real Time Clock, Stepper Motor Controller (SMC): 6 ch, Data Flash: 64KB, Windows Watchdog, Clock supervisor, Sound Generator, I2S: 2 ch, Quad SPI Flash Interface: 1 ch, NMI (intern/extern): 32/1 ch, CRC Hardware Module: 1 ch, Protection Unit: MPU, PPU, TPU, various Power Down modes	On-chip Debug
MB9EF226	MB9EF226PMC	128	LQFP-176	1.1 to 1.3 3.0 to 5.5	✓	FLASH	2176	128	16	8	32	-	117	50(1)	-	-	8	8	8	10	-	-	24	2	-	1	2	3	2	2	-	-	-	ARM Cortex R4, 2D Graphics Engine: scaler, color palette, gamma correction, blending, raster operation, various alpha blending modes, run-length decoding, hor/ver flip and rotation, affine transformations, Embedded Video-RAM: 1MB, TFT Output Interface: RGB888/RSDS Output, SHE (Secure Hardware Extension), Real Time Clock, Stepper Motor Controller (SMC): 4 ch, Data Flash: 48KB, Windows Watchdog, Clock supervisor, Sound Generator, I2S: 2 ch, Quad SPI Flash Interface: 2 ch(1 ch for MCU and 1 ch for Graphic), NMI (intern/extern): 32/1 ch, MediaLB (3 wire): 1 ch, CRC Hardware Module: 1 ch, Protection Unit: MPU, PPU, TPU, various Power Down modes	On-chip Debug
	MB9EF226EPMC																																	ARM Cortex R4, 2D Graphics Engine: scaler, color palette, gamma correction, blending, raster operation, various alpha blending modes, run-length decoding, hor/ver flip and rotation, affine transformations, Embedded Video-RAM: 1MB, TFT Output Interface: RGB888/RSDS Output, SHE (Secure Hardware Extension), Real Time Clock, Stepper Motor Controller (SMC): 6 ch, Data Flash: 48KB, Windows Watchdog, Clock supervisor, Sound Generator, I2S: 2 ch, Quad SPI Flash Interface: 2 ch(1 ch for MCU and 1 ch for Graphic), NMI (intern/extern): 32/1 ch, MediaLB (3 wire): 1 ch, CRC Hardware Module: 1 ch, Protection Unit: MPU, PPU, TPU, various Power Down modes	On-chip Debug

Series Name		Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub-Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer							Serial			Communication		Note	Evaluation Device																						
																		Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]			LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]	USB-Function [ch]	LCD Controller [seg x com]	Three-phase Inverter																
CAN/AUTOMOTIVE																																																					
MB91520	MB91F522B	LQFP-64	80	2.7 to 5.5	Main Flash +Work Flash	320K+64K	56K	-	16	16	-	44	13(1) 13(1)	8bit x 1	16bit x 6 32bit x 4	16bit x 4 32bit x 5	Reload Timer x 7ch + PPG Timer x 21ch (Reload/PPG/PWM/PWC Selectable)	2	-	Multi Function Serial x 8ch (LIN/UART/SIO/I2C Selectable)			3	-	-	-	✓	LIN, FPU, MPU, Tuning RAM MB91520B/D/F/J/K/L series: CAN: 64Msg-buffer x 2ch, 128Msg-buffer x 1ch, MB91520R/U/M/Y series: CAN: 128Msg-buffer x 6ch, FlexRay: 1 unit Details of part number suffix <table border="1"><tr><td></td><td colspan="2">Dual clock system</td></tr><tr><td></td><td>xWC</td><td>xJC</td></tr><tr><td>CSV initial value</td><td>ON</td><td>OFF</td></tr></table> <table border="1"><tr><td></td><td colspan="2">Single clock system</td></tr><tr><td></td><td>xSC</td><td>xHC</td></tr><tr><td>CSV initial value</td><td>ON</td><td>OFF</td></tr></table>		Dual clock system			xWC	xJC	CSV initial value	ON	OFF		Single clock system			xSC	xHC	CSV initial value	ON	OFF	On-chip Debug						
						Dual clock system																																															
						xWC	xJC																																														
	CSV initial value					ON	OFF																																														
						Single clock system																																															
						xSC	xHC																																														
	CSV initial value					ON	OFF																																														
	MB91F523B					448K+64K											16(1) 16(1)			16bit x 3 32bit x 2	16bit x 3 32bit x 2	16bit x 4 32bit x 6							Reload Timer x 7ch + PPG Timer x 27ch + Base Timer x 1ch (Reload/PPG/PWM/PWC Selectable)	Multi Function Serial x 9ch (LIN/UART/SIO/I2C Selectable)																							
	MB91F524B					576K+64K	72K																						16(1) 21(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6	Reload Timer x 8ch + PPG Timer x 34ch + Base Timer x 1ch (Reload/PPG/PWM/PWC Selectable)	Multi Function Serial x 12ch (LIN/UART/SIO/I2C Selectable)																			
	MB91F525B					832K+64K	104K																										16(1) 32(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6	Reload Timer x 8ch + PPG Timer x 38ch + Base Timer x 2ch (Reloa d/PPG/PWM/ PWC Selectable)	Multi Function Serial x 12ch (LIN/UART/SIO/I2C Selectable)															
	MB91F526B					1088K+64K	136K																														16(1) 32(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6	Reload Timer x 8ch + PPG Timer x 44ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	Multi Function Serial x 12ch (LIN/UART/SIO/I2C Selectable)											
	MB91F522D					320K+64K	56K																																		16(1) 32(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6	Reload Timer x 8ch + PPG Timer x 48ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	Multi Function Serial x 20ch (LIN/UART/SIO/I2C Selectable)							
	MB91F523D	448K+64K	56K	16(1) 32(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6	Reload Timer x 8ch + PPG Timer x 48ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	Multi Function Serial x 20ch (LIN/UART/SIO/I2C Selectable)																																												
	MB91F524D	576K+64K	72K					16(1) 32(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6	Reload Timer x 8ch + PPG Timer x 48ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	Multi Function Serial x 20ch (LIN/UART/SIO/I2C Selectable)																																								
	MB91F525D	832K+64K	104K									16(1) 32(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6	Reload Timer x 8ch + PPG Timer x 48ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)		Multi Function Serial x 20ch (LIN/UART/SIO/I2C Selectable)																																			
	MB91F526D	1088K+64K	136K													16(1) 32(1)		16bit x 6 32bit x 6	16bit x 3 32bit x 3				16bit x 4 32bit x 6	Reload Timer x 8ch + PPG Timer x 48ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	Multi Function Serial x 20ch (LIN/UART/SIO/I2C Selectable)																												
	MB91F522F	320K+64K	56K																					16(1) 32(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6																		Reload Timer x 8ch + PPG Timer x 48ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	Multi Function Serial x 20ch (LIN/UART/SIO/I2C Selectable)							
	MB91F523F	448K+64K	56K																																										16(1) 32(1)	16bit x 6 32bit x 6		16bit x 3 32bit x 3	16bit x 4 32bit x 6	Reload Timer x 8ch + PPG Timer x 48ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	Multi Function Serial x 20ch (LIN/UART/SIO/I2C Selectable)		
	MB91F524F	576K+64K	72K																																															16(1) 32(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6
	MB91F525F	832K+64K	104K														16(1) 32(1)			16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6																															
	MB91F526F	1088K+64K	136K																										16(1) 32(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6																					
	MB91F522J	320K+64K	56K																														16(1) 32(1)	16bit x 6 32bit x 6	16bit x 3 32bit x 3	16bit x 4 32bit x 6																	
	MB91F523J	448K+64K																																																			

FR Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch(unt)]	12bit AD Converter [ch(unt)]	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]				
CAN/AUTOMOTIVE																																		
MB91590	MB91F591B	80	LQFP-208	3.0 to 3.6 4.5 to 5.5 (2 power supplies)	Main Flash +Work Flash	Dedicated for GDC External Memory	576K +64K	48K	-	16	16	32(1)	-	-	4	2	6	Reload Timer x 4ch + PPG Timer x 24ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	-	Multi Function Serial x 2ch (LIN/UART/ SIO/I2C Selectable)	6	3	-	-	-	-	CAN: 32/64Mseg-buffer, LIN, FPU, MPU, Sound generator, SMC x 6ch, From among the RAM, 8KB can be used as BackUpRAM, Built-in 2D GDC	On-chip Debug						
	MB91F591BS																																	
	MB91F591BH																																	
	MB91F591BHS																																	
	MB91F592B																																	
	MB91F592BS																																	
	MB91F592BH																																	
	MB91F592BHS																																	
	MB91F594B	128	BGA-320				1088K +64K	72K							264K	4	8	12	Reload Timer x 8ch + PPG Timer x 24ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	3	Multi Function Serial x 6ch (LIN/UART SIO/I2C Selectable. However, I2C only supports ch0/ ch1)													
	MB91F594BS																																	
	MB91F594BH																																	
	MB91F594BHS																																	
	MB91F59AC																																	
	MB91F59ACS																																	
	MB91F59ACH																																	
	MB91F59ACHS																																	
MB91F59BC	2112K +64K	264K	61	63	61	63	61	63	61	63	61	63																						
MB91F59BCS																																		
MB91F59BCH																																		
MB91F59BCHS																																		

F²MC-16FX – 16bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch(unit)]	12bit AD Converter [ch(unit)]	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device	
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SO [ch]	LIN/UART/SIO [ch]	CAN [ch]					USB-Host [ch]
AUTOMOTIVE																																			
MB96310	MB96F313AS	56	LQFP-48	3.0 to 5.5	-	FLASH	96K	8K	-	4	11	-	36	12(1)	-	-	2	4	4 +3 (Dedicated for LIN)	4 +1 (Dedicated for PPG)	-	-	14	-	-	-	-	-	3	-	-	-	-	LVD, built-in CR Option without CAN	MB96V300C
	✓				34																									1					
	-				36																									-					
	✓				34																									-					
	MB96F313AW				✓		36																							-					
	MB96F315AS				✓		34																							-					
	MB96F315AW				✓		36																							-					
	MB96F315RS				✓		36																							1					
MB96F315RW	✓	34	-																																
MB96320	MB96F326AS	56	LQFP-80	3.0 to 5.5	-	FLASH	288K	12K	-	4	15	✓	66	18(1)	-	-	6	4	12	4 +1 (Dedicated for PPG)	-	-	20	-	-	1	-	-	4	-	-	-	-	LVD, built-in CR Option without CAN	MB96V300C
	✓				64								-																						
	MB96F326AW				✓								66																	2					
	MB96F326RS				✓								66																	-					
	MB96F326RW				✓								64																	-					
MB96330	MB96F336US	48	LQFP-144	3.0 to 5.5	-	FLASH	288K	24K	-	10	16	✓	124	36(1)	-	-	12	4	10	4 +1 (Dedicated for PPG)	-	-	20	-	-	2	-	-	8	1	1ch (USB-Host/ USB-Function Selectable)	-	-	LVD, built-in CR	MB96V300C
	✓				122								-																						
	MB96F338RS				✓		124	3					1ch (USB-Host/ USB-Function Selectable)																						
	MB96F338RW				✓		122																												
	MB96F338US				✓		120																												
	MB96F338UW				✓		118																												

