



Welcome to [E-XFL.COM](https://www.e-xfl.com)

What is "[Embedded - Microcontrollers](#)"?


"[Embedded - Microcontrollers](#)" refer to small, integrated circuits designed to perform specific tasks within larger systems. These microcontrollers are essentially compact computers on a single chip, containing a processor core, memory, and programmable input/output peripherals. They are called "embedded" because they are embedded within electronic devices to control various functions, rather than serving as standalone computers. Microcontrollers are crucial in modern electronics, providing the intelligence and control needed for a wide range of applications.

Applications of "[Embedded - Microcontrollers](#)"

Details

Product Status	Obsolete
Core Processor	F ² MC-8FX
Core Size	8-Bit
Speed	16MHz
Connectivity	I ² C, LINbus, SIO, UART/USART
Peripherals	LVD, POR, PWM, WDT
Number of I/O	58
Program Memory Size	60KB (60K x 8)
Program Memory Type	FLASH
EEPROM Size	-
RAM Size	2K x 8
Voltage - Supply (Vcc/Vdd)	2.88V ~ 5.5V
Data Converters	A/D 12x8/10b
Oscillator Type	External
Operating Temperature	-40°C ~ 85°C (TA)
Mounting Type	Surface Mount
Package / Case	64-LQFP
Supplier Device Package	64-LQFP (10x10)
Purchase URL	https://www.e-xfl.com/product-detail/infineon-technologies/mb95f818kpmc1-g-snk1e2

Consumer and Industrial MCU Core Roadmap



FM4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer								Serial				Communication			Note	Evaluation Device													
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/ISI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]			USB-Function [ch]	LCD Controller [seg x com]	Three-phase Inverter										
S6E2C4	S6E2C4AH0A	200	LQFP-144	2.7 to 5.5	✓	Main Flash +Main Flash	2M	256K	-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	3 (2 x CAN + CAN FD)	-	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC	On-Chip Debug (SWJ-DP/ETM/HTM)																			
	S6E2C4AJ0A		LQFP-176 BGA-192																																											
	S6E2C4AL0A		LQFP-216																																											
	S6E2C49H0A		LQFP-144																																											
	S6E2C49J0A		LQFP-176 BGA-192				1M	128K																				-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC	On-Chip Debug (SWJ-DP/ETM/HTM)
	S6E2C49L0A		LQFP-216																																											
	S6E2C48H0A		LQFP-144																																											
	S6E2C48J0A		LQFP-176 BGA-192																																											
S6E2C48L0A	LQFP-216	1M	128K	-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC	On-Chip Debug (SWJ-DP/ETM/HTM)																								
S6E2C3AJ0A	LQFP-176 BGA-192																																													
S6E2C3AL0A	LQFP-216																																													
S6E2C39H0A	LQFP-144																																													
S6E2C39J0A	LQFP-176 BGA-192	1M	128K																				-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC	On-Chip Debug (SWJ-DP/ETM/HTM)					
S6E2C39L0A	LQFP-216																																													
S6E2C38H0A	LQFP-144																																													
S6E2C38J0A	LQFP-176 BGA-192																																													
S6E2C38L0A	LQFP-216	1M	128K	-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC, Eth1ch, Chipher	On-Chip Debug (SWJ-DP/ETM/HTM)																								
S6E2C2AHHA	LQFP-144																																													
S6E2C2AJHA	LQFP-176 BGA-192																																													
S6E2C2ALHA	LQFP-216																																													
S6E2C29HHA	LQFP-144	1M	128K																				-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC, Eth1ch, Chipher	On-Chip Debug (SWJ-DP/ETM/HTM)					
S6E2C29JHA	LQFP-176 BGA-192																																													
S6E2C29LHA	LQFP-216																																													
S6E2C28HHA	LQFP-144																																													
S6E2C28JHA	LQFP-176 BGA-192	1M	128K	-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC, Eth1ch	On-Chip Debug (SWJ-DP/ETM/HTM)																								
S6E2C28LHA	LQFP-216																																													
S6E2C2AH0A	LQFP-144																																													
S6E2C2AJ0A	LQFP-176 BGA-192																																													
S6E2C2AL0A	LQFP-216	1M	128K																				-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC, Eth1ch	On-Chip Debug (SWJ-DP/ETM/HTM)					
S6E2C29H0A	LQFP-144																																													
S6E2C29J0A	LQFP-176 BGA-192																																													
S6E2C29L0A	LQFP-216																																													
S6E2C28H0A	LQFP-144	1M	128K	-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	2ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC, Eth1ch	On-Chip Debug (SWJ-DP/ETM/HTM)																								
S6E2C28J0A	LQFP-176 BGA-192																																													
S6E2C28L0A	LQFP-216																																													
S6E2C1AH0A	LQFP-144																																													
S6E2C1AJ0A	LQFP-176 BGA-192	2M	256K																				-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	-	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC	On-Chip Debug (SWJ-DP/ETM/HTM)					
S6E2C1AL0A	LQFP-216																																													
S6E2C19H0A	LQFP-144																																													
S6E2C19J0A	LQFP-176 BGA-192																																													
S6E2C19L0A	LQFP-216	1M	128K	-	8	32	✓	120	-	24 (3)	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	-	-	✓	Dual Timer, Real Timer Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC	On-Chip Debug (SWJ-DP/ETM/HTM)																								
S6E2C18H0A	LQFP-144																																													
S6E2C18J0A	LQFP-176 BGA-192																																													
S6E2C18L0A	LQFP-216																																													

FM4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DAC Converter [bit x ch]	Timer								Serial				Communication			Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]			
S6E2C1-E	S6E2C10H2A	200	LQFP-144	2.7 to 5.5	✓	-	0M	256K	-	8	32	✓	120	-	152	12 x 2	Multi-Function Timer x3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable), PPG 9ch	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 4	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	-	-	✓	Dual Timer, Real Time Clock, Unique ID, DSTC x 256ch, SDC, I2S 1ch(without 144pin), HDMI-CEC 2ch, High Speed Quad SPI x1(without 144pin), Programmable CRC, Chipher	On-Chip Debug (SWJ-DP/ETM/ HTM)							
	S6E2C10J2A		LQFP-176 BGA-192																															
	S6E2C10L2A		LQFP-216																															
MB9B560R	MB9BF566M	160	LQFP-80	2.7 to 5.5	✓	Main Flash +Work Flash	512K +32K	64K	-	8	16	✓	63	16(3)	12 x 2	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)	2	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, DSTC x 128ch, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)								
	MB9BF566N		LQFP-100 QFP-100 BGA-112																								80	24(3)						
	MB9BF566R		LQFP-120 BGA-144																								100	16(3)						
	MB9BF567M		LQFP-80				63	16(3)					80	24(3)			100	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)	2	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, DSTC x 128ch, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)								
	MB9BF567N		LQFP-100 QFP-100 BGA-112				63	16(3)																										
	MB9BF567R		LQFP-120 BGA-144				100	24(3)																										
	MB9BF568M		LQFP-80				63	16(3)					80	24(3)			100	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)	2	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, DSTC x 128ch, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)								
	MB9BF568N		LQFP-100 QFP-100 BGA-112				63	16(3)																										
	MB9BF568R		LQFP-120 BGA-144				100	24(3)																										
MB9B460R	MB9BF466M	160	LQFP-80	2.7 to 5.5	✓	Main Flash +Work Flash	512K +32K	64K	-	8	16	✓	63	16(3)	12 x 2	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)	2	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, DSTC x 128ch, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)							
	MB9BF466N		LQFP-100 QFP-100 BGA-112																									80	24(3)					
	MB9BF466R		LQFP-120 BGA-144																									100	16(3)					
	MB9BF467M		LQFP-80				63	16(3)					80	24(3)			100	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)	2	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, DSTC x 128ch, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)							
	MB9BF467N		LQFP-100 QFP-100 BGA-112				63	16(3)																										
	MB9BF467R		LQFP-120 BGA-144				100	24(3)																										
	MB9BF468M		LQFP-80				63	16(3)					80	24(3)			100	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)	2	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, DSTC x 128ch, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)							
	MB9BF468N		LQFP-100 QFP-100 BGA-112				63	16(3)																										
	MB9BF468R		LQFP-120 BGA-144				100	24(3)																										
MB9B360R	MB9BF366M	160	LQFP-80	2.7 to 5.5	✓	Main Flash +Work Flash	512K +32K	64K	-	8	16	✓	63	16(3)	12 x 2	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Time Clock, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)								
	MB9BF366N		LQFP-100 QFP-100 BGA-112																								80	24(3)						
	MB9BF366R		LQFP-120 BGA-144																								100	16(3)						
	MB9BF367M		LQFP-80				63	16(3)					80	24(3)			100	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Time Clock, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)								
	MB9BF367N		LQFP-100 QFP-100 BGA-112				63	16(3)																										
	MB9BF367R		LQFP-120 BGA-144				100	24(3)																										
	MB9BF368M		LQFP-80				63	16(3)					80	24(3)			100	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Time Clock, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)								
	MB9BF368N		LQFP-100 QFP-100 BGA-112				63	16(3)																										
	MB9BF368R		LQFP-120 BGA-144				100	24(3)																										

FM4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch](unit)]	12bit AD Converter [ch](unit)]	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/ISI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]				
MB9B160R	MB9BF166M	160	LQFP-80	2.7 to 5.5	✓	Main Flash +Work Flash	512K +32K	64K	-	8	16	✓	63	-	16(3)	12 x 2	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	-	-	-	-	✓	Dual Timer, Real Time Clock, DSTC x 128ch, Unique ID, SD Card I/F	On-chip Debug (SWJ-DP/ETM)						
	MB9BF166N		LQFP-100 QFP-100 BGA-112																										63	-	24(3)			
	MB9BF166R		LQFP-120 BGA-144																															
	MB9BF167M		LQFP-80				80	-					24(3)																					
	MB9BF167N		LQFP-100 QFP-100 BGA-112											100																				
	MB9BF167R		LQFP-120 BGA-144																															
	MB9BF168M		LQFP-80				63	-					16(3)																					
	MB9BF168N		LQFP-100 QFP-100 BGA-112											80																				
	MB9BF168R		LQFP-120 BGA-144												100																			
MB9B560L	MB9BF564K	160	LQFP-48 QFN-48	2.7 to 5.5	✓	Main Flash +Work Flash	256K +32K	32K	-	8	15	-	33			-	8(2)	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I ² C/LIN Selectable)	1	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)					
	MB9BF564L		LQFP-64 QFN-64											16																48	15(2)			
	MB9BF565K		LQFP-48 QFN-48				15	33			8(2)																							
	MB9BF565L		LQFP-64 QFN-64									384K +32K	48K	16	48		15(2)																	
	MB9BF566K	160	LQFP-48 QFN-48	2.7 to 5.5	✓	Main Flash +Work Flash	512K +32K	64K	-	8	15					-		33	-	8(2)	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I ² C/LIN Selectable)	1	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)		
	MB9BF566L		LQFP-64 QFN-64									16	48	15(2)																				

FM4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch(unit)]	12bit AD Converter [ch(unit)]	DA Converter [bit x ch]	Timer									Serial				Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device															
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]	USB-Function [ch]																			
MB9B460L	MB9BF464K	160	LQFP-48 QFN-48	2.7 to 5.5	✓	Main Flash +Work Flash	256K +32K	32K	-	8	-	-	-	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)									Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	1	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)																	
	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																																																		
	MB9BF464L		LQFP-64 QFN-64				Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																																												
	MB9BF465K		LQFP-48 QFN-48				384K +32K	48K							-	8	-	-	-	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)														Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	1	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)						
	MB9BF465L		LQFP-64 QFN-64																		Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																														
	MB9BF466K		LQFP-48 QFN-48				512K +32K	64K													Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																									Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	1	-
MB9BF466L	LQFP-64 QFN-64	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																																																	

FM4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer								Serial				Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]				
MB9B360L	MB9BF364K	160	LQFP-48 QFN-48	2.7 to 5.5 2.7 to 5.5	✓	Main Flash +Work Flash	256K +32K	32K	-	8	-	-	-	12 x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)								Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 6ch (UART/CSIO/I2C/LIN Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, Real Time Clock, Unique ID, DSTC x 128ch	On-chip Debug (SWJ-DP)			
	MB9BF364L		LQFP-64 QFN-64												Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																				
	MB9BF365K		LQFP-48 QFN-48												Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																				
	MB9BF365L		LQFP-64 QFN-64				384K +32K	48K							Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																				
	MB9BF366K		LQFP-48 QFN-48												Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																				
	MB9BF366L		LQFP-64 QFN-64												Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 6ch Selectable)																				

FM3 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer									Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI ² C [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]				
HIGH-PERFORMANCE GROUP																																			
MB9B510R	MB9BF512N	144	QFP-100 LQFP-100 BGA-112	2.7 to 5.5	✓	Main Flash +Work Flash	128K +32K	16K	-	8	16	✓	83	-	16(3)	-	Multi-Function Timer x 3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 3	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	2	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer	On-chip Debug (SWJ-DP/ETM)								
	MB9BF512R		LQFP-120				103																												
	MB9BF514N		QFP-100 LQFP-100 BGA-112				256K +32K	32K					83																						
	MB9BF514R		LQFP-120				103																												
	MB9BF515N		QFP-100 LQFP-100 BGA-112				384K +32K	48K					83																						
	MB9BF515R		LQFP-120				103																												
	MB9BF516N		QFP-100 LQFP-100 BGA-112				512K +32K	64K					83																						
	MB9BF516R		LQFP-120				103																												
MB9B410R	MB9BF412N	144	QFP-100 LQFP-100 BGA-112	2.7 to 5.5	✓	Main Flash +Work Flash	128K +32K	16K	-	8	16	✓	83	-	16(3)	-	Multi-Function Timer x 3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 3	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	2	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer	On-chip Debug (SWJ-DP/ETM)							
	MB9BF412R		LQFP-120				103																												
	MB9BF414N		QFP-100 LQFP-100 BGA-112				256K +32K	32K					83																						
	MB9BF414R		LQFP-120				103																												
	MB9BF415N		QFP-100 LQFP-100 BGA-112				384K +32K	48K					83																						
	MB9BF415R		LQFP-120				103																												
	MB9BF416N		QFP-100 LQFP-100 BGA-112				512K +32K	64K					83																						
	MB9BF416R		LQFP-120				103																												
MB9B310R	MB9BF312N	144	QFP-100 LQFP-100 BGA-112	2.7 to 5.5	✓	Main Flash +Work Flash	128K +32K	16K	-	8	16	✓	83	-	16(3)	-	Multi-Function Timer x 3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 3	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer	On-chip Debug (SWJ-DP/ETM)								
	MB9BF312R		LQFP-120				103																												
	MB9BF314N		QFP-100 LQFP-100 BGA-112				256K +32K	32K					83																						
	MB9BF314R		LQFP-120				103																												
	MB9BF315N		QFP-100 LQFP-100 BGA-112				384K +32K	48K					83																						
	MB9BF315R		LQFP-120				103																												
	MB9BF316N		QFP-100 LQFP-100 BGA-112				512K +32K	64K					83																						
	MB9BF316R		LQFP-120				103																												
MB9B110R	MB9BF112N	144	QFP-100 LQFP-100 BGA-112	2.7 to 5.5	✓	Main Flash +Work Flash	128K +32K	16K	-	8	16	✓	83	-	16(3)	-	Multi-Function Timer x 3units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 3	1	Multi Function Serial x 8ch (UART/CSIO/I ² C/LIN Selectable)	-	-	-	-	✓	Dual Timer	On-chip Debug (SWJ-DP/ETM)							
	MB9BF112R		LQFP-120				103																												
	MB9BF114N		QFP-100 LQFP-100 BGA-112				256K +32K	32K					83																						
	MB9BF114R		LQFP-120				103																												
	MB9BF115N		QFP-100 LQFP-100 BGA-112				384K +32K	48K					83																						
	MB9BF115R		LQFP-120				103																												
	MB9BF116N		QFP-100 LQFP-100 BGA-112				512K +32K	64K					83																						

FM3 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [bit]	Ext. Interrupt [bit]	External Bus	Maximum I/O port [bit]	10bit AD Converter [bit(unit)]	12bit AD Converter [bit(unit)]	DA Converter [bit x bit]	Timer								Serial			Communication			Note	Evaluation Device
																	Output Compare [bit]	Free-Run Timer [bit]	Input Capture [bit]	Reload Timer [bit]	PWM Timer [bit]	PWC Timer [bit]	PPG Timer [bit]	Up/Down Counter [bit]	Other timers [bit]	I ² C [bit]	UART/SSI [bit]	SIO [bit]	LIN/UART/SIO [bit]	CAN [bit]		
HIGH-PERFORMANCE GROUP																																
MB9B500B	MB9BF504NB	80	LQFP-100 BGA-112	2.7 to 5.5	✓	FLASH	256K	32K	-	8	16	✓	80	-	16(3)	-	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)	2	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer	On-chip Debug (SWJ-DP/ETM)					
	MB9BF504RB		LQFP-120				100																									
	MB9BF505NB		LQFP-100 BGA-112				80																									
	MB9BF505RB		LQFP-120				100																									
	MB9BF506NB		LQFP-100 BGA-112				80																									
	MB9BF506RB		LQFP-120				100																									
MB9B400A	MB9BF404NA	80	LQFP-100 BGA-112	2.7 to 5.5	✓	FLASH	256K	32K	-	8	16	✓	80	-	16(3)	-	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)	2	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer	On-chip Debug (SWJ-DP/ETM)				
	MB9BF404RA		LQFP-120				100																									
	MB9BF405NA		LQFP-100 BGA-112				80																									
	MB9BF405RA		LQFP-120				100																									
	MB9BF406NA		LQFP-100 BGA-112				80																									
	MB9BF406RA		LQFP-120				100																									
MB9B300B	MB9BF304NB	80	LQFP-100 BGA-112	2.7 to 5.5	✓	FLASH	256K	32K	-	8	16	✓	80	-	16(3)	-	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer	On-chip Debug (SWJ-DP/ETM)					
	MB9BF304RB		LQFP-120				100																									
	MB9BF305NB		LQFP-100 BGA-112				80																									
	MB9BF305RB		LQFP-120				100																									
	MB9BF306NB		LQFP-100 BGA-112				80																									
	MB9BF306RB		LQFP-120				100																									
MB9B100A	MB9BF102NA	80	LQFP-100 BGA-112	2.7 to 5.5	✓	FLASH	128K	16K	-	8	16	✓	80	-	16(3)	-	Multi-Function Timer x 2units (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 2	1	Multi Function Serial x 8ch (UART/CSIO/I2C/LIN Selectable)	-	-	-	-	✓	Dual Timer	On-chip Debug (SWJ-DP/ETM)				
	MB9BF102RA		LQFP-120				100																									
	MB9BF104NA		LQFP-100 BGA-112				80																									
	MB9BF104RA		LQFP-120				100																									
	MB9BF105NA		LQFP-100 BGA-112				80																									
	MB9BF105RA		LQFP-120				100																									
	MB9BF106NA		LQFP-100 BGA-112				80																									
	MB9BF106RA		LQFP-120				100																									
BASIC GROUP																																
MB9B520M	MB9BF521K	72	LQFP-48 QFN-48	2.7 to 5.5	✓	Dual Op. Flash (Main area + Work area)	64K +32K	16K	-	8	-	-	14	-	10bit x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1	1	Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)	1	1ch (USB-Host/ USB-Function Selectable)	-	✓	CAN: 32Msg-buffer, Dual Timer, Unique ID, Real Time Clock	On-chip Debug (SWJ-DP)						
	MB9BF521L		LQFP-64 QFN-64										19					50									23(2)	QPRC x 2				
	MB9BF521M		LQFP-80 BGA-96										23					65									26(2)	QPRC x 1				
	MB9BF522K		LQFP-48 QFN-48										14					35									14(2)	QPRC x 2				
	MB9BF522L		LQFP-64 QFN-64				19	50					23(2)					QPRC x 1														
	MB9BF522M		LQFP-80 BGA-96				23	65					26(2)																			
	MB9BF524K		LQFP-48 QFN-48				14	35					14(2)																			
	MB9BF524L		LQFP-64 QFN-64				19	50					23(2)																			
	MB9BF524M		LQFP-80 BGA-96				23	65					26(2)																			

FM3 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch(unit)]	12bit AD Converter [ch(unit)]	DA Converter [bit x ch]	Timer							Serial				Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]				
BASIC GROUP																																		
MB9B320T	MB9BF328S*	60	LQFP-144	2.7 to 5.5	✓	Dual Op. Flash (Main area + Work area)	1M +64K	160K	-	8	32	✓	-	24(2)	10bit x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1 QPRC x 2 QPRC x 1 QPRC x 2	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	✓	Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP/ETM)								
	MB9BF328T*		LQFP-176 BGA-192																															
	MB9BF329S*		LQFP-144																															
	MB9BF329T*		LQFP-176 BGA-192																															
MB9B120T	MB9BF128S*	60	LQFP-144	2.7 to 5.5	✓	Dual Op. Flash (Main area + Work area)	1M +64K	160K	-	8	32	✓	-	24(2)	10bit x 2	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 16ch (Reload/PPG/PWM/ PWC Selectable)	QPRC x 1 QPRC x 2 QPRC x 1 QPRC x 2	1	Multi Function Serial x 16ch (UART/CSIO/I2C/LIN Selectable)	-	-	-	-	✓	Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP/ETM)							
	MB9BF128T*		LQFP-176 BGA-192																															
	MB9BF129S*		LQFP-144																															
	MB9BF129T*		LQFP-176 BGA-192																															
MB9A420L	MB9AF421K	40	LQFP-48 LQFP-52 QFN-48	2.7 to 5.5	✓	FLASH	64K	4K	-	-	14	36	-	8(1)	10bit x 1	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 3ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	1	Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)	1	-	-	-	✓	CAN: 32Msg-buffer, Dual Timer, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP)							
	MB9AF421L		LQFP-64 QFN-64				19	51																										
MB9A120L	MB9AF121K	40	LQFP-48 LQFP-52 QFN-48	2.7 to 5.5	✓	FLASH	64K	4K	-	-	14	36	-	8(1)	10bit x 1	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 3ch/PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	1	Multi Function Serial x 4ch (UART/CSIO/I2C/LIN Selectable)	-	-	-	-	✓	Dual Timer, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP)							
	MB9AF121L		LQFP-64 QFN-64				19	51																										

FM3 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bitAD Converter [ch/unit]	12bitAD Converter [ch/unit]	DA Converter [bit x ch]	Timer								Serial				Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device						
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]					USB-Function [ch]					
LOW-POWER GROUP																																									
MB9A150R	MB9AF154MA	40	LQFP-80 BGA-96	1.65 to 3.6	✓	Dual Op. Flash (Main area + Work area)	256K +32K	32K	-	8	23	66	-	17(2)	-	Multi-Function Timer x 1unit (Free-Run 3ch/ Output Compare 6ch/ Input Capture 4ch/ PPG 3ch/ Waveform Generator 3ch/ AD Activation Compare 3ch Selectable)	QPRC x 2	1	Base Timer x 15ch (Reload/PPG/PWM/ PWC Selectable)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP)					
	MB9AF154NA		LQFP-100 BGA-112																																	On-chip Debug (SWJ-DP/ETM)					
	MB9AF154RA		LQFP-120																																	On-chip Debug (SWJ-DP)					
	MB9AF155MA		LQFP-80 BGA-96				384K +32K	48K		-	8	23		66																						17(2)	24(2)	Base Timer x 15ch (Reload/PPG/PWM/ PWC Selectable)	Multi Function Serial x 10ch (UART/CSIO/I2C Selectable)	On-chip Debug (SWJ-DP)	
	MB9AF155NA		LQFP-100 BGA-112																																						On-chip Debug (SWJ-DP/ETM)
	MB9AF155RA		LQFP-120																																						On-chip Debug (SWJ-DP/ETM)
	MB9AF156MA		LQFP-80 BGA-96				512K +32K	64K		23	66	17(2)		24(2)																						Base Timer x 15ch (Reload/PPG/PWM/ PWC Selectable)	Multi Function Serial x 10ch (UART/CSIO/I2C Selectable)	On-chip Debug (SWJ-DP)			
	MB9AF156NA		LQFP-100 BGA-112																																				On-chip Debug (SWJ-DP/ETM)		
	MB9AF156RA		LQFP-120																																				On-chip Debug (SWJ-DP/ETM)		
MB9AB40NA	MB9AFB41LB	40	LQFP-64 QFN-64	1.65 to 3.6	✓	Dual Op. Flash (Main area + Work area)	64K +32K	16K	-	8	8	-	51	12(2)	-	-	-	-	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I2C Selectable)	-	1ch (USB-Host/ USB-Function Selectable)	-	-	-	-	-	-	-	-	Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP)							
	MB9AFB41MB		LQFP-80 BGA-96								11	66	17(2)																					33 x 8							
	MB9AFB41NB		LQFP-100 QFP-100 BGA-112								16	✓	83	24(2)																				40 x 8							
	MB9AFB42LB		LQFP-64 QFN-64				8				-	51	12(2)	20 x 8																											
	MB9AFB42MB		LQFP-80 BGA-96				11				66	17(2)	33 x 8																												
	MB9AFB42NB		LQFP-100 QFP-100 BGA-112				16				✓	83	24(2)	40 x 8																											
	MB9AFB44LB		LQFP-64 QFN-64				8	-			51	12(2)	20 x 8																												
	MB9AFB44MB		LQFP-80 BGA-96				11	66			17(2)	33 x 8																													
	MB9AFB44NB		LQFP-100 QFP-100 BGA-112				16	✓			83	24(2)	40 x 8																												
MB9AA40NA	MB9AFA41LB	40	LQFP-64 QFN-64	1.65 to 3.6	✓	Dual Op. Flash (Main area + Work area)	64K +32K	16K	-	8	8	-	51	12(2)	-	-	-	-	Base Timer x 8ch (Reload/PPG/PWM/ PWC Selectable)	-	1	Multi Function Serial x 8ch (UART/CSIO/I2C Selectable)	-	-	-	-	-	-	-	-	-	-	Dual Timer, HDMI-CEC/Remote Control Reception x 2, Real Time Clock, Unique ID	On-chip Debug (SWJ-DP)							
	MB9AFA41MB		LQFP-80 BGA-96								11	66	17(2)																					33 x 8							
	MB9AFA41NB		LQFP-100 QFP-100 BGA-112								16	✓	83	24(2)																				40 x 8							
	MB9AFA42LB		LQFP-64 QFN-64				8				-	51	12(2)	20 x 8																											
	MB9AFA42MB		LQFP-80 BGA-96				11				66	17(2)	33 x 8																												
	MB9AFA42NB		LQFP-100 QFP-100 BGA-112				16				✓	83	24(2)	40 x 8																											
	MB9AFA44LB		LQFP-64 QFN-64				8	-			51	12(2)	20 x 8																												
	MB9AFA44MB		LQFP-80 BGA-96				11	66			17(2)	33 x 8																													
	MB9AFA44NB		LQFP-100 QFP-100 BGA-112				16	✓			83	24(2)	40 x 8																												

8FX – 8bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device	
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]					USB-Host [ch]
STANDARD																																			
MB95650L	MB95F652E	16	TSSOP-24 SOP-24 QFN-32	1.8 to 5.5	✓	Dual Op. Flash	8K	256	-	-	6	-	21	-	6(1)	-	-	8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	-	-	-	2	1	-	1	-	-	-	-	-	-	-	-	Low-voltage Detection Reset, Clock Supervisor	On-chip Debug
	MB95F652L							20																											
	MB95F653E							21																											
	MB95F653L							20																											
	MB95F654E							21																											
	MB95F654L							20																											
	MB95F656E							21																											
	MB95F656L							20																											
MB95810K	MB95F814K	16	LQFP-64	2.88 to 5.5	✓	Dual Op. Flash	20K	512	-	-	12	-	58	12(1)	-	-	-	Reload Timer x 1ch + 8/16bit Compound Timer x 2ch (Interval Timer/PWM/PWC/ Input Capture Selectable)	4	-	-	-	1	-	1	-	-	-	-	-	-	Low-voltage Detection Reset, Clock Supervisor	On-chip Debug		
	MB95F816K						36K	1K																											
	MB95F818K						60K	2K																											

Traveo Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC[V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	12bit AD Converter [ch/unit]	12bit AD Converter with 4ch sample & hold	DA Converter [bit x ch]	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I2C [ch]	UART/S [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]	USB-Function [ch]	LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																						
CAN/AUTOMOTIVE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
MB9D560	MB9DF564MA	200	TEQFP -208	1.1 to 1.3 4.5 to 5.5	-	Main Flash +Work Flash	(640K +64K) x2	64K x2	-	16	8	-	125	32(1)	8(2)	10bit x 2	32bitFree-Run Timer x 5ch	16bit Base Timer x 12ch (PWM/PPG/Reload/PWC Selectable)	32bitInput Capture x 3unit 6ch	16bit Base Timer x 12ch (PWM/PPG/Reload/PWC Selectable)	16bitFree-Run Timer x 20ch	16bit Input Capture x 8unit 15ch	16bitOutput Compare x 12unit 24ch	Waveform Generator x 4unit 24ch	4	-	Multi Function Serial x 5ch (LIN/UART/SIO Selectable)	3	-	-	-	✓	ARM Cortex-R5 CAN: 64msb, RDC x 2unit, Motor vector accelaretor x 2unit	On-Chip Debug																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
	MB9DF564MG																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									

Traveo Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [Mhz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	12bit AD Converter [ch](unit)]	12bit AD Converter with 4ch sample & hold	DA Converter [bit x ch]	Timer								Serial		Communication		Three-phase Inverter	Note	Evaluation Device			
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I2C [ch]	UART/ISI [ch]	SIO [ch]				LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]
CAN/AUTOMOTIVE																																		
S6J3120	S6J3128HA	112	TEQFP -144	4.5 to 5.25	-	Main Flash +Work Flash	576K + 48K	TC-RAM: 32KB System - RAM: 16KB Backup - RAM: 8KB	Instruction: 16 Data: 16	16	16	A24/D16	112	50(2)	-	-	12	6	12	16bit Base Timer x 30ch (PWM/PPG/Reload/PWC Selectable)	2	RTC x 1ch	Multi Function Serial x 10ch (LIN/UART/SIO Selectable)	CAN-FD x 3ch	-	-	32 x 4	-	ARM Cortex-R5, SHE(Secure Hardware Extension), SMC x 4ch, Sound generator x 3ch	On-Chip Debug				
	S6J3129HA		832K + 48K	TC-RAM: 48KB System - RAM: 16KB Backup - RAM: 8KB																														
	S6J312AHA		1088K +112K	TC-RAM: 64KB System - RAM: 16KB Backup - RAM: 8KB																														
S6J3200	S6J32AAKS	160	TEQFP -208	1.1 to 1.3 3.0 to 3.6 4.5 to 5.5	✓	Main Flash +Work Flash	1088K + 112K	TC-RAM: 64KB System - RAM: 128KB Backup - RAM: 16KB VRAM: 1024KB	Instruction: 16 Data: 16	16	16	-	120	46(1)	-	-	24	12	24	Reload Timer x 14ch 16bit Base Timer x 24ch (PWM/PPG/Reload/PWC Selectable)	2	RTC x 1ch	Multi Function Serial x 12ch (LIN/UART/SIO/I2C Selectable)	CAN-FD x 4ch	-	-	30 x 4	-	ARM Cortex-R5, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 1ch	On-Chip Debug				
	S6J32AAKU		TEQFP -216 (0.4mm pitch)										128	50(1)													32 x 4							
	S6J32AALS												120	46(1)													30 x 4							
	S6J32AALU		TEQFP -208										TEQFP -216 (0.4mm pitch)	128													50(1)				32 x 4			
	S6J32BAKS		TEQFP -208											120													46(1)				30 x 4			
	S6J32BAKU		TEQFP -216 (0.4mm pitch)										128	50(1)													32 x 4							
	S6J32BALS												TEQFP -208	120													46(1)				30 x 4			
	S6J32BALU		TEQFP -216 (0.4mm pitch)										120	46(1)													32 x 4							
	S6J32CAKS		TEQFP -208										TEQFP -216 (0.4mm pitch)	128													50(1)				30 x 4			
	S6J32CAKU		TEQFP -208											128													50(1)				32 x 4			
	S6J32CALS		TEQFP -216 (0.4mm pitch)										120	46(1)													32 x 4							
	S6J32CALU		TEQFP -208										TEQFP -216 (0.4mm pitch)	128													50(1)				30 x 4			
	S6J32DAKS		TEQFP -208											128													50(1)				32 x 4			
	S6J32DAKU		TEQFP -216 (0.4mm pitch)										128	50(1)													32 x 4							
	S6J32DALU												TEQFP -216 (0.4mm pitch)	128													50(1)				32 x 4			

Traveo Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	12bit AD Converter [ch/unit]	12bit AD Converter with 4ch sample & hold	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I2C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]				
CAN/AUTOMOTIVE																																		
S6J3200	S6J323CKS	240	TEQFP -208	1.1 to 1.3 3.0 to 3.6 4.5 to 5.5	✓	Main Flash +Work Flash	2112K + 112K	TC-RAM: 128KB System - RAM: 128KB Backup - RAM: 16KB VRAM: 2048KB	Instruction: 16 Data: 16	16	16	-	120	46(1)	-	-	24	12	24	Reload Timer x 14ch 16bit Base Timer x 24ch (PWM/PPC/Reload/PWC Selectable)	2	RTC x 1ch	Multi Function Serial x 12ch (LIN/UART/SIO/I2C Selectable)	CAN-FD x 4ch	-	-	30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system,	On-Chip Debug					
	S6J323CKU		TEQFP -216 (0.4mm pitch)																											32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system,			
	S6J323CLS		TEQFP -208																											30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system,			
	S6J323CLU		TEQFP -216 (0.4mm pitch)																											32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system,			
	S6J324CKS		TEQFP -208																											30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system,			
	S6J324CKU		TEQFP -208																											30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system,			
	S6J324CLS		TEQFP -216 (0.4mm pitch)																											32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system,			
	S6J325CKS		TEQFP -208																											30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system,			
	S6J325CKU		TEQFP -208																											30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system,			
	S6J325CLS		TEQFP -216 (0.4mm pitch)																											32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch,			
	S6J325CLU		TEQFP -216 (0.4mm pitch)																											32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch,			
	S6J326CKS		TEQFP -208																											30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch, FPD-Link, Sound system,			
	S6J326CKU		TEQFP -208																											30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch, FPD-Link, Sound system,			
	S6J326CLS		TEQFP -216 (0.4mm pitch)																											32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch, FPD-Link, Sound system,			
	S6J326CLU		TEQFP -216 (0.4mm pitch)																											32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch, FPD-Link, Sound system,			
	S6J327CKS		TEQFP -208																											30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch, FPD-Link, Sound system,			
S6J327CKU	TEQFP -208	30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch, FPD-Link, Sound system,																															
S6J327CLS	TEQFP -216 (0.4mm pitch)	32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system																															
S6J327CLU	TEQFP -216 (0.4mm pitch)	32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D Graphic Engine, Display Output x 2ch, Sound system																															
S6J328CKS	TEQFP -208	30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch, FPD-Link, Sound system																															
S6J328CKU	TEQFP -208	30 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch, FPD-Link, Sound system																															
S6J328CLS	TEQFP -216 (0.4mm pitch)	32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch, FPD-Link, Sound system																															
S6J328CLU	TEQFP -216 (0.4mm pitch)	32 x 4	ARM Cortex-R5, Ethernet AVB, Media-LB, SHE(Secure Hardware Extension), SMC x 6ch, Sound generator x 4ch, 2D+3D Graphic Engine, Display Output x 2ch, FPD-Link, Sound system																															

FCR4 Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer										Serial		Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I2C [ch]	UART/SPI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]				
HYBRID AUTOMOTIVE INSTRUMENTS CLUSTER																																			
MB9DF125	MB9DF125PMC	128	LQFP-176	1.1 to 1.3 3.0 to 5.5	✓	FLASH	1088	128	8	8	32	-	123	50(1)	-	-	8	8	8	10	-	-	24	2	-	1	2	3	2	2	-	-	-	ARM Cortex R4, SHE (Secure Hardware Extension), Real Time Clock, Stepper Motor Controller (SMC): 4 ch, Data Flash: 48KB, Windows Watchdog, Clock supervisor, Sound Generator, I2S: 2 ch, Quad SPI Flash Interface: 1 ch, NMI (intern/extern): 32/1 ch, CRC Hardware Module: 1 ch, Protection Unit: MPU, PPU, TPU, various Power Down modes	On-chip Debug
	MB9DF125EPMC																																ARM Cortex R4, SHE (Secure Hardware Extension), Real Time Clock, Stepper Motor Controller (SMC): 6 ch, Data Flash: 48KB, Windows Watchdog, Clock supervisor, Sound Generator, I2S: 2 ch, Quad SPI Flash Interface: 1 ch, NMI (intern/extern): 32/1 ch, CRC Hardware Module: 1 ch, Protection Unit: MPU, PPU, TPU, various Power Down modes	On-chip Debug	
MB9DF126	MB9DF126BPMC	128	LQFP-176	1.1 to 1.3 3.0 to 5.5	✓	FLASH	2176	208	16	8	32	-	110	50(1)	-	-	8	8	8	10	-	-	24	2	-	1	2	3	2	3	-	-	-	ARM Cortex R4, APIX Remote handler with 2 ch AIC (APIX Inter Connect), APIX1 Phy: 1 ch, Real Time Clock, Stepper Motor Controller (SMC): 6 ch, Data Flash: 64KB, Windows Watchdog, Clock supervisor, Sound Generator, I2S: 2 ch, Quad SPI Flash Interface: 1 ch, NMI (intern/extern): 32/1 ch, CRC Hardware Module: 1 ch, Protection Unit: MPU, PPU, TPU, various Power Down modes	On-chip Debug
MB9EF226	MB9EF226PMC	128	LQFP-176	1.1 to 1.3 3.0 to 5.5	✓	FLASH	2176	128	16	8	32	-	117	50(1)	-	-	8	8	8	10	-	-	24	2	-	1	2	3	2	2	-	-	-	ARM Cortex R4, 2D Graphics Engine: scaler, color palette, gamma correction, blending, raster operation, various alpha blending modes, run-length decoding, hor/ver flip and rotation, affine transformations, Embedded Video-RAM: 1MB, TFT Output Interface: RGB888/RSDS Output, SHE (Secure Hardware Extension), Real Time Clock, Stepper Motor Controller (SMC): 4 ch, Data Flash: 48KB, Windows Watchdog, Clock supervisor, Sound Generator, I2S: 2 ch, Quad SPI Flash Interface: 2 ch(1 ch for MCU and 1 ch for Graphic), NMI (intern/extern): 32/1 ch, MediaLB (3 wire): 1 ch, CRC Hardware Module: 1 ch, Protection Unit: MPU, PPU, TPU, various Power Down modes	On-chip Debug
	MB9EF226EPMC																																	ARM Cortex R4, 2D Graphics Engine: scaler, color palette, gamma correction, blending, raster operation, various alpha blending modes, run-length decoding, hor/ver flip and rotation, affine transformations, Embedded Video-RAM: 1MB, TFT Output Interface: RGB888/RSDS Output, SHE (Secure Hardware Extension), Real Time Clock, Stepper Motor Controller (SMC): 6 ch, Data Flash: 48KB, Windows Watchdog, Clock supervisor, Sound Generator, I2S: 2 ch, Quad SPI Flash Interface: 2 ch(1 ch for MCU and 1 ch for Graphic), NMI (intern/extern): 32/1 ch, MediaLB (3 wire): 1 ch, CRC Hardware Module: 1 ch, Protection Unit: MPU, PPU, TPU, various Power Down modes	On-chip Debug

FR Family – 32bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch(unt)]	12bit AD Converter [ch(unt)]	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]				
CAN/AUTOMOTIVE																																		
MB91590	MB91F591B	80	LQFP-208	3.0 to 3.6 4.5 to 5.5 (2 power supplies)	Main Flash +Work Flash	Dedicated for GDC External Memory	576K +64K	48K	-	16	16	32(1)	-	-	4	2	6	Reload Timer x 4ch + PPG Timer x 24ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	-	Multi Function Serial x 2ch (LIN/UART/ SIO/I2C Selectable)	6	3	-	-	-	-	CAN: 32/64Mseg-buffer, LIN, FPU, MPU, Sound generator, SMC x 6ch, From among the RAM, 8KB can be used as BackUpRAM, Built-in 2D GDC	On-chip Debug						
	MB91F591BS																																	
	MB91F591BH																																	
	MB91F591BHS																																	
	MB91F592B																																	
	MB91F592BS																																	
	MB91F592BH																																	
	MB91F592BHS																																	
	MB91F594B	128	BGA-320				1088K +64K	72K							1600K +64K	264K	2112K +64K	264K	4	8	12	Reload Timer x 8ch + PPG Timer x 24ch + Base Timer x 2ch (Reload/PPG/PWM/PWC Selectable)	3	Multi Function Serial x 6ch (LIN/UART SIO/I2C Selectable. However, I2C only supports ch0/ ch1)										
	MB91F594BS																																	
	MB91F594BH																																	
	MB91F594BHS																																	
	MB91F59AC																																	
	MB91F59ACS																																	
	MB91F59ACH																																	
	MB91F59ACHS																																	
MB91F59BC																																		
MB91F59BCS																																		
MB91F59BCH																																		
MB91F59BCHS																																		

F²MC-16FX – 16bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch(unit)]	12bit AD Converter [ch(unit)]	DA Converter [bit x ch]	Timer								Serial			Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device		
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SO [ch]	LIN/UART/SIO [ch]	CAN [ch]					USB-Host [ch]	USB-Function [ch]
AUTOMOTIVE																																				
MB96310	MB96F313AS	56	LQFP-48	3.0 to 5.5	FLASH	96K	8K	-	4	11	-	36	12(1)	-	-	2	4	4 +3 (Dedicated for LIN)	4 +1 (Dedicated for PPG)	-	-	14	-	-	-	-	-	-	3	-	-	-	-	LVD, built-in CR Option without CAN	MB96V300C	
	✓																													34						1
	-																													36						-
	✓																													34						-
	MB96F313AW					✓																								36						-
	MB96F313RS					✓																								34						-
	MB96F313RW					✓																								36						-
	MB96F315AS					✓																								34						-
MB96320	MB96F326AS	56	LQFP-80	3.0 to 5.5	FLASH	288K	12K	-	4	15	✓	66	18(1)	-	-	6	4	12	4 +1 (Dedicated for PPG)	-	-	20	-	-	1	-	-	4	-	-	-	-	LVD, built-in CR Option without CAN	MB96V300C		
	✓											64																	-							
	MB96F326AW											✓																	66						2	
	MB96F326RS											✓																	64						-	
	MB96F326RW											✓																	66						-	
	MB96F336US											-																	124						36(1)	-
MB96F336UW	✓	122	-																																	
MB96F338RS	-	124	-																																	
MB96F338RW	✓	122	-																																	
MB96F338US	-	120	36(1)	-	-	-	-	-	-	-	-	2	-	-	-	-	-	-	3	1ch (USB-Host/USB-Function Selectable)	-	-	LVD, built-in CR	MB96V300C												
MB96F338UW	✓	118																		-																

F²MC-16FX – 16bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer										Serial		Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device																														
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/Sl [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]					USB-Function [ch]																													
AUTOMOTIVE																																																																	
MB96340	MB96345RS	56	LQFP-100	3.0 to 5.5	-	MASK	160K	8K	-	6	16	✓	82	24(1)	-	-	8	2	8	4 +1 (Dedicated for PPG)	-	16	-	-	-	2	-	-	7	2	-	-	-	Option without CAN	MB96V300C																														
	MB96345RW				✓		288K	16K					80																	1																																			
	MB96346RS				-		160K +64K	8K					82																	-																																			
	MB96346RW				✓								80																	2																																			
	MB96F345DS	-			FLASH	288K							16K																	82						-																													
	MB96F345DW	✓																												80						2																													
	MB96F346AS	-					82	-																																																									
	MB96F346AW	✓					80	2																																																									
	MB96F346RS	-				416K	16K	82					-																																																				
	MB96F346RW	✓						80					2																																																				
	MB96F347AS	-						82					-																																																				
	MB96F347AW	✓						80					2																																																				
	MB96F347RS	-				544K	24K	82					-																																																				
	MB96F347RW	✓						80					2																																																				
	MB96F348AS	-						82					-																																																				
	MB96F348AW	✓						80					2																																																				
	MB96F348RS	-				544K +32K	24K	82					-																																																				
	MB96F348RW	✓						80					2																																																				
	MB96F348HS	-						82					-																																																				
	MB96F348HW	✓						80					4																																																				
MB96350	MB96F353AS	56	LQFP-64	3.0 to 5.5	-	FLASH	96K	8K	-	4	13	✓	51	15(1)	-	-	4	4	6 +3 (Dedicated for LIN)	4 +1 (Dedicated for PPG)	-	-	20	-	-	1	-	-	4	1	-	-	-	Option without CAN	MB96V300C																														
	MB96F353AW				✓								49																	-																																			
	MB96F353RS				-								51																	-																																			
	MB96F353RW				✓								49																	-																																			
	MB96F355AS				-		160K	12K					51																	-																																			
	MB96F355AW				✓								49																	-																																			
	MB96F355RS				-								51																	-																																			
	MB96F355RW				✓								49																	-																																			
	MB96F356AS				-		288K	12K					51																	-																																			
	MB96F356AW				✓								49																	-																																			
	MB96F356RS				-								51																	-																																			
	MB96F356RW				✓								49																	-																																			
MB96370	MB96F378HS	40	LQFP-144	3.0 to 5.5	-	FLASH	544K +32K	28K	-	7	8	✓	120	22(1)	-	-	6	2	8	4 +1 (Dedicated for PPG)	-	-	12	-	-	2	-	-	6	2	-	-	72 x 4	SMC x 6ch Sound generator x 2ch	MB96V300C																														
	MB96F378HW				✓		832K	32K					118																	-																																			
	MB96F379RS				-								120																	-																																			
	MB96F379RW				✓		118	-																																																									
MB96380	MB96384RS	56	LQFP-120	3.0 to 5.5	-	MASK	128K	6K	-	7	8	✓	96	16(1)	-	-	4	2	8	4 +1 (Dedicated for PPG)	5	-	8	-	-	1	-	-	5	1	-	-	65 x 4	SMC x 5ch Sound generator x 2ch	MB96V300C																														
	MB96384RW				✓		160K	8K					94																	-																																			
	MB96385RS				-								96																	-																																			
	MB96385RW				✓		94	-																																																									
	MB96F385RS	-			160K	6K	96	-																																																									
	MB96F385RW	✓					94	-																																																									
	MB96F386RS	-					288K	16K					96																	-																																			
	MB96F386RW	✓											94																	-																																			
	MB96F387RS	-			416K	16K							96																	-																																			
	MB96F387RW	✓											94																	-																																			
	MB96F388HS	-					544K +32K	28K					96																	-																																			
	MB96F388HW	✓											94																	-																																			
	MB96F389RS	-			544K +288K	32K							96																	-																																			
	MB96F389RW	✓											94																	-																																			
	MB96390	MB96393RS					40	LQFP-100					3.0 to 5.5																	-						MASK	96K	5K	-	-	8	-	76	11(1)	-	-	4	2	4	4 +1 (Dedicated for PPG)	4	-	4	-	-	1	-	-	3	1	-	-	49 x 4	SMC x 4ch Sound generator x 1ch	MB96V300C
		MB96393RW																												✓							160K	8K					74																	-					
MB96395RS		-	76	-																																																													
MB96395RW		✓	74	-																																																													
MB96F395RS		-	160K	8K	76	-																																																											
MB96F395RW		✓			74	-																																																											
		-																																																															
		-																																																															

F²MC-16FX – 16bit Microcontrollers

Series Name	Product Name	Maximum Internal Clock Frequency [MHz]	Package [pin]	Operating Voltage: VCC [V]	Sub Clock	Memory Type	ROM [byte]	RAM [byte]	Cache [Kbyte]	DMAC [ch]	Ext. Interrupt [ch]	External Bus	Maximum I/O port [ch]	10bit AD Converter [ch/unit]	12bit AD Converter [ch/unit]	DA Converter [bit x ch]	Timer								Serial				Communication			LCD Controller [seg x com]	Three-phase Inverter	Note	Evaluation Device	
																	Output Compare [ch]	Free-Run Timer [ch]	Input Capture [ch]	Reload Timer [ch]	PWM Timer [ch]	PWC Timer [ch]	PPG Timer [ch]	Up/Down Counter [ch]	Other timers [ch]	I ² C [ch]	UART/SI [ch]	SIO [ch]	LIN/UART/SIO [ch]	CAN [ch]	USB-Host [ch]					USB-Function [ch]
AUTOMOTIVE																																				
MB96610	MB96F612A	32	LQFP-48	2.7 to 5.5	✓	Dual Op. Flash	32.5K +32K	4K	-	2	11	-	37 (Single clock) 35 (Dual clock)	16(1)	-	-	5	4	4 +3 (Dedicated for LIN)	2 +1 (Dedicated for PPG)	-	-	8bit x 16 16bit x 8	-	QPRC x 2	-	-	-	3	-	-	-	-	-	Option without CAN	On-chip Debug
	MB96F612R						-																													
	MB96F613A						-																													
	MB96F613R						-																													
	MB96F615A						-																													
MB96620	MB96F615R	32	LQFP-64	2.7 to 5.5	✓	Dual Op. Flash	128.5K +32K	10K	-	2	13	-	52 (Single clock) 50 (Dual clock)	21(1)	-	-	6	4	6 +2 (Dedicated for LIN)	2 +1 (Dedicated for PPG)	-	-	8bit x 16 16bit x 8	-	QPRC x 2	1	-	-	3	-	-	-	-	-	Option without CAN	On-chip Debug
	MB96F622A						-																													
	MB96F622R						-																													
	MB96F623A						-																													
	MB96F623R						-																													
MB96630	MB96F625A	32	LQFP-80	2.7 to 5.5	✓	Dual Op. Flash	128.5K +32K	10K	-	4	15	-	64 (Single clock) 66 (Dual clock)	21(1)	-	-	7	3	6 +1 (Dedicated for LIN)	3	-	-	8bit x 20 16bit x 15	-	QPRC x 2	2	-	-	5	-	-	-	-	-	Option without CAN	On-chip Debug
	MB96F625R						-																													
	MB96F633A						-																													
	MB96F633R						-																													
	MB96F635A						-																													
MB96640	MB96F635R	32	LQFP-100	2.7 to 5.5	✓	Dual Op. Flash	256.5K +32K	16K	-	4	16	-	81 (Single clock) 79 (Dual clock)	24(1)	-	-	7	3	6 +1 (Dedicated for LIN)	5	-	-	8bit x 24 16bit x 16	-	QPRC x 2	2	-	-	6	-	-	-	-	-	Option without CAN	On-chip Debug
	MB96F636R						-																													
	MB96F637R						-																													
	MB96F643A						-																													
	MB96F643R						-																													
MB96650	MB96F645A	32	LQFP-120	2.7 to 5.5	✓	Dual Op. Flash	128.5K +32K	16K	-	4	16	-	101 (Single clock) 99 (Dual clock)	29(1)	-	-	7	3	6 +1 (Dedicated for LIN)	5	-	-	8bit x 32 16bit x 16	-	QPRC x 2	2	-	-	6	-	-	-	-	-	Option without CAN	On-chip Debug
	MB96F645R						-																													
	MB96F646R						-																													
	MB96F647R						-																													
	MB96F653A						-																													
MB96660	MB96F653R	32	LQFP-120	2.7 to 5.5	✓	Dual Op. Flash	128.5K +32K	16K	-	4	16	-	101 (Single clock) 99 (Dual clock)	29(1)	-	-	7	3	6 +1 (Dedicated for LIN)	5	-	-	8bit x 32 16bit x 16	-	QPRC x 2	2	-	-	6	-	-	-	-	-	Option without CAN	On-chip Debug
	MB96F655A						-																													
	MB96F655R						-																													
	MB96F656R						-																													
	MB96F657R						-																													
MB96670	MB96F657R	32	LQFP-64	2.7 to 5.5	✓	Dual Op. Flash	64.5K +32K	4K	-	2	7	-	50 (Single clock) 48 (Dual clock)	12(1)	-	-	-	2	4	3	-	-	8bit x 8 16bit x 4	-	-	1	-	-	2	-	-	-	24 x 4	-	SMC x 2ch Sound generator Option without CAN	On-chip Debug
	MB96F673R						-																													
	MB96F675A						-																													
	MB96F675R						-																													
	MB96F683A						-																													
MB96680	MB96F683R	32	LQFP-80	2.7 to 5.5	✓	Dual Op. Flash	128.5K +32K	4K	-	2	7	-	65 (Single clock) 63 (Dual clock)	14(1)	-	-	-	2	4	3	-	-	8bit x 8 16bit x 4	-	-	1	-	-	2	-	-	-	32 x 4	-	SMC x 2ch Sound generator Option without CAN	On-chip Debug
	MB96F685A						-																													
	MB96F685R						-																													
	MB96F693A						-																													
	MB96F693R						-																													
MB96690	MB96F695A	32	LQFP-100	2.7 to 5.5	✓	Dual Op. Flash	128.5K +32K	8K	-	4	16	-	79 (Single clock) 77 (Dual clock)	27(1)	-	-	4	2	6	5	-	-	8bit x 14 16bit x 10	-	-	1	-	-	5	-	-	-	36 x 4	-	SMC x 4ch Sound generator x 2ch Option without CAN	On-chip Debug
	MB96F695R						-																													
	MB96F696R						-																													
	MB96F6A5A						-																													
	MB96F6A5R						-																													
MB966A0	MB96F6A6R	32	LQFP-120	2.7 to 5.5	✓	Dual Op. Flash	128.5K +32K	8K	-	4	16	-	97 (Single clock) 95 (Dual clock)	32(1)	-	-	4	2	8	5	-	-	8bit x 24 16bit x 12	-	-	1	-	-	5	-	-	-	44 x 4	-	SMC x 5ch Sound generator x 2ch Option without CAN	On-chip Debug
	MB96F6B5A						-																													
	MB96F6B5R						-																													
	MB96F6B6R						-																													
	MB96F6C5A						-																													
MB966B0	MB96F6B5A	32	LQFP-100	2.7 to 5.5	✓	Dual Op. Flash	128.5K +32K	8K	-	4	16	-	79 (Single clock) 77 (Dual clock)	27(1)	-	-	4	2	6	5	-	-	8bit x 16 16bit x 12	-	QPRC x 2	1	-	-	5	-	-	-	36 x 4	-	Sound generator x 2ch Option without CAN	On-chip Debug
	MB96F6B5R						-																													
	MB96F6B6R						-																													
	MB96F6C5A						-																													
	MB96F6C5R						-																													
MB966C0	MB96F6C5R	32	LQFP-120	2.7 to 5.5	✓	Dual Op. Flash	128.5K +32K	8K	-	4	16	-	99 (Single clock) 97 (Dual clock)	32(1)	-	-	4	2	8	5	-	-	8bit x 16 16bit x 12	-	QPRC x 2	1	-	-	5	-	-	-	44 x 4	-	Sound generator x 2ch Option without CAN	On-chip Debug
	MB96F6C6R						-																													
	MB96F6C6R						-																													
	MB96F6C6R						-																													
	MB96F6C6R						-																													



Cypress Semiconductor Corporation

198 Champion Court, San Jose CA 95134

phone +1 408.943.2600 fax +1 408.943.6848

toll free +1 800.858.1810 (U.S. only) Press "1" to reach your local sales representative

© 2015 Cypress Semiconductor Corporation. All rights reserved. All other trademarks are the property of their respective owners.

Doc# 002-06949 Rev. *A