



Welcome to **E-XFL.COM**

Understanding Embedded - Microprocessors

Embedded microprocessors are specialized computing chips designed to perform specific tasks within an embedded system. Unlike general-purpose microprocessors found in personal computers, embedded microprocessors are tailored for dedicated functions within larger systems, offering optimized performance, efficiency, and reliability. These microprocessors are integral to the operation of countless electronic devices, providing the computational power necessary for controlling processes, handling data, and managing communications.


Applications of Embedded - Microprocessors

Embedded microprocessors are utilized across a broad spectrum of applications, making them indispensable in

Details	
Product Status	Active
Core Processor	Celeron Mobile B810
Number of Cores/Bus Width	2 Core, 64-Bit
Speed	1.6GHz
Co-Processors/DSP	-
RAM Controllers	-
Graphics Acceleration	-
Display & Interface Controllers	-
Ethernet	-
SATA	-
USB	-
Voltage - I/O	-
Operating Temperature	-
Security Features	-
Package / Case	988-PGA Module
Supplier Device Package	988-PGA (37.5x37.5)
Purchase URL	https://www.e-xfl.com/product-detail/advantech/96mpcm-1-6-2m9t

Email: info@E-XFL.COM

Address: Room A, 16/F, Full Win Commercial Centre, 573 Nathan Road, Mongkok, Hong Kong



SPECIFICATIONS

All

Essentials

Memory Specifications

Graphics Specifications

Expansion Options

Package Specifications

Advanced Technologies

COMPATIBLE PRODUCTS

BLOCK DIAGRAMS

ORDERING / SSPECS / STEPPINGS

SPECIFICATIONS

Essentials		
Status		Launched
Launch Date		Q1'11
Processor Number		B810
# of Cores		2
# of Threads		2
Clock Speed		1.6 GHz
Intel® Smart Cache		2 MB
Bus/Core Ratio		16
Instruction Set		64-bit
Instruction Set Extensions		SSE4.x
Embedded Options Available	P	Yes
Lithography		32 nm
Max TDP		35 W
Recommended Channel Price		\$86.00
Memory Specifications		
Max Memory Size (dependent on memory type)		16 GB
Memory Types		DDR3-1066/1333
# of Memory Channels		2
Max Memory Bandwidth		21.3 GB/s
ECC Memory Supported		No
Graphics Specifications		
Integrated Graphics	A	Yes
Graphics Base Frequency		650 MHz
Graphics Max Dynamic Frequency		950 MHz
Graphics Output		eDP/DP /HDMI/SDVO/CRT
Intel® Quick Sync Video		No
Intel® InTru™ 3D Technology,		No
Intel® Wireless Display		No
Intel® Flexible Display Interface (Intel® FDI)		Yes
Intel® Clear Video HD Technology		No
Dual Display Capable		Yes
Macrovision* License Required		No

©Intel Corporation

COMPARE PRODUCTS

- Add to Compare
- Compare Now (0)

• Visit the Embedded Design Center >

QUICK LINKS

- Products formerly Sandy Bridge
- No Datasheet Available

ADDITIONAL INFORMATION

SEARCH DISTRIBUTORS

FF8062700848800

Buy From: Arrow | Avnet

PCN/MDDS INFORMATION

Expansion Options	
PCI Express Revision	2.0
PCI Express Configurations	1x16, 2x8, 1x8 2x4
# of PCI Express Ports	8
Package Specifications	
Max CPU Configuration	1
TJUNCTION	100C
Package Size	37.5mmx37.5mm (rPGA988B)
Graphics and IMC Lithography	32 nm
Sockets Supported	PGA988
Halogen Free Options Available	Yes

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Enabling Execute Disable Bit functionality requires a PC with a processor with Execute Disable Bit capability and a supporting operating system. Check with your PC manufacturer on whether your system delivers Execute Disable Bit functionality.

64-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. Consult with your system vendor for more information.

Hyper-Threading Technology (HT Technology) requires a computer system with an Intel® processor supporting HT Technology and an HT Technology enabled chipset, BIOS and operating system. Performance will vary depending on the specific hardware and software you see. See www.intel.com/products/ht/hyperthreading_more.htm for more information including details on which processors support HT Technology.

Intel® Virtualization Technology requires a computer system with a processor, chipset, BIOS, virtual machine monitor (VMM) and for some uses, certain platform software, enabled for it. Functionality, performance or other benefit will vary depending on hardware and software configurations. Intel Virtualization Technology-enabled VMM applications are currently in development.

Note: Prices subject to change without notice. Prices are for direct Intel customers in 1000-unit bulk quantities and, unless specified, represent the latest technology versions of the products. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See http://www.intel.com/products/processor_number for details.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Halogen Free implies the following:

Bromine and/or chlorine in materials that may be used during processing, but do not remain within the final product are not included in this definition. The halogens fluorine (F), iodine (I), and astatine (At) are not restricted by this standard.

"BFR/CFR and PVC-Free" Definition:

All PCB laminates must meet Br and CI requirements for low halogen as defined in IPC-4101B For components other than PCB laminates, all homogeneous materials must contain < 900 ppm (0.09%) of Bromine [if the Bromine [Bf source is from BFRs] and < 900 ppm (0.09%) of Chlorine [if the Chlorine (CI) source is from CFRs or PVC. Higher concentrations of Br and CI are allowed in homogenous materials of components other than PCB laminates as long as their sources are not BFRs. CFRs. PVC.

Although the elemental analysis for Br and Cl in homogeneous materials can be performed by any analytical method with sufficient sensitivity and selectivity, the presence or absence of BFRs, CFRs or PVC must be verified by any acceptable analytical techniques that allow for the unequivocal identification of the specific Br or Cl compounds, or by appropriate material declarations agreed to between customer and supplier.

Max Turbo Frequency refers to the maximum single-core frequency that can be achieved with Intel® Turbo Boost Technology, which requires a PC with a processor with Intel Turbo Boost Technology capability. Intel Turbo Boost Technology performance varies depending on hardware, software, and overall system configuration. Check with your PC manufacturer on whether your system delivers Intel Turbo Boost Technology. See www.intel.com/technology/turboboost/formore information.

Advanced Technologies	
Intel® Turbo Boost Technology	No
Intel® Hyper-Threading Technology	No
Intel® Virtualization Technology (VT-x)	Yes
Intel® Virtualization Technology for Directed I/O (VT-d)	No
Intel® Trusted Execution Technology	No
AES New Instructions	No
Intel® 64	Yes
Intel® Anti-Theft Technology	No
Intel® My WiFi Technology	No
4G WiMAX Wireless Technology	No
Idle States	Yes
Enhanced Intel SpeedStep® Technology	Yes
Intel® Demand Based Switching	No
Thermal Monitoring Technologies	Yes
Intel® Fast Memory Access	Yes
Intel® Flex Memory Access	Yes
Execute Disable Bit	Yes





English

Type Here to Search Products

Intel® Processors

Intel® Celeron® Mobile Processor

Intel® Celeron® Processor B800 Series



Intel® Celeron® Processor B810 (2M Cache, 1.60 GHz)


SPECIFICATIONS

BLOCK DIAGRAMS

BLOCK DIAGRAMS

ORDERING / SSPECS / **STEPPINGS**

COMPATIBLE PRODUCTS



COMPARE PRODUCTS

- Add to Compare
- Compare Now (0)
- Visit the Embedded Design Center >

QUICKLINKS

- Products formerly Sandy Bridge
- No Datasheet Available

ADDITIONAL INFORMATION

SEARCH DISTRIBUTORS

FF8062700848800 Buy From: Arrow | Avnet

PCN/MDDS INFORMATION

Enabling Execute Disable Bit functionality requires a PC with a processor with Execute Disable Bit capability and a supporting operating system. Check with your PC manufacturer on whether your system

64-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. Consult with your system vendor for more

Hyper-Threading Technology (HT Technology) requires a computer system with an Intel® processor supporting HT Technology and an HT Technology enabled chipset, BIOS and operating system. Performance will vary depending on the specific hardware and software you use. See www.intel.com/products/ht/hyperthreading_more.htm for more information including details on which processors support HT Technology

Intel® Virtualization Technology requires a computer system with a processor, chipset, B/OS, virtual machine monitor (VMM) and for some uses, certain platform software, enabled for it. Functionality, performance or other benefit will vary depending on hardware and software configurations. Intel Virtualization Technology-enabled VMM applications are currently in development.

Note: Prices subject to change without notice. Prices are for direct Intel customers in 1000-unit bulk quantities and, unless specified, represent the latest technology versions of the products. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See http://www.intel.com/products /processor number for details.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Halogen Free implies the following:

Bromine and/or chlorine in materials that may be used during processing, but do not remain within the final product are not included in this definition. The halogens fluorine (F), iodine (I), and astatine (At) are not restricted by this standard.

"BFR/CFR and PVC-Free" Definition:

All PCB laminates must meet Br and CI requirements for low halogen as defined in IPC-4101B

All PCB latinitiates must friese to a fact Circular interients for own related in PCB latinitates must contain < 900 ppm (0.09%) of Bromine [if the Bromine (Br) source is from BFRs] and < 900 ppm (0.09%) of Chlorine [if the Chlorine (CI) source is from CFRs or PVC. Higher concentrations of Br and CI are allowed in homogeneous materials of components other than PCB laminates as long as their sources are not BFRs, CFRs, PVC. Although the elemental analysis for Br and CI in homogeneous materials can be performed by any analytical method with sufficient sensitivity and selectivity, the presence or absence of BFRs, CFRs or PVC must be verified by any acceptable analytical techniques that allow for the unequivocal identification of the specific Br or CI compounds, or by appropriate material declarations agreed to between customer and supplier.

[&]quot;Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.





English

Type Here to Search Products

Intel® Processors

Intel® Celeron® Mobile Processor

Intel® Celeron® Processor B800 Series



Intel® Celeron® Processor B810 (2M Cache, 1.60 GHz)

SPECIFICATIONS

BLOCK DIAGRAMS

COMPATIBLE PRODUCTS

ORDERING / SSPECS / **STEPPINGS**

Ordering / sSpecs / Steppings Retired and Discontinued

ORDERING AND SPEC INFORMATION

Ordering and Spec Information

Intel® Celeron® Processor B810 (2M Cache, 1.60 GHz) FC-PGA10, Tray

Socket	Step	Step TDP	Ordering Code	Spec Code	Halogen Free	VT-x
PGA988	Q0	35 Watts	FF8062700848800	SR088	Yes	Yes

COMPARE PRODUCTS

- Add to Compare
- Compare Now (0)

 Visit the Embedded Design Center >

QUICKLINKS

- Products formerly Sandy Bridge
- No Datasheet Available

ADDITIONAL INFORMATION

SEARCH DISTRIBUTORS

FF8062700848800 Buy From: Arrow | Avnet

PCN/MDDS INFORMATION

Enabling Execute Disable Bit functionality requires a PC with a processor with Execute Disable Bit capability and a supporting operating system. Check with your PC manufacturer on whether your system

64-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. Consult with your system vendor for more

Hyper-Threading Technology (HT Technology) requires a computer system with an Intel® processor supporting HT Technology and an HT Technology enabled chipset, BIOS and operating system. Performance will vary depending on the specific hardware and software you use. See www.intel.com/products/ht/hyperthreading_more.htm for more information including details on which processors support HT Technology

Intel® Virtualization Technology requires a computer system with a processor, chipset, B/OS, virtual machine monitor (VMM) and for some uses, certain platform software, enabled for it. Functionality, performance or other benefit will vary depending on hardware and software configurations. Intel Virtualization Technology-enabled VMM applications are currently in development.

Note: Prices subject to change without notice. Prices are for direct Intel customers in 1000-unit bulk quantities and, unless specified, represent the latest technology versions of the products. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See http://www.intel.com/products /processor number for details.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Halogen Free implies the following:

Bromine and/or chlorine in materials that may be used during processing, but do not remain within the final product are not included in this definition. The halogens fluorine (F), iodine (I), and astatine (At) are not restricted by this standard.

"BFR/CFR and PVC-Free" Definition:

All PCB laminates must meet Br and CI requirements for low halogen as defined in IPC-4101B

All PCB latinitiates must friese to a fact Circular interients for own related in PCB latinitates must contain < 900 ppm (0.09%) of Bromine [if the Bromine (Br) source is from BFRs] and < 900 ppm (0.09%) of Chlorine [if the Chlorine (CI) source is from CFRs or PVC. Higher concentrations of Br and CI are allowed in homogeneous materials of components other than PCB laminates as long as their sources are not BFRs, CFRs, PVC. Although the elemental analysis for Br and CI in homogeneous materials can be performed by any analytical method with sufficient sensitivity and selectivity, the presence or absence of BFRs, CFRs or PVC must be verified by any acceptable analytical techniques that allow for the unequivocal identification of the specific Br or CI compounds, or by appropriate material declarations agreed to between customer and supplier.

[&]quot;Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.