



Welcome to [E-XFL.COM](https://www.e-xfl.com)

### Understanding [Embedded - FPGAs \(Field Programmable Gate Array\)](#)

Embedded - FPGAs, or Field Programmable Gate Arrays, are advanced integrated circuits that offer unparalleled flexibility and performance for digital systems. Unlike traditional fixed-function logic devices, FPGAs can be programmed and reprogrammed to execute a wide array of logical operations, enabling customized functionality tailored to specific applications. This reprogrammability allows developers to iterate designs quickly and implement complex functions without the need for custom hardware.

### Applications of Embedded - FPGAs

The versatility of Embedded - FPGAs makes them indispensable in numerous fields. In telecommunications.


#### Details

|                                |                                                                                                                                                                   |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Status                 | Active                                                                                                                                                            |
| Number of LABs/CLBs            | -                                                                                                                                                                 |
| Number of Logic Elements/Cells | -                                                                                                                                                                 |
| Total RAM Bits                 | -                                                                                                                                                                 |
| Number of I/O                  | 104                                                                                                                                                               |
| Number of Gates                | 14000                                                                                                                                                             |
| Voltage - Supply               | 3V ~ 3.6V, 4.5V ~ 5.5V                                                                                                                                            |
| Mounting Type                  | Surface Mount                                                                                                                                                     |
| Operating Temperature          | -55°C ~ 125°C (TC)                                                                                                                                                |
| Package / Case                 | 176-LQFP                                                                                                                                                          |
| Supplier Device Package        | 176-TQFP (24x24)                                                                                                                                                  |
| Purchase URL                   | <a href="https://www.e-xfl.com/product-detail/microchip-technology/a42mx09-tqg176m">https://www.e-xfl.com/product-detail/microchip-technology/a42mx09-tqg176m</a> |

### 3.2.3.3 Antifuse Structures

An antifuse is a “normally open” structure. The use of antifuses to implement a programmable logic device results in highly testable structures as well as efficient programming algorithms. There are no pre-existing connections; temporary connections can be made using pass transistors. These temporary connections can isolate individual antifuses to be programmed and individual circuit structures to be tested, which can be done before and after programming. For instance, all metal tracks can be tested for continuity and shorts between adjacent tracks, and the functionality of all logic modules can be verified.

**Figure 7 • MX Routing Structure**



### 3.2.4 Clock Networks

The 40MX devices have one global clock distribution network (CLK). A signal can be put on the CLK network by being routed through the CLKBUF buffer.


In 42MX devices, there are two low-skew, high-fanout clock distribution networks, referred to as CLKA and CLKB. Each network has a clock module (CLKMOD) that can select the source of the clock signal from any of the following (Figure 8, page 11):

- Externally from the CLKA pad, using CLKBUF buffer
- Externally from the CLKB pad, using CLKBUF buffer
- Internally from the CLKINTA input, using CLKINT buffer
- Internally from the CLKINTB input, using CLKINT buffer

The clock modules are located in the top row of I/O modules. Clock drivers and a dedicated horizontal clock track are located in each horizontal routing channel.

Clock input pads in both 40MX and 42MX devices can also be used as normal I/Os, bypassing the clock networks.


The A42MX36 device has four additional register control resources, called quadrant clock networks (Figure 9, page 11). Each quadrant clock provides a local, high-fanout resource to the contiguous logic modules within its quadrant of the device. Quadrant clock signals can originate from specific I/O pins or from the internal array and can be used as a secondary register clock, register clear, or output enable.

**Figure 20 • 42MX Timing Model (SRAM Functions)**

**Note:** Values are shown for A42MX36 –3 at 5.0 V worst-case commercial conditions.

### 3.10.1 Parameter Measurement

The following figures show parameter measurement details.

**Figure 21 • Output Buffer Delays**






**Figure 22 • AC Test Loads****Figure 23 • Input Buffer Delays****Figure 24 • Module Delays**

Figure 30 • 42MX SRAM Write Operation




**Note:** Identical timing for falling edge clock

Figure 31 • 42MX SRAM Synchronous Read Operation



**Note:** Identical timing for falling edge clock

Figure 32 • 42MX SRAM Asynchronous Read Operation—Type 1 (Read Address Controlled)



**Table 35 • A40MX02 Timing Characteristics (Nominal 3.3 V Operation) (continued)**  
**(Worst-Case Commercial Conditions, VCC = 3.0 V, T<sub>J</sub> = 70°C)**

| Parameter / Description               |                      |          | –3 Speed |      | –2 Speed |      | –1 Speed |      | Std Speed |      | –F Speed |      | Units |
|---------------------------------------|----------------------|----------|----------|------|----------|------|----------|------|-----------|------|----------|------|-------|
|                                       |                      |          | Min.     | Max. | Min.     | Max. | Min.     | Max. | Min.      | Max. | Min.     | Max. |       |
| t <sub>p</sub>                        | Minimum Period       | FO = 16  | 6.5      |      | 7.5      |      | 8.5      |      | 10.1      |      | 14.1     |      | ns    |
|                                       |                      | FO = 128 | 6.8      |      | 7.8      |      | 8.9      |      | 10.4      |      | 14.6     |      |       |
| f <sub>MAX</sub>                      | Maximum Frequency    | FO = 16  |          | 113  |          | 105  |          | 96   |           | 83   |          | 50   | MHz   |
|                                       |                      | FO = 128 |          | 109  |          | 101  |          | 92   |           | 80   |          | 48   |       |
| TTL Output Module Timing <sup>4</sup> |                      |          |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>DLH</sub>                      | Data-to-Pad HIGH     |          |          | 4.7  |          | 5.4  |          | 6.1  |           | 7.2  |          | 10.0 | ns    |
| t <sub>DHL</sub>                      | Data-to-Pad LOW      |          |          | 5.6  |          | 6.4  |          | 7.3  |           | 8.6  |          | 12.0 | ns    |
| t <sub>ENZH</sub>                     | Enable Pad Z to HIGH |          |          | 5.2  |          | 6.0  |          | 6.8  |           | 8.1  |          | 11.3 | ns    |
| t <sub>ENZL</sub>                     | Enable Pad Z to LOW  |          |          | 6.6  |          | 7.6  |          | 8.6  |           | 10.1 |          | 14.1 | ns    |
| t <sub>ENHZ</sub>                     | Enable Pad HIGH to Z |          |          | 11.1 |          | 12.8 |          | 14.5 |           | 17.1 |          | 23.9 | ns    |
| t <sub>ENLZ</sub>                     | Enable Pad LOW to Z  |          |          | 8.2  |          | 9.5  |          | 10.7 |           | 12.6 |          | 17.7 | ns    |
| d <sub>TLH</sub>                      | Delta LOW to HIGH    |          |          | 0.03 |          | 0.03 |          | 0.04 |           | 0.04 |          | 0.06 | ns/pF |
| d <sub>THL</sub>                      | Delta HIGH to LOW    |          |          | 0.04 |          | 0.04 |          | 0.05 |           | 0.06 |          | 0.08 | ns/pF |

**Table 39 • A42MX09 Timing Characteristics (Nominal 3.3 V Operation) (continued)(Worst-Case Commercial Conditions, VCCA = 3.0 V, T<sub>J</sub> = 70°C)**

| Parameter / Description               |                                                       | –3 Speed |      | –2 Speed |      | –1 Speed |      | Std Speed |      | –F Speed |      | Units |
|---------------------------------------|-------------------------------------------------------|----------|------|----------|------|----------|------|-----------|------|----------|------|-------|
|                                       |                                                       | Min.     | Max. | Min.     | Max. | Min.     | Max. | Min.      | Max. | Min.     | Max. |       |
| TTL Output Module Timing <sup>5</sup> |                                                       |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>DLH</sub>                      | Data-to-Pad HIGH                                      |          | 3.4  |          | 3.8  |          | 4.3  |           | 5.1  |          | 7.1  | ns    |
| t <sub>DHL</sub>                      | Data-to-Pad LOW                                       |          | 4.0  |          | 4.5  |          | 5.1  |           | 6.1  |          | 8.3  | ns    |
| t <sub>ENZH</sub>                     | Enable Pad Z to HIGH                                  |          | 3.7  |          | 4.1  |          | 4.6  |           | 5.5  |          | 7.6  | ns    |
| t <sub>ENZL</sub>                     | Enable Pad Z to LOW                                   |          | 4.1  |          | 4.5  |          | 5.1  |           | 6.1  |          | 8.5  | ns    |
| t <sub>ENHZ</sub>                     | Enable Pad HIGH to Z                                  |          | 6.9  |          | 7.6  |          | 8.6  |           | 10.2 |          | 14.2 | ns    |
| t <sub>ENLZ</sub>                     | Enable Pad LOW to Z                                   |          | 7.5  |          | 8.3  |          | 9.4  |           | 11.1 |          | 15.5 | ns    |
| t <sub>GLH</sub>                      | G-to-Pad HIGH                                         |          | 5.8  |          | 6.5  |          | 7.3  |           | 8.6  |          | 12.0 | ns    |
| t <sub>GHL</sub>                      | G-to-Pad LOW                                          |          | 5.8  |          | 6.5  |          | 7.3  |           | 8.6  |          | 12.0 | ns    |
| t <sub>LSU</sub>                      | I/O Latch Set-Up                                      | 0.7      |      | 0.8      |      | 0.9      |      | 1.0       |      | 1.4      |      | ns    |
| t <sub>LH</sub>                       | I/O Latch Hold                                        | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>LCO</sub>                      | I/O Latch Clock-to-Out (Pad-to-Pad), 64 Clock Loading |          | 8.7  |          | 9.7  |          | 10.9 |           | 12.9 |          | 18.0 | ns    |
| t <sub>ACO</sub>                      | Array Clock-to-Out (Pad-to-Pad),64 Clock Loading      |          | 12.2 |          | 13.5 |          | 15.4 |           | 18.1 |          | 25.3 | ns    |
| d <sub>TLH</sub>                      | Capacity Loading, LOW to HIGH                         |          | 0.00 |          | 0.00 |          | 0.00 |           | 0.10 |          | 0.01 | ns/pF |
| d <sub>THL</sub>                      | Capacity Loading, HIGH to LOW                         |          | 0.09 |          | 0.10 |          | 0.10 |           | 0.10 |          | 0.10 | ns/pF |

**Table 41 • A42MX16 Timing Characteristics (Nominal 3.3 V Operation) (continued)(Worst-Case Commercial Conditions, VCCA = 3.0 V, T<sub>J</sub> = 70°C)**

| Parameter / Description                            |                                            |          | –3 Speed |      | –2 Speed |      | –1 Speed |      | Std Speed |      | –F Speed |      | Units |
|----------------------------------------------------|--------------------------------------------|----------|----------|------|----------|------|----------|------|-----------|------|----------|------|-------|
|                                                    |                                            |          | Min.     | Max. | Min.     | Max. | Min.     | Max. | Min.      | Max. | Min.     | Max. |       |
| Logic Module Sequential Timing <sup>3, 4</sup>     |                                            |          |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>SUD</sub>                                   | Flip-Flop (Latch) Data Input Set-Up        |          | 0.5      |      | 0.5      |      | 0.6      |      | 0.7       |      | 0.9      |      | ns    |
| t <sub>HD</sub>                                    | Flip-Flop (Latch) Data Input Hold          |          | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>SUENA</sub>                                 | Flip-Flop (Latch) Enable Set-Up            |          | 1.0      |      | 1.1      |      | 1.2      |      | 1.4       |      | 2.0      |      | ns    |
| t <sub>HENA</sub>                                  | Flip-Flop (Latch) Enable Hold              |          | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>WCLKA</sub>                                 | Flip-Flop (Latch) Clock Active Pulse Width |          | 4.8      |      | 5.3      |      | 6.0      |      | 7.1       |      | 9.9      |      | ns    |
| t <sub>WASYN</sub>                                 | Flip-Flop (Latch) Asynchronous Pulse Width |          | 6.2      |      | 6.9      |      | 7.9      |      | 9.2       |      | 12.9     |      | ns    |
| t <sub>A</sub>                                     | Flip-Flop Clock Input Period               |          | 9.5      |      | 10.6     |      | 12.0     |      | 14.1      |      | 19.8     |      | ns    |
| t <sub>INH</sub>                                   | Input Buffer Latch Hold                    |          | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>INSU</sub>                                  | Input Buffer Latch Set-Up                  |          | 0.7      |      | 0.8      |      | 0.9      |      | 1.01      |      | 1.4      |      | ns    |
| t <sub>OUTH</sub>                                  | Output Buffer Latch Hold                   |          | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>OUTSU</sub>                                 | Output Buffer Latch Set-Up                 |          | 0.7      |      | 0.8      |      | 0.89     |      | 1.01      |      | 1.4      |      | ns    |
| f <sub>MAX</sub>                                   | Flip-Flop (Latch) Clock Frequency          |          |          | 129  |          | 117  |          | 108  |           | 94   |          | 56   | MHz   |
| Input Module Propagation Delays                    |                                            |          |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>INYH</sub>                                  | Pad-to-Y HIGH                              |          |          | 1.5  |          | 1.6  |          | 1.9  |           | 2.2  |          | 3.1  | ns    |
| t <sub>INYL</sub>                                  | Pad-to-Y LOW                               |          |          | 1.1  |          | 1.3  |          | 1.4  |           | 1.7  |          | 2.4  | ns    |
| t <sub>INGH</sub>                                  | G to Y HIGH                                |          |          | 2.0  |          | 2.2  |          | 2.5  |           | 2.9  |          | 4.1  | ns    |
| t <sub>INGL</sub>                                  | G to Y LOW                                 |          |          | 2.0  |          | 2.2  |          | 2.5  |           | 2.9  |          | 4.1  | ns    |
| Input Module Predicted Routing Delays <sup>2</sup> |                                            |          |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>IRD1</sub>                                  | FO = 1 Routing Delay                       |          |          | 2.6  |          | 2.9  |          | 3.2  |           | 3.8  |          | 5.3  | ns    |
| t <sub>IRD2</sub>                                  | FO = 2 Routing Delay                       |          |          | 2.9  |          | 3.2  |          | 3.7  |           | 4.3  |          | 6.1  | ns    |
| t <sub>IRD3</sub>                                  | FO = 3 Routing Delay                       |          |          | 3.3  |          | 3.6  |          | 4.1  |           | 4.9  |          | 6.8  | ns    |
| t <sub>IRD4</sub>                                  | FO = 4 Routing Delay                       |          |          | 3.6  |          | 4.0  |          | 4.6  |           | 5.4  |          | 7.6  | ns    |
| t <sub>IRD8</sub>                                  | FO = 8 Routing Delay                       |          |          | 5.1  |          | 5.6  |          | 6.4  |           | 7.5  |          | 10.5 | ns    |
| Global Clock Network                               |                                            |          |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>CKH</sub>                                   | Input LOW to HIGH                          | FO = 32  | 4.4      |      | 4.8      |      | 5.5      |      | 6.5       |      | 9.0      | ns   |       |
|                                                    |                                            | FO = 384 | 4.8      |      | 5.3      |      | 6.0      |      | 7.1       |      | 9.9      | ns   |       |
| t <sub>CKL</sub>                                   | Input HIGH to LOW                          | FO = 32  | 5.3      |      | 5.9      |      | 6.7      |      | 7.8       |      | 11.0     | ns   |       |
|                                                    |                                            | FO = 384 | 6.2      |      | 6.9      |      | 7.9      |      | 9.2       |      | 12.9     | ns   |       |
| t <sub>PWH</sub>                                   | Minimum Pulse Width HIGH                   | FO = 32  | 5.7      |      | 6.3      |      | 7.1      |      | 8.4       |      | 11.8     | ns   |       |
|                                                    |                                            | FO = 384 | 6.6      |      | 7.4      |      | 8.3      |      | 9.8       |      | 13.7     | ns   |       |

**Table 44 • A42MX36 Timing Characteristics (Nominal 5.0 V Operation)(Worst-Case Commercial Conditions, VCCA = 4.75 V, T<sub>J</sub> = 70°C)**

| Parameter / Description                            |                                            | –3 Speed |      | –2 Speed |      | –1 Speed |      | Std Speed |      | –F Speed |      | Units |
|----------------------------------------------------|--------------------------------------------|----------|------|----------|------|----------|------|-----------|------|----------|------|-------|
|                                                    |                                            | Min.     | Max. | Min.     | Max. | Min.     | Max. | Min.      | Max. | Min.     | Max. |       |
| Logic Module Combinatorial Functions <sup>1</sup>  |                                            |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>PD</sub>                                    | Internal Array Module Delay                |          | 1.3  |          | 1.5  |          | 1.7  |           | 2.0  |          | 2.7  | ns    |
| t <sub>PDD</sub>                                   | Internal Decode Module Delay               |          | 1.6  |          | 1.8  |          | 2.0  |           | 2.4  |          | 3.3  | ns    |
| Logic Module Predicted Routing Delays <sup>2</sup> |                                            |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>RD1</sub>                                   | FO = 1 Routing Delay                       |          | 0.9  |          | 1.0  |          | 1.2  |           | 1.4  |          | 2.0  | ns    |
| t <sub>RD2</sub>                                   | FO = 2 Routing Delay                       |          | 1.3  |          | 1.4  |          | 1.6  |           | 1.9  |          | 2.7  | ns    |
| t <sub>RD3</sub>                                   | FO =3 Routing Delay                        |          | 1.6  |          | 1.8  |          | 2.0  |           | 2.4  |          | 3.4  | ns    |
| t <sub>RD4</sub>                                   | FO = 4 Routing Delay                       |          | 2.0  |          | 2.2  |          | 2.5  |           | 2.9  |          | 4.1  | ns    |
| t <sub>RD5</sub>                                   | FO = 8 Routing Delay                       |          | 3.3  |          | 3.7  |          | 4.2  |           | 4.9  |          | 6.9  | ns    |
| t <sub>RDD</sub>                                   | Decode-to-Output Routing Delay             |          | 0.3  |          | 0.4  |          | 0.4  |           | 0.5  |          | 0.7  | ns    |
| Logic Module Sequential Timing <sup>3, 4</sup>     |                                            |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>CO</sub>                                    | Flip-Flop Clock-to-Output                  |          | 1.3  |          | 1.4  |          | 1.6  |           | 1.9  |          | 2.7  | ns    |
| t <sub>GO</sub>                                    | Latch Gate-to-Output                       |          | 1.3  |          | 1.4  |          | 1.6  |           | 1.9  |          | 2.7  | ns    |
| t <sub>SUD</sub>                                   | Flip-Flop (Latch) Set-Up Time              | 0.3      |      | 0.3      |      | 0.4      |      | 0.5       |      | 0.7      |      | ns    |
| t <sub>HD</sub>                                    | Flip-Flop (Latch) Hold Time                | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>RO</sub>                                    | Flip-Flop (Latch) Reset-to-Output          |          | 1.6  |          | 1.7  |          | 2.0  |           | 2.3  |          | 3.2  | ns    |
| t <sub>SUENA</sub>                                 | Flip-Flop (Latch) Enable Set-Up            | 0.7      |      | 0.8      |      | 0.9      |      | 1.0       |      | 1.4      |      | ns    |
| t <sub>HENA</sub>                                  | Flip-Flop (Latch) Enable Hold              | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>WCLKA</sub>                                 | Flip-Flop (Latch) Clock Active Pulse Width | 3.3      |      | 3.7      |      | 4.2      |      | 4.9       |      | 6.9      |      | ns    |
| t <sub>WASYN</sub>                                 | Flip-Flop (Latch) Asynchronous Pulse Width | 4.4      |      | 4.8      |      | 5.5      |      | 6.4       |      | 9.0      |      | ns    |
| Synchronous SRAM Operations                        |                                            |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>RC</sub>                                    | Read Cycle Time                            |          | 6.8  |          | 7.5  |          | 8.5  |           | 10.0 |          | 14.0 | ns    |
| t <sub>WC</sub>                                    | Write Cycle Time                           |          | 6.8  |          | 7.5  |          | 8.5  |           | 10.0 |          | 14.0 | ns    |
| t <sub>RCKHL</sub>                                 | Clock HIGH/LOW Time                        |          | 3.4  |          | 3.8  |          | 4.3  |           | 5.0  |          | 7.0  | ns    |
| t <sub>RCO</sub>                                   | Data Valid After Clock HIGH/LOW            |          | 3.4  |          | 3.8  |          | 4.3  |           | 5.0  |          | 7.0  | ns    |
| t <sub>ADSU</sub>                                  | Address/Data Set-Up Time                   |          | 1.6  |          | 1.8  |          | 2.0  |           | 2.4  |          | 3.4  | ns    |
| Synchronous SRAM Operations (continued)            |                                            |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>ADH</sub>                                   | Address/Data Hold Time                     |          | 0.0  |          | 0.0  |          | 0.0  |           | 0.0  |          | 0.0  | ns    |
| t <sub>RENSU</sub>                                 | Read Enable Set-Up                         |          | 0.6  |          | 0.7  |          | 0.8  |           | 0.9  |          | 1.3  | ns    |
| t <sub>RENH</sub>                                  | Read Enable Hold                           |          | 3.4  |          | 3.8  |          | 4.3  |           | 5.0  |          | 7.0  | ns    |
| t <sub>WENSU</sub>                                 | Write Enable Set-Up                        |          | 2.7  |          | 3.0  |          | 3.4  |           | 4.0  |          | 5.6  | ns    |
| t <sub>WENH</sub>                                  | Write Enable Hold                          |          | 0.0  |          | 0.0  |          | 0.0  |           | 0.0  |          | 0.0  | ns    |
| t <sub>BENS</sub>                                  | Block Enable Set-Up                        |          | 2.8  |          | 3.1  |          | 3.5  |           | 4.1  |          | 5.7  | ns    |
| t <sub>BENH</sub>                                  | Block Enable Hold                          |          | 0.0  |          | 0.0  |          | 0.0  |           | 0.0  |          | 0.0  | ns    |

**Table 44 • A42MX36 Timing Characteristics (Nominal 5.0 V Operation)(Worst-Case Commercial Conditions, VCCA = 4.75 V, T<sub>J</sub> = 70°C)**


| Parameter / Description               |                                      |          | –3 Speed |      | –2 Speed |      | –1 Speed |      | Std Speed |      | –F Speed |      | Units |
|---------------------------------------|--------------------------------------|----------|----------|------|----------|------|----------|------|-----------|------|----------|------|-------|
|                                       |                                      |          | Min.     | Max. | Min.     | Max. | Min.     | Max. | Min.      | Max. | Min.     | Max. |       |
| t <sub>SUEXT</sub>                    | Input Latch External Set-Up          | FO = 32  | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
|                                       |                                      | FO = 635 | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>HEXT</sub>                     | Input Latch External Hold            | FO = 32  | 2.8      |      | 3.2      |      | 3.6      |      | 4.2       |      | 5.9      |      | ns    |
|                                       |                                      | FO = 635 | 3.3      |      | 3.7      |      | 4.2      |      | 4.9       |      | 6.9      |      | ns    |
| t <sub>P</sub>                        | Minimum Period (1/f <sub>MAX</sub> ) | FO = 32  | 5.5      |      | 6.1      |      | 6.6      |      | 7.6       |      | 12.7     |      | ns    |
|                                       |                                      | FO = 635 | 6.0      |      | 6.6      |      | 7.2      |      | 8.3       |      | 13.8     |      | ns    |
| f <sub>MAX</sub>                      | Maximum Datapath Frequency           | FO = 32  |          | 180  |          | 164  |          | 151  |           | 131  |          | 79   | MHz   |
|                                       |                                      | FO = 635 |          | 166  |          | 151  |          | 139  |           | 121  |          | 73   | MHz   |
| TTL Output Module Timing <sup>5</sup> |                                      |          |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>DLH</sub>                      | Data-to-Pad HIGH                     |          |          | 2.6  |          | 2.8  |          | 3.2  |           | 3.8  |          | 5.3  | ns    |
| t <sub>DHL</sub>                      | Data-to-Pad LOW                      |          |          | 3.0  |          | 3.3  |          | 3.7  |           | 4.4  |          | 6.2  | ns    |
| t <sub>ENZH</sub>                     | Enable Pad Z to HIGH                 |          |          | 2.7  |          | 3.0  |          | 3.3  |           | 3.9  |          | 5.5  | ns    |
| t <sub>ENZL</sub>                     | Enable Pad Z to LOW                  |          |          | 3.0  |          | 3.3  |          | 3.7  |           | 4.3  |          | 6.1  | ns    |
| t <sub>ENHZ</sub>                     | Enable Pad HIGH to Z                 |          |          | 5.3  |          | 5.8  |          | 6.6  |           | 7.8  |          | 10.9 | ns    |

**Table 45 • A42MX36 Timing Characteristics (Nominal 3.3 V Operation) (continued)**(Worst-Case Commercial Conditions, VCCA = 3.0 V, T<sub>J</sub> = 70°C)

| Parameter / Description                 |                                     | –3 Speed |      | –2 Speed |      | –1 Speed |      | Std Speed |      | –F Speed |      | Units |
|-----------------------------------------|-------------------------------------|----------|------|----------|------|----------|------|-----------|------|----------|------|-------|
|                                         |                                     | Min.     | Max. | Min.     | Max. | Min.     | Max. | Min.      | Max. | Min.     | Max. |       |
| Synchronous SRAM Operations (continued) |                                     |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>ADH</sub>                        | Address/Data Hold Time              | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>RENSU</sub>                      | Read Enable Set-Up                  | 0.9      |      | 1.0      |      | 1.1      |      | 1.3       |      | 1.8      |      | ns    |
| t <sub>RENH</sub>                       | Read Enable Hold                    | 4.8      |      | 5.3      |      | 6.0      |      | 7.0       |      | 9.8      |      | ns    |
| t <sub>WENSU</sub>                      | Write Enable Set-Up                 | 3.8      |      | 4.2      |      | 4.8      |      | 5.6       |      | 7.8      |      | ns    |
| t <sub>WENH</sub>                       | Write Enable Hold                   | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>BENS</sub>                       | Block Enable Set-Up                 | 3.9      |      | 4.3      |      | 4.9      |      | 5.7       |      | 8.0      |      | ns    |
| t <sub>BENH</sub>                       | Block Enable Hold                   | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| Asynchronous SRAM Operations            |                                     |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>RPD</sub>                        | Asynchronous Access Time            |          | 11.3 |          | 12.6 |          | 14.3 |           | 16.8 |          | 23.5 | ns    |
| t <sub>RDADV</sub>                      | Read Address Valid                  | 12.3     |      | 13.7     |      | 15.5     |      | 18.2      |      | 25.5     |      | ns    |
| t <sub>ADSU</sub>                       | Address/Data Set-Up Time            | 2.3      |      | 2.5      |      | 2.8      |      | 3.4       |      | 4.8      |      | ns    |
| t <sub>ADH</sub>                        | Address/Data Hold Time              | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>RENSUA</sub>                     | Read Enable Set-Up to Address Valid | 0.9      |      | 1.0      |      | 1.1      |      | 1.3       |      | 1.8      |      | ns    |
| t <sub>RENHA</sub>                      | Read Enable Hold                    | 4.8      |      | 5.3      |      | 6.0      |      | 7.0       |      | 9.8      |      | ns    |
| t <sub>WENSU</sub>                      | Write Enable Set-Up                 | 3.8      |      | 4.2      |      | 4.8      |      | 5.6       |      | 7.8      |      | ns    |
| t <sub>WENH</sub>                       | Write Enable Hold                   | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>DOH</sub>                        | Data Out Hold Time                  |          | 1.8  |          | 2.0  |          | 2.1  |           | 2.5  |          | 3.5  | ns    |
| Input Module Propagation Delays         |                                     |          |      |          |      |          |      |           |      |          |      |       |
| t <sub>INPY</sub>                       | Input Data Pad-to-Y                 |          | 1.4  |          | 1.6  |          | 1.8  |           | 2.1  |          | 3.0  | ns    |
| t <sub>INGO</sub>                       | Input Latch Gate-to-Output          |          | 2.0  |          | 2.2  |          | 2.5  |           | 2.9  |          | 4.1  | ns    |
| t <sub>INH</sub>                        | Input Latch Hold                    | 0.0      |      | 0.0      |      | 0.0      |      | 0.0       |      | 0.0      |      | ns    |
| t <sub>INSU</sub>                       | Input Latch Set-Up                  | 0.7      |      | 0.7      |      | 0.8      |      | 1.0       |      | 1.4      |      | ns    |
| t <sub>ILA</sub>                        | Latch Active Pulse Width            | 6.5      |      | 7.3      |      | 8.2      |      | 9.7       |      | 13.5     |      | ns    |

**Table 49 • PL84**

| <b>PL84</b>       |                         |                         |                         |                         |
|-------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| <b>Pin Number</b> | <b>A40MX04 Function</b> | <b>A42MX09 Function</b> | <b>A42MX16 Function</b> | <b>A42MX24 Function</b> |
| 84                | I/O                     | VCCA                    | VCCA                    | VCCA                    |

**Figure 41 • PQ100****Table 50 • PQ 100**

| <b>PQ100</b>      |                         |                         |                         |                         |
|-------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| <b>Pin Number</b> | <b>A40MX02 Function</b> | <b>A40MX04 Function</b> | <b>A42MX09 Function</b> | <b>A42MX16 Function</b> |
| 1                 | NC                      | NC                      | I/O                     | I/O                     |
| 2                 | NC                      | NC                      | DCLK, I/O               | DCLK, I/O               |
| 3                 | NC                      | NC                      | I/O                     | I/O                     |
| 4                 | NC                      | NC                      | MODE                    | MODE                    |
| 5                 | NC                      | NC                      | I/O                     | I/O                     |
| 6                 | PRB, I/O                | PRB, I/O                | I/O                     | I/O                     |
| 7                 | I/O                     | I/O                     | I/O                     | I/O                     |
| 8                 | I/O                     | I/O                     | I/O                     | I/O                     |
| 9                 | I/O                     | I/O                     | GND                     | GND                     |
| 10                | I/O                     | I/O                     | I/O                     | I/O                     |
| 11                | I/O                     | I/O                     | I/O                     | I/O                     |
| 12                | I/O                     | I/O                     | I/O                     | I/O                     |
| 13                | GND                     | GND                     | I/O                     | I/O                     |
| 14                | I/O                     | I/O                     | I/O                     | I/O                     |
| 15                | I/O                     | I/O                     | I/O                     | I/O                     |
| 16                | I/O                     | I/O                     | VCCA                    | VCCA                    |
| 17                | I/O                     | I/O                     | VCCI                    | VCCA                    |
| 18                | I/O                     | I/O                     | I/O                     | I/O                     |

**Table 50 • PQ 100**

| <b>PQ100</b>      |                         |                         |                         |                         |
|-------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| <b>Pin Number</b> | <b>A40MX02 Function</b> | <b>A40MX04 Function</b> | <b>A42MX09 Function</b> | <b>A42MX16 Function</b> |
| 93                | VCC                     | VCC                     | I/O                     | I/O                     |
| 94                | VCC                     | VCC                     | PRB, I/O                | PRB, I/O                |
| 95                | NC                      | I/O                     | I/O                     | I/O                     |
| 96                | NC                      | I/O                     | GND                     | GND                     |
| 97                | NC                      | I/O                     | I/O                     | I/O                     |
| 98                | SDI, I/O                | SDI, I/O                | I/O                     | I/O                     |
| 99                | DCLK, I/O               | DCLK, I/O               | I/O                     | I/O                     |
| 100               | PRA, I/O                | PRA, I/O                | I/O                     | I/O                     |

**Table 54 • PQ240**

| <b>PQ240</b>      |                         |
|-------------------|-------------------------|
| <b>Pin Number</b> | <b>A42MX36 Function</b> |
| 52                | VCCI                    |
| 53                | I/O                     |
| 54                | WD, I/O                 |
| 55                | WD, I/O                 |
| 56                | I/O                     |
| 57                | SDI, I/O                |
| 58                | I/O                     |
| 59                | VCCA                    |
| 60                | GND                     |
| 61                | GND                     |
| 62                | I/O                     |
| 63                | I/O                     |
| 64                | I/O                     |
| 65                | I/O                     |
| 66                | I/O                     |
| 67                | I/O                     |
| 68                | I/O                     |
| 69                | I/O                     |
| 70                | I/O                     |
| 71                | VCCI                    |
| 72                | I/O                     |
| 73                | I/O                     |
| 74                | I/O                     |
| 75                | I/O                     |
| 76                | I/O                     |
| 77                | I/O                     |
| 78                | I/O                     |
| 79                | I/O                     |
| 80                | I/O                     |
| 81                | I/O                     |
| 82                | I/O                     |
| 83                | I/O                     |
| 84                | I/O                     |
| 85                | VCCA                    |
| 86                | I/O                     |
| 87                | I/O                     |
| 88                | VCCA                    |

**Table 54 • PQ240**

| <b>PQ240</b>      |                         |
|-------------------|-------------------------|
| <b>Pin Number</b> | <b>A42MX36 Function</b> |
| 126               | WD, I/O                 |
| 127               | I/O                     |
| 128               | VCCI                    |
| 129               | I/O                     |
| 130               | I/O                     |
| 131               | I/O                     |
| 132               | WD, I/O                 |
| 133               | WD, I/O                 |
| 134               | I/O                     |
| 135               | QCLKB, I/O              |
| 136               | I/O                     |
| 137               | I/O                     |
| 138               | I/O                     |
| 139               | I/O                     |
| 140               | I/O                     |
| 141               | I/O                     |
| 142               | WD, I/O                 |
| 143               | WD, I/O                 |
| 144               | I/O                     |
| 145               | I/O                     |
| 146               | I/O                     |
| 147               | I/O                     |
| 148               | I/O                     |
| 149               | I/O                     |
| 150               | VCCI                    |
| 151               | VCCA                    |
| 152               | GND                     |
| 153               | I/O                     |
| 154               | I/O                     |
| 155               | I/O                     |
| 156               | I/O                     |
| 157               | I/O                     |
| 158               | I/O                     |
| 159               | WD, I/O                 |
| 160               | WD, I/O                 |
| 161               | I/O                     |
| 162               | I/O                     |

**Table 58 • CQ208**

| <b>CQ208</b>      |                         |
|-------------------|-------------------------|
| <b>Pin Number</b> | <b>A42MX36 Function</b> |
| 111               | I/O                     |
| 112               | I/O                     |
| 113               | I/O                     |
| 114               | I/O                     |
| 115               | I/O                     |
| 116               | I/O                     |
| 117               | I/O                     |
| 118               | I/O                     |
| 119               | I/O                     |
| 120               | I/O                     |
| 121               | I/O                     |
| 122               | I/O                     |
| 123               | I/O                     |
| 124               | I/O                     |
| 125               | I/O                     |
| 126               | GND                     |
| 127               | I/O                     |
| 128               | TCK, I/O                |
| 129               | LP                      |
| 130               | VCCA                    |
| 131               | GND                     |
| 132               | VCCI                    |
| 133               | VCCA                    |
| 134               | I/O                     |
| 135               | I/O                     |
| 136               | VCCA                    |
| 137               | I/O                     |
| 138               | I/O                     |
| 139               | I/O                     |
| 140               | I/O                     |
| 141               | I/O                     |
| 142               | I/O                     |
| 143               | I/O                     |
| 144               | I/O                     |
| 145               | I/O                     |
| 146               | I/O                     |
| 147               | I/O                     |

Figure 50 • CQ256




Table 59 • CQ256

| CQ256      |                  |
|------------|------------------|
| Pin Number | A42MX36 Function |
| 1          | NC               |
| 2          | GND              |
| 3          | I/O              |
| 4          | I/O              |
| 5          | I/O              |
| 6          | I/O              |
| 7          | I/O              |
| 8          | I/O              |
| 9          | I/O              |
| 10         | GND              |
| 11         | I/O              |
| 12         | I/O              |
| 13         | I/O              |
| 14         | I/O              |
| 15         | I/O              |
| 16         | I/O              |
| 17         | I/O              |
| 18         | I/O              |
| 19         | I/O              |
| 20         | I/O              |
| 21         | I/O              |

**Table 59 • CQ256**

| <b>CQ256</b>      |                         |
|-------------------|-------------------------|
| <b>Pin Number</b> | <b>A42MX36 Function</b> |
| 22                | I/O                     |
| 23                | I/O                     |
| 24                | I/O                     |
| 25                | I/O                     |
| 26                | VCCA                    |
| 27                | I/O                     |
| 28                | I/O                     |
| 29                | VCCA                    |
| 30                | VCCI                    |
| 31                | GND                     |
| 32                | VCCA                    |
| 33                | LP                      |
| 34                | TCK, I/O                |
| 35                | I/O                     |
| 36                | GND                     |
| 37                | I/O                     |
| 38                | I/O                     |
| 39                | I/O                     |
| 40                | I/O                     |
| 41                | I/O                     |
| 42                | I/O                     |
| 43                | I/O                     |
| 44                | I/O                     |
| 45                | I/O                     |
| 46                | I/O                     |
| 47                | I/O                     |
| 48                | GND                     |
| 49                | I/O                     |
| 50                | I/O                     |
| 51                | I/O                     |
| 52                | I/O                     |
| 53                | I/O                     |
| 54                | I/O                     |
| 55                | I/O                     |
| 56                | I/O                     |
| 57                | I/O                     |
| 58                | I/O                     |

**Table 60 • BG272**

| <b>BG272</b>      |                         |
|-------------------|-------------------------|
| <b>Pin Number</b> | <b>A42MX36 Function</b> |
| A6                | I/O                     |
| A7                | WD, I/O                 |
| A8                | WD, I/O                 |
| A9                | I/O                     |
| A10               | I/O                     |
| A11               | CLKA                    |
| A12               | I/O                     |
| A13               | I/O                     |
| A14               | I/O                     |
| A15               | I/O                     |
| A16               | WD, I/O                 |
| A17               | I/O                     |
| A18               | I/O                     |
| A19               | GND                     |
| A20               | GND                     |
| B1                | GND                     |
| B2                | GND                     |
| B3                | DCLK, I/O               |
| B4                | I/O                     |
| B5                | I/O                     |
| B6                | I/O                     |
| B7                | WD, I/O                 |
| B8                | I/O                     |
| B9                | PRB, I/O                |
| B10               | I/O                     |
| B11               | I/O                     |
| B12               | WD, I/O                 |
| B13               | I/O                     |
| B14               | I/O                     |
| B15               | WD, I/O                 |
| B16               | I/O                     |
| B17               | WD, I/O                 |
| B18               | I/O                     |
| B19               | GND                     |
| B20               | GND                     |
| C1                | I/O                     |
| C2                | MODE                    |

**Table 61 • PG132**

| <b>PG132</b>      |                         |
|-------------------|-------------------------|
| <b>Pin Number</b> | <b>A42MX09 Function</b> |
| N10               | I/O                     |
| M10               | I/O                     |
| N11               | I/O                     |
| L10               | I/O                     |
| M11               | I/O                     |
| N12               | SDO                     |
| M12               | I/O                     |
| L11               | I/O                     |
| N13               | I/O                     |
| M13               | I/O                     |
| K11               | I/O                     |
| L12               | I/O                     |
| L13               | I/O                     |
| K13               | I/O                     |
| H10               | I/O                     |
| J12               | I/O                     |
| J13               | I/O                     |
| H11               | I/O                     |
| H12               | I/O                     |
| H13               | VKS                     |
| G13               | VPP                     |

**Table 62 • CQ172**

|     |       |
|-----|-------|
| 138 | I/O   |
| 139 | I/O   |
| 140 | I/O   |
| 141 | GND   |
| 142 | I/O   |
| 143 | I/O   |
| 144 | I/O   |
| 145 | I/O   |
| 146 | I/O   |
| 147 | I/O   |
| 148 | PROBA |
| 149 | I/O   |
| 150 | CLKA  |
| 151 | VCC   |
| 152 | GND   |
| 153 | I/O   |
| 154 | CLKB  |
| 155 | I/O   |
| 156 | PROBB |
| 157 | I/O   |
| 158 | I/O   |
| 159 | I/O   |
| 160 | I/O   |
| 161 | GND   |
| 162 | I/O   |
| 163 | I/O   |
| 164 | I/O   |
| 165 | I/O   |
| 166 | VCCI  |
| 167 | I/O   |
| 168 | I/O   |
| 169 | I/O   |
| 170 | I/O   |
| 171 | DCLK  |