Welcome to <u>E-XFL.COM</u>

What is "Embedded - Microcontrollers"?

"Embedded - Microcontrollers" refer to small, integrated circuits designed to perform specific tasks within larger systems. These microcontrollers are essentially compact computers on a single chip, containing a processor core, memory, and programmable input/output peripherals. They are called "embedded" because they are embedded within electronic devices to control various functions, rather than serving as standalone computers. Microcontrollers are crucial in modern electronics, providing the intelligence and control needed for a wide range of applications.

Applications of "<u>Embedded -</u> <u>Microcontrollers</u>"

Details

Product Status	Active
Core Processor	ARM® Cortex®-M3
Core Size	32-Bit Single-Core
Speed	60MHz
Connectivity	CSIO, EBI/EMI, I ² C, LINbus, UART/USART, USB
Peripherals	DMA, LVD, POR, PWM, WDT
Number of I/O	154
Program Memory Size	1.5625MB (1.5625M x 8)
Program Memory Type	FLASH
EEPROM Size	-
RAM Size	192К х 8
Voltage - Supply (Vcc/Vdd)	2.7V ~ 5.5V
Data Converters	A/D 24x12b; D/A 2x10b
Oscillator Type	Internal
Operating Temperature	-40°C ~ 105°C (TA)
Mounting Type	Surface Mount
Package / Case	192-LFBGA
Supplier Device Package	192-FBGA (12x12)
Purchase URL	https://www.e-xfl.com/product-detail/infineon-technologies/mb9bf329tbgl-ge1

Email: info@E-XFL.COM

Address: Room A, 16/F, Full Win Commercial Centre, 573 Nathan Road, Mongkok, Hong Kong



The following document contains information on Cypress products. Although the document is marked with the name "Spansion", the company that originally developed the specification, Cypress will continue to offer these products to new and existing customers.

Continuity of Specifications

There is no change to this document as a result of offering the device as a Cypress product. Any changes that have been made are the result of normal document improvements and are noted in the document history page, where supported. Future revisions will occur when appropriate, and changes will be noted in a document history page.

Continuity of Ordering Part Numbers

Cypress continues to support existing part numbers. To order these products, please use only the Ordering Part Numbers listed in this document.

For More Information

Please contact your local sales office for additional information about Cypress products and solutions.

About Cypress

Cypress (NASDAQ: CY) delivers high-performance, high-quality solutions at the heart of today's most advanced embedded systems, from automotive, industrial and networking platforms to highly interactive consumer and mobile devices. With a broad, differentiated product portfolio that includes NOR flash memories, F-RAM[™] and SRAM, Traveo[™] microcontrollers, the industry's only PSoC[®] programmable system-on-chip solutions, analog and PMIC Power Management ICs, CapSense[®] capacitive touch-sensing controllers, and Wireless BLE Bluetooth[®] Low-Energy and USB connectivity solutions, Cypress is committed to providing its customers worldwide with consistent innovation, best-in-class support and exceptional system value.

MB9B320T Series

32-bit Microcontroller FM3 Family

Fact Sheet



MB9B320T Series are highly integrated 32-bit microcontrollers dedicated for embedded controllers with low power consumption mode and competitive cost. MB9B320T Series are based on the ARM Cortex-M3 Processor with Flash memory and SRAM, and has peripheral functions such as various timers, ADCs, DACs and Communication Interfaces.

FEATURES 1.

- 32bit ARM Cortex-M3 Core : Processor version : r2p1
- Clock : Maximum clock frequency : 60MHz
- **Base Timer** : 16 channels (Max.)
- Multi-function Timer : 1 unit (Max.)
- 16-bit free-run timer x3channels
- _ Input capture ×4channels
- _ Output compare x6channels
- _ A/D activation compare x2channels
- Waveform generator x3channels _
- 16-bit PPG timer ×3channels _
- QPRC
- MB9BF328S/329S : 1 channel (Max.) MB9BF328T/329T : 2 channels (Max.)
- **Dual Timer** : 1 unit
- Watch dog Timer : 1 channel (SW) + 1 channel (HW)
- Multi-function Serial Interface : 16 channels (Max.)
- Selectable from UART/CSIO/LIN/I²C
- **External Bus Interface**
- **DMA Controller** : 8channels
- USB2.0(Function/Host) : 1 channel (Max.)
- Real-Time Clock : 1 unit
- HDMI-CEC/Remote control : 2 channels (Max.)
- Watch counter : 1 unit
- External Interrupt Controller Unit
- Up to 32 external interrupt input pins
- Include one non-maskable interrupt (NMI)
- 12-bit A/D Converter : Max. 24 channels (2 units)
- 10-bit D/A Converter : Max. 2 channels (Max.)
- CRC Accelerator
- Low Power Mode
- 6 low power consumption modes supported
- SLEEP mode/TIMER mode/RTC mode/Deep standby RTC mode/STOP mode/Deep standby STOP mode
- General Purpose I/O port : 154 (Max.)
- Unique ID
- **Built-in CR**
- Debug
- Serial Wire JTAG Debug Port (SWJ-DP)
- Embedded Trace Macrocells (ETM)
- Low Voltage Detector
- **Clock Super Visor**
- Power Supply : 2.7 to 5.5V

2. PRODUCT LINEUP

Part number Parameter	MB9BF328S/T	MB9BF329S/T
Flash Main area (Byte)	1M	1.5M
Flash Work area (Byte)	64K	64K
RAM (Byte)	160K	192K

ORDERING INFORMATION 3.

Part number	Package	
MB9BF328SPMC	Plastic • LQFP(0.5mm pitch),144-pin (FPT-144P-M08)	
MB9BF329SPMC		
MB9BF328TPMC	Plastic • LQFP(0.5mm pitch),176-pin (FPT-176P-M07)	
MB9BF329TPMC		
MB9BF328TBGL	Plastic • BGA(0.8mm pitch),192-pin (BGA-192P-M06)	
MB9BF329TBGL		

PACKAGE EXAMPLE OF 4. REFERENCE



Plastic · LQFP、176-pins (FPT-176P-M07)

Publication Number MB9B320T_NP706-00041

Revision 1.0

Copyright © 2013-2014 Spansion All rights reserved. Spansion[®], the Spansion logo, MirrorBit[®], MirrorBit[®] Eclipse[™], ORNAND[™] and combinations thereof, are trademarks and registered trademarks of Spansion LLC in the United States and other countries. Other names used are for informational purposes only and may be trademarks of their respective owners.



5. BLOCK DIAGRAM



ARM and Cortex are the registered trademarks of ARM Limited in the EU and other countries.

2