




Welcome to [E-XFL.COM](https://www.e-xfl.com)

Understanding Embedded - FPGAs (Field Programmable Gate Array)

Embedded - FPGAs, or Field Programmable Gate Arrays, are advanced integrated circuits that offer unparalleled flexibility and performance for digital systems. Unlike traditional fixed-function logic devices, FPGAs can be programmed and reprogrammed to execute a wide array of logical operations, enabling customized functionality tailored to specific applications. This reprogrammability allows developers to iterate designs quickly and implement complex functions without the need for custom hardware.

Applications of Embedded - FPGAs

The versatility of Embedded - FPGAs makes them indispensable in numerous fields. In telecommunications.

Details

Product Status	Active
Number of LABs/CLBs	-
Number of Logic Elements/Cells	109000
Total RAM Bits	7782400
Number of I/O	284
Number of Gates	-
Voltage - Supply	0.97V ~ 1.08V
Mounting Type	Surface Mount
Operating Temperature	-40°C ~ 100°C (TJ)
Package / Case	484-BBGA, FCBGA
Supplier Device Package	484-FCBGA (23x23)
Purchase URL	https://www.e-xfl.com/product-detail/microchip-technology/mpf100ts-fcvg484i

7.3.2	SRAM Blocks	41
7.4	Transceiver Switching Characteristics	42
7.4.1	Transceiver Performance	42
7.4.2	Transceiver Reference Clock Performance	42
7.4.3	Transceiver Reference Clock I/O Standards	43
7.4.4	Transceiver Interface Performance	44
7.4.5	Transmitter Performance	44
7.4.6	Receiver Performance	47
7.5	Transceiver Protocol Characteristics	48
7.5.1	PCI Express	48
7.5.2	Interlaken	49
7.5.3	10GbE (10GBASE-R, and 10GBASE-KR)	49
7.5.4	1GbE (1000BASE-T)	50
7.5.5	SGMII and QSGMII	50
7.5.6	SDI	50
7.5.7	CPRI	51
7.5.8	JESD204B	51
7.6	Non-Volatile Characteristics	51
7.6.1	FPGA Programming Cycle and Retention	52
7.6.2	FPGA Programming Time	52
7.6.3	FPGA Bitstream Sizes	53
7.6.4	Digest Cycles	53
7.6.5	Digest Time	54
7.6.6	Zeroization Time	55
7.6.7	Verify Time	57
7.6.8	Authentication Time	58
7.6.9	Secure NVM Performance	58
7.6.10	Secure NVM Programming Cycles	59
7.7	System Services	59
7.7.1	System Services Throughput Characteristics	59
7.8	Fabric Macros	60
7.8.1	UJTAG Switching Characteristics	60
7.8.2	UJTAG_SEC Switching Characteristics	61
7.8.3	USPI Switching Characteristics	62
7.8.4	Tamper Detectors	62
7.8.5	System Controller Suspend Switching Characteristics	64
7.8.6	Dynamic Reconfiguration Interface	64
7.9	Power-Up to Functional Timing	64
7.9.1	Power-On (Cold) Reset Initialization Sequence	64
7.9.2	Warm Reset Initialization Sequence	65
7.9.3	Power-On Reset Voltages	66

7.9.4	Design Dependence of T PUFT and T WRFT	67
7.9.5	Cold Reset to Fabric and I/Os (Low Speed) Functional	67
7.9.6	Warm Reset to Fabric and I/Os (Low Speed) Functional	67
7.9.7	Miscellaneous Initialization Parameters	67
7.9.8	I/O Calibration	68
7.10	Dedicated Pins	69
7.10.1	JTAG Switching Characteristics	69
7.10.2	SPI Switching Characteristics	69
7.10.3	SmartDebug Probe Switching Characteristics	70
7.10.4	DEVRST_N Switching Characteristics	70
7.10.5	FF_EXIT Switching Characteristics	70
7.11	User Crypto	71
7.11.1	TeraFire 5200B Switching Characteristics	71
7.11.2	TeraFire 5200B Throughput Characteristics	71

Parameter	Symbol	Min	Typ	Max	Unit
Transceiver TX and RX lanes supply at 1.05 V mode (when any lane rate is greater than 10.3125 Gbps) ¹	V _{DDA}	1.02	1.05	1.08	V
Programming and HSIO receiver supply	V _{DD18}	1.71	1.80	1.89	V
FPGA core and FPGA PLL high-voltage supply	V _{DD25}	2.425	2.50	2.575	V
Transceiver PLL high-voltage supply	V _{DDA25}	2.425	2.50	2.575	V
Transceiver reference clock supply –3.3 V nominal	V _{DD_XCVR_CLK}	3.135	3.3	3.465	V
Transceiver reference clock supply –2.5 V nominal	V _{DD_XCVR_CLK}	2.375	2.5	2.625	V
Global V _{REF} for transceiver reference clocks ³	XCVR _{VREF}	Ground		V _{DD_XCVR_CLK}	V
HSIO DC I/O supply. Allowed nominal options: 1.2 V, 1.35 V, 1.5 V, and 1.8 V ⁴	V _{DDI_x}	1.14	Various	1.89	V
GPIO DC I/O supply. Allowed nominal options: 1.2 V, 1.5 V, 1.8 V, 2.5 V, and 3.3 V ^{2,4}	V _{DDI_x}	1.14	Various	3.465	V
Dedicated I/O DC supply for JTAG and SPI (GPIO Bank 3). Allowed nominal options: 1.8 V, 2.5 V, and 3.3 V	V _{DDI3}	1.71	Various	3.465	V
GPIO auxiliary supply for I/O bank x with V _{DDI_x} = 3.3 V nominal ^{2,4}	V _{DDAUX_x}	3.135	3.3	3.465	V
GPIO auxiliary supply for I/O bank x with V _{DDI_x} = 2.5 V nominal or lower ^{2,4}	V _{DDAUX_x}	2.375	2.5	2.625	V
Extended commercial temperature range	T _J	0		100	°C
Industrial temperature range	T _J	–40		100	°C
Extended commercial programming temperature range	T _{PRG}	0		100	°C
Industrial programming temperature range	T _{PRG}	–40		100	°C

1. V_{DD} and V_{DDA} can independently operate at 1.0 V or 1.05 V nominal. These supplies are not dynamically adjustable.
2. For GPIO buffers where I/O bank is designated as bank number, if V_{DDI_x} is 2.5 V nominal or 3.3 V nominal, V_{DDAUX_x} must be connected to the V_{DDI_x} supply for that bank. If V_{DDI_x} for a given GPIO bank is <2.5 V nominal, V_{DDAUX_x} per I/O bank must be powered at 2.5 V nominal.
3. XCVR_{VREF} globally sets the reference voltage of the transceiver's single-ended reference clock input buffers. It is typically near V_{DD_XCVR_CLK}/2 V but is allowed in the specified range.
4. The power supplies for a given I/O bank x are shown as VDDI_x and VDDAUX_x.

Table 8 • Maximum Overshoot During Transitions for GPIO

AC (V _{IN}) Overshoot Duration as % at T _J = 100 °C	Condition (V)
100	3.8
100	3.85
100	3.9
100	3.95
70	4
50	4.05
33	4.1
22	4.15
14	4.2
9.8	4.25
6.5	4.3
4.4	4.35
3	4.4
2	4.45
1.4	4.5
0.9	4.55
0.6	4.6

Note: Overshoot level is for V_{DDI} at 3.3 V.

The following table shows the maximum AC input voltage (V_{IN}) undershoot duration for GPIO.

Table 9 • Maximum Undershoot During Transitions for GPIO

AC (V _{IN}) Undershoot Duration as % at T _J = 100 °C	Condition (V)
100	-0.5
100	-0.55
100	-0.6
100	-0.65
100	-0.7
100	-0.75
100	-0.8
100	-0.85
100	-0.9
100	-0.95
100	-1
100	-1.05
100	-1.1
100	-1.15
100	-1.2
69	-1.25
45	-1.3

I/O Standard	V _{DDI} Min (V)	V _{DDI} Typ (V)	V _{DDI} Max (V)	V _{IL} Min (V)	V _{IL} Max (V)	V _{IH} Min (V)	V _{IH} ¹ Max (V)
SSTL135I	1.283	1.35	1.418	-0.3	V _{REF} - 0.09	V _{REF} + 0.09	1.418
SSTL135II	1.283	1.35	1.418	-0.3	V _{REF} - 0.09	V _{REF} + 0.09	1.418
HSTL15I	1.425	1.5	1.575	-0.3	V _{REF} - 0.1	V _{REF} + 0.1	1.575
HSTL15II	1.425	1.5	1.575	-0.3	V _{REF} - 0.1	V _{REF} + 0.1	1.575
HSTL135I	1.283	1.35	1.418	-0.3	V _{REF} - 0.09	V _{REF} + 0.09	1.418
HSTL135II	1.283	1.35	1.418	-0.3	V _{REF} - 0.09	V _{REF} + 0.09	1.418
HSTL12I	1.14	1.2	1.26	-0.3	V _{REF} - 0.1	V _{REF} + 0.1	1.26
HSTL12II	1.14	1.2	1.26	-0.3	V _{REF} - 0.1	V _{REF} + 0.1	1.26
HSUL18I	1.71	1.8	1.89	-0.3	0.3 x V _{DDI}	0.7 x V _{DDI}	1.89
HSUL18II	1.71	1.8	1.89	-0.3	0.3 x V _{DDI}	0.7 x V _{DDI}	1.89
HSUL12I	1.14	1.2	1.26	-0.3	V _{REF} - 0.1	V _{REF} + 0.1	1.26
POD12I	1.14	1.2	1.26	-0.3	V _{REF} - 0.08	V _{REF} + 0.08	1.26
POD12II	1.14	1.2	1.26	-0.3	V _{REF} - 0.08	V _{REF} + 0.08	1.26

1. GPIO V_{IH} max is 3.45 V with PCI clamp diode turned off regardless of mode, that is, over-voltage tolerant.

2. For external stub-series resistance. This resistance is on-die for GPIO.

Note: 3.3 V and 2.5 V are only supported in GPIO banks.

Table 13 • DC Output Levels

I/O Standard	V _{DDI} Min (V)	V _{DDI} Typ (V)	V _{DDI} Max (V)	V _{OL} Min (V)	V _{OL} Max (V)	V _{OH} Min (V)	V _{OH} Max (V)	I _{OL} ^{2,6} mA	I _{OH} ^{2,6} mA
PCI ¹	3.15	3.3	3.45		0.1 x V _{DDI}	0.9 x V _{DDI}		1.5	0.5
LVTTL	3.15	3.3	3.45		0.4	2.4			
LVC MOS33	3.15	3.3	3.45		0.4	V _{DDI} – 0.4			
LVC MOS25	2.375	2.5	2.625		0.4	V _{DDI} – 0.4			
LVC MOS18	1.71	1.8	1.89		0.45	V _{DDI} – 0.45			
LVC MOS15	1.425	1.5	1.575		0.25 x V _{DDI}	0.75 x V _{DDI}			
LVC MOS12	1.14	1.2	1.26		0.25 x V _{DDI}	0.75 x V _{DDI}			
SSTL25I ³	2.375	2.5	2.625		V _{TT} – 0.608	V _{TT} + 0.608		8.1	8.1
SSTL25II ³	2.375	2.5	2.625		V _{TT} – 0.810	V _{TT} + 0.810		16.2	16.2
SSTL18I ³	1.71	1.8	1.89		V _{TT} – 0.603	V _{TT} + 0.603		6.7	6.7
SSTL18II ³	1.71	1.8	1.89		V _{TT} – 0.603	V _{TT} + 0.603		13.4	13.4
SSTL15I ⁴	1.425	1.5	1.575		0.2 x V _{DDI}	0.8 x V _{DDI}		V _{OL} /40	(V _{DDI} – V _{OH})/40
SSTL15II ⁴	1.425	1.5	1.575		0.2 x V _{DDI}	0.8 x V _{DDI}		V _{OL} /34	(V _{DDI} – V _{OH})/34
SSTL135I ⁴	1.283	1.35	1.418		0.2 x V _{DDI}	0.8 x V _{DDI}		V _{OL} /40	(V _{DDI} – V _{OH})/40
SSTL135II ⁴	1.283	1.35	1.418		0.2 x V _{DDI}	0.8 x V _{DDI}		V _{OL} /34	(V _{DDI} – V _{OH})/34
HSTL15I	1.425	1.5	1.575		0.4	V _{DDI} – 0.4		8	8
HSTL15II	1.425	1.5	1.575		0.4	V _{DDI} – 0.4		16	16

I/O Standard	V _{DDI} Min (V)	V _{DDI} Typ (V)	V _{DDI} Max (V)	V _{OL} Min (V)	V _{OL} Max (V)	V _{OH} Min (V)	V _{OH} Max (V)	I _{OL} ^{2,6} mA	I _{OH} ^{2,6} mA
HSTL135I ⁴	1.283	1.35	1.418		0.2 x V _{DDI}	0.8 x V _{DDI}		V _{OL} /50	(V _{DDI} – V _{OH}) /50
HSTL135II ⁴	1.283	1.35	1.418		0.2 x V _{DDI}	0.8 x V _{DDI}		V _{OL} /25	(V _{DDI} – V _{OH}) /25
HSTL12I ⁴	1.14	1.2	1.26		0.1 x V _{DDI}	0.9 x V _{DDI}		V _{OL} /50	(V _{DDI} – V _{OH}) /50
HSTL12II ⁴	1.14	1.2	1.26		0.1 x V _{DDI}	0.9 x V _{DDI}		V _{OL} /25	(V _{DDI} – V _{OH}) /25
HSUL18I ⁴	1.71	1.8	1.89		0.1 x V _{DDI}	0.9 x V _{DDI}		V _{OL} /55	(V _{DDI} – V _{OH}) /55
HSUL18II ⁴	1.71	1.8	1.89		0.1 x V _{DDI}	0.9 x V _{DDI}		V _{OL} /25	(V _{DDI} – V _{OH}) /25
HSUL12I ⁴	1.14	1.2	1.26		0.1 x V _{DDI}	0.9 x V _{DDI}		V _{OL} /40	(V _{DDI} – V _{OH}) /40
POD12I ^{4,5}	1.14	1.2	1.26		0.5 x V _{DDI}			V _{OL} /48	(V _{DDI} – V _{OH}) /48
POD12II ^{4,5}	1.14	1.2	1.26		0.5 x V _{DDI}			V _{OL} /34	(V _{DDI} – V _{OH}) /34

1. Drive strengths per PCI specification V/I curves.
2. Refer to [UG0686: PolarFire FPGA User I/O User Guide](#) for details on supported drive strengths.
3. For external stub-series resistance. This resistance is on-die for GPIO.
4. I_{OL}/I_{OH} units for impedance standards in amps (not mA).
5. V_{OH_MAX} based on external pull-up termination (pseudo-open drain).
6. The total DC sink/source current of all IOs within a lane is limited as follows:
 - a. HSIO lane: 120 mA per 12 IO buffers.
 - b. GPIO lane: 160 mA per 12 IO buffers.

Note: 3.3 V and 2.5 V are only supported in GPIO banks.

6.3.2 Differential DC Input and Output Levels

The follow tables list the differential DC I/O levels.

Table 14 • Differential DC Input Levels

I/O Standard	Bank Type	VICM_RANGE Libero Setting	V _{ICM} ^{1,3} Min (V)	V _{ICM} ^{1,3} Typ (V)	V _{ICM} ^{1,3} Max (V)	V _{ID} ² Min (V)	V _{ID} Typ (V)	V _{ID} Max (V)
LVDS33	GPIO	Mid (default)	0.6	1.25	2.35	0.1	0.35	0.6
		Low	0.05	0.4	0.8	0.1	0.35	0.6
LVDS25	GPIO	Mid (default)	0.6	1.25	2.35	0.1	0.35	0.6
		Low	0.05	0.4	0.8	0.1	0.35	0.6
LVDS18 ⁴	GPIO	Mid (default)	0.6	1.25	1.65	0.1	0.35	0.6

I/O Standard	Bank Type	VICM_RANGE Libero Setting	V _{ICM} ^{1,3} Min (V)	V _{ICM} ^{1,3} Typ (V)	V _{ICM} ^{1,3} Max (V)	V _{ID} ² Min (V)	V _{ID} Typ (V)	V _{ID} Max (V)
HCSL25 ⁶	GPIO	Mid (default)	0.6	1.25	2.35	0.1	0.55	1.1
		Low	0.05	0.35	0.8	0.1	0.55	1.1
HCSL18 ⁵	HSIO	Mid (default)	0.6	1.0	1.65	0.1	0.55	1.1
		Low	0.05	0.4	0.8	0.1	0.55	1.1
BUSLVDSE25	GPIO	Mid (default)	0.6	1.25	2.35	0.05	0.1	V _{DDIn}
		Low	0.05	0.4	0.8	0.05	0.1	V _{DDIn}
MLVDSE25	GPIO	Mid (default)	0.6	1.25	2.35	0.05	0.35	2.4
		Low	0.05	0.4	0.8	0.05	0.35	2.4
LVPECL33	GPIO	Mid (default)	0.6	1.65	2.35	0.05	0.8	2.4
		Low	0.05	0.4	0.8	0.05	0.8	2.4
LVPECL33	GPIO	Mid (default)	0.6	1.65	2.35	0.05	0.8	2.4
		Low	0.05	0.4	0.8	0.05	0.8	2.4
MIPI25	GPIO	Mid (default)	0.6	1.25	2.35	0.05	0.2	0.3
		Low	0.05	0.2	0.8	0.05	0.2	0.3

1. V_{ICM} is the input common mode.
2. V_{ID} is the input differential voltage.
3. V_{ICM} rules are as follows:
 - a. V_{ICM} must be less than V_{DDI} – 0.4 V;
 - b. V_{ICM} + V_{ID}/2 must be <V_{DDI} + 0.4 V;
 - c. V_{ICM} – V_{ID}/2 must be >V_{SS} – 0.3 V;
 - d. Any differential input with V_{ICM} ≤ 0.6 V requires the low common mode setting in Libero (VICM_RANGE=LOW).
4. V_{DDI} = 1.8 V, V_{DDAUX} = 2.5 V.
5. HSIO receiver only.
6. GPIO receiver only.

Table 15 • Differential DC Output Levels

I/O Standard	Bank Type	V _{OCM} ¹ Min (V)	V _{OCM} Typ (V)	V _{OCM} Max (V)	V _{OD} ² Min (V)	V _{OD} ² Typ (V)	V _{OD} ² Max (V)
LVDS33	GPIO		1.2		0.25	0.35	0.45
LVDS25	GPIO		1.2		0.25	0.35	0.45
LCMDS33	GPIO		0.6		0.25	0.35	0.45
LCMDS25	GPIO		0.6		0.25	0.35	0.45
RSDS33	GPIO		1.2		0.17	0.2	0.23
RSDS25	GPIO		1.2		0.17	0.2	0.23
MINILVDS33	GPIO		1.2		0.3	0.4	0.6
MINILVDS25	GPIO		1.2		0.3	0.4	0.6
SUBLVDS33	GPIO		0.9		0.1	0.15	0.3
SUBLVDS25	GPIO		0.9		0.1	0.15	0.3
PPDS33	GPIO		0.8		0.17	0.2	0.23
PPDS25	GPIO		0.8		0.17	0.2	0.23
SLVSE15 ³	GPIO, HSIO		0.2		0.12	0.135	0.15
BUSLVDSE25 ³	GPIO		1.25		0.24	0.262	0.272

I/O Standard	Bank Type	V _{OCM} ¹ Min (V)	V _{OCM} Typ (V)	V _{OCM} Max (V)	V _{OD} ² Min (V)	V _{OD} ² Typ (V)	V _{OD} ² Max (V)
MLVDSSE25 ³	GPIO		1.25		0.396	0.442	0.453
LVPECL33 ³	GPIO		1.65		0.664	0.722	0.755
MIPIE25 ³	GPIO		0.25		0.1	0.22	0.3

1. V_{OCM} is the output common mode voltage.
2. V_{OD} is the output differential voltage.
3. Emulated output only.

6.3.3 Complementary Differential DC Input and Output Levels



The following tables list the complementary differential DC I/O levels.

Table 16 • Complementary Differential DC Input Levels

I/O Standard	V _{DDI} Min (V)	V _{DDI} Typ (V)	V _{DDI} Max (V)	V _{ICM} ^{1,3} Min (V)	V _{ICM} ^{1,3} Typ (V)	V _{ICM} ^{1,3} Max (V)	V _{ID} ² Min (V)	V _{ID} Max (V)
SSTL25I	2.375	2.5	2.625	1.164	1.250	1.339	0.1	
SSTL25II	2.375	2.5	2.625	1.164	1.250	1.339	0.1	
SSTL18I	1.71	1.8	1.89	0.838	0.900	0.964	0.1	
SSTL18II	1.71	1.8	1.89	0.838	0.900	0.964	0.1	
SSTL15I	1.425	1.5	1.575	0.698	0.750	0.803	0.1	
SSTL15II	1.425	1.5	1.575	0.698	0.750	0.803	0.1	
SSTL135I	1.283	1.35	1.418	0.629	0.675	0.723	0.1	
SSTL135II	1.283	1.35	1.418	0.629	0.675	0.723	0.1	
HSTL15I	1.425	1.5	1.575	0.698	0.750	0.803	0.1	
HSTL15II	1.425	1.5	1.575	0.698	0.750	0.803	0.1	
HSTL135I	1.283	1.35	1.418	0.629	0.675	0.723	0.1	
HSTL135II	1.283	1.35	1.418	0.629	0.675	0.723	0.1	
HSTL12I	1.14	1.2	1.26	0.559	0.600	0.643	0.1	
HSUL18I	1.71	1.8	1.89	0.838	0.900	0.964	0.1	
HSUL18II	1.71	1.8	1.89	0.838	0.900	0.964	0.1	
HSUL12I	1.14	1.2	1.26	0.559	0.600	0.643	0.1	
POD12I	1.14	1.2	1.26	0.787	0.840	0.895	0.1	
POD12II	1.14	1.2	1.26	0.787	0.840	0.895	0.1	

1. V_{ICM} is the input common mode voltage.
2. V_{ID} is the input differential voltage.
3. V_{ICM} rules are as follows:
 - a. V_{ICM} must be less than V_{DDI} - 0.4V;
 - b. V_{ICM} + V_{ID}/2 must be < V_{DDI} + 0.4 V;
 - c. V_{ICM} - V_{ID}/2 must be > V_{SS} - 0.3 V.

Standard	Description	V_L^1	V_H^1	V_{ID}^2	V_{ICM}^2	$V_{MEAS}^{3,4}$	$V_{REF}^{1,5}$	Unit
SLVS25	SLVS 2.5 V	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.200	0		V
SLVS18	SLVS 1.8 V	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.200	0		V
HCSL33	High-speed current steering logic (HCSL) 3.3 V	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.350	0		V
HCSL25	HCSL 2.5 V	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.350	0		V
HCSL18	HCSL 1.8 V	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.350	0		V
BLVDSE25 ⁶	Bus LVDS 2.5 V	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	1.250	0		V
MLVDSE25 ⁶	Multipoint LVDS 2.5 V	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	1.250	0		V
LVPECL33	Low-voltage positive emitter coupled logic	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	1.650	0		V
LVPECL33 ⁶	Low-voltage positive emitter coupled logic	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	1.650	0		V
SSTL25I	Differential SSTL 2.5 V Class I	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	1.250	0		V
SSTL25II	Differential SSTL 2.5 V Class II	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	1.250	0		V
SSTL18I	Differential SSTL 1.8 V Class I	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.900	0		V
SSTL18II	Differential SSTL 1.8 V Class II	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.900	0		V
SSTL15	Differential SSTL 1.5 V Class I	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.750	0		V
SSTL135	Differential SSTL 1.5 V Class II	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.750	0		V
HSTL15I	Differential HSTL 1.5 V Class I	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.750	0		V
HSTL15II	Differential HSTL 1.5 V Class II	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.750	0		V
HSTL135I	Differential HSTL 1.35 V Class I	$V_{ICM} - .125$	$V_{ICM} + .125$	0.250	0.675	0		V

Figure 1 • Output Delay Measurement—Single-Ended Test Setup

Figure 2 • Output Delay Measurement—Differential Test Setup


7.1.3 Input Buffer Speed

The following tables provide information about input buffer speed.

Table 24 • HSIO Maximum Input Buffer Speed

Standard	STD	-1	Unit
LVDS18	1250	1250	Mbps
RDS18	800	800	Mbps
MINILVDS18	800	800	Mbps
SUBLVDS18	800	800	Mbps
PPDS18	800	800	Mbps
SLVS18	800	800	Mbps
SSTL18I	800	1066	Mbps
SSTL18II	800	1066	Mbps
SSTL15I	1066	1333	Mbps
SSTL15II	1066	1333	Mbps
SSTL135I	1066	1333	Mbps
SSTL135II	1066	1333	Mbps

7.1.5 Maximum PHY Rate for Memory Interface IP

The following tables provide information about the maximum PHY rate for memory interface IP.

Table 28 • Maximum PHY Rate for Memory Interfaces IP for HSIO Banks

Memory Standard	Gearing Ratio	VDDAUX	VDDI	STD (Mbps)	–1 (Mbps)	Fabric STD (MHz)	Fabric –1 (MHz)
DDR4	8:1	1.8 V	1.2 V	1333	1600	167	200
DDR3	8:1	1.8 V	1.5 V	1067	1333	133	167
DDR3L	8:1	1.8 V	1.35 V	1067	1333	133	167
LPDDR3	8:1	1.8 V	1.2 V	1067	1333	133	167
QDRII+	8:1	1.8 V	1.5 V	900	1100	112.5	137.5
RLDRAM3 ¹	8:1	1.8 V	1.35 V	1067	1067	133	133
RLDRAM3 ¹	4:1	1.8 V	1.35 V	667	800	167	200
RLDRAM3 ¹	2:1	1.8 V	1.35 V	333	400	167	200
RLDRAM2 ¹	8:1	1.8 V	1.8 V	800	1067	100	133
RLDRAM2 ¹	4:1	1.8 V	1.8 V	667	800	167	200
RLDRAM2 ¹	2:1	1.8 V	1.8 V	333	400	167	200

1. RLDRAM2 and RLDRAM3 are not supported with a soft IP controller currently.

Table 29 • Maximum PHY Rate for Memory Interfaces IP for GPIO Banks

Memory Standard	Gearing Ratio	VDDAUX	VDDI	STD (Mbps)	–1 (Mbps)	Fabric STD (MHz)	Fabric –1 (MHz)
DDR3	8:1	2.5 V	1.5 V	800	1067	100	133
QDRII+	8:1	2.5 V	1.5 V	900	900	113	113
RLDRAM2 ¹	4:1	2.5 V	1.8 V	800	800	200	200
RLDRAM2 ¹	2:1	2.5 V	1.8 V	400	400	200	200

1. RLDRAM2 is currently not supported with a soft IP controller.

Parameter	Interface Name	Topology	STD Min	STD Typ	STD Max	-1 Min	-1 Typ	-1 Max	Unit	Forwarded Clock-to-Data Skew
Output F _{MAX} 2:1	TX_DDRX_B_C	Tx DDR digital mode							MHz	From a HS_IO_CLK clock source, centered with PLL
Output F _{MAX} 4:1	TX_DDRX_B_C	Tx DDR digital mode							MHz	From a HS_IO_CLK clock source, centered with PLL
Output F _{MAX} 8:1	TX_DDRX_B_C	Tx DDR digital mode							MHz	From a HS_IO_CLK clock source, centered with PLL
In delay, out delay, DLL delay step sizes			12.7	30	35	12.7	25	29.5	ps	

Table 34 • I/O CDR Switching Characteristics

Parameter	Min	Max	Unit
Data rate	266	1250	Mbps
Receiver Sinusoidal jitter tolerance ¹	0.2		UI

1. Jitter values based on bit error ratio (BER) of 10–12, 80 MHz sinusoidal jitter injected to Rx data.

Note: See the LVDS output buffer specifications for transmit characteristics.

7.2 Clocking Specifications

This section describes the PLL and DLL clocking and oscillator specifications.

7.2.1 Clocking

The following table provides clocking specifications.

Table 35 • Global and Regional Clock Characteristics (–40 °C to 100 °C)

Parameter	Symbol	V _{DD} = 1.0 V STD	V _{DD} = 1.0 V –1	V _{DD} = 1.05 V STD	V _{DD} = 1.05 V –1	Unit	Condition
Global clock F _{MAX}	F _{MAXG}	500	500	500	500	MHz	
Regional clock F _{MAX}	F _{MAXR}	375	375	375	375	MHz	Transceiver interfaces only
	F _{MAXR}	250	250	250	250	MHz	All other interfaces
Global clock duty cycle distortion	T _{DCDG}	190	190	190	190	ps	At 500 MHz

Parameter	Symbol	STD Min	STD Typ	STD Max	–1 Min	–1 Typ	–1 Max	Unit
Reference clock input rate ^{1, 2, 3}	F _{XCVRREFCLKMAX} CASCADE	20		156	20		156	MHz
Reference clock rate at the PFD ⁴	F _{TXREFCLKPFD}	20		156	20		156	MHz
Reference clock rate recommended at the PFD for Tx rates 10 Gbps and above ⁴	F _{TXREFCLKPFD10G}	75		156	75		156	MHz
Tx reference clock phase noise requirements to meet jitter specifications (156 MHz clock at reference clock input) ⁵	F _{TXREFPN}			–110			–110	dBc /Hz
Phase noise at 10 KHz	F _{TXREFPN}			–110			–110	dBc /Hz
Phase noise at 100 KHz	F _{TXREFPN}			–115			–115	dBc /Hz
Phase noise at 1 MHz	F _{TXREFPN}			–135			–135	dBc /Hz
Reference clock input rise time (10%–90%)	T _{REFRISE}		200	500		200	500	ps
Reference clock input fall time (90%–10%)	T _{REFFALL}		200	500		200	500	ps
Reference clock duty cycle	T _{REFDUTY}	40		60	40		60	%
Spread spectrum modulation spread ⁶	Mod_Spread	0.1		3.1	0.1		3.1	%
Spread spectrum modulation frequency ⁷	Mod_Freq	TxREF CLKPFD/ (128)	32	TxREF CLKPFD/ (128*63)	TxREF CLKPFD/ (128)	32	TxREF CLKPFD/ (128*63)	KHz

1. See the maximum reference clock rate allowed per input buffer standard.
2. The minimum value applies to this clock when used as an XCVR reference clock. It does not apply when used as a non-XCVR input buffer (DC input allowed).
3. Cascaded reference clock.
4. After reference clock input divider.
5. Required maximum phase noise is scaled based on actual F_{TxRefClkPFD} value by $20 \times \log_{10} (\text{TxRefClkPFD} / 156 \text{ MHz})$. It is assumed that the reference clock divider of 4 is used for these calculations to always meet the maximum PFD frequency specification.
6. Programmable capability for depth of down-spread or center-spread modulation.
7. Programmable modulation rate based on the modulation divider setting (1 to 63).

7.4.3 Transceiver Reference Clock I/O Standards

The following table describes the differential I/O standards supported as transceiver reference clocks.

7.6.3 FPGA Bitstream Sizes

The following table describes FPGA bitstream sizes.

Table 72 • Initialization Client Sizes

Device	Plaintext	Ciphertext
MPF100T, TL, TS, TLS		
MPF200T, TL, TS, TLS	2916 KB	3006 KB
MPF300T, TL, TS, TLS	4265 KB	4403 KB
MPF500T, TL, TS, TLS		

Note: Worst case initializing all fabric LSRAM, USRAM, and UPROM.

Table 73 • Bitstream Sizes

File	Devices	FPGA	Security	SNVM (all pages)	FPGA+ SNVM	FPGA+ Sec	SNVM+ Sec	FPGA+ SNVM+ Sec
SPI	MPF100T, TL, TS, TLS							
DAT	MPF100T, TL, TS, TLS							
SPI	MPF200T, TL, TS, TLS	5.9 MB	3.4 KB	59.7 KB	5.9 MB	5.9 MB	62.2 KB	6.0 MB
DAT	MPF200T, TL, TS, TLS	5.9 MB	7.3 KB	61.2 KB	6.0 MB	5.9 MB	66.3 KB	6.0 MB
SPI	MPF300T, TL, TS, TLS	9.3 MB	3.5 KB	59.7 KB	9.6 MB	9.5 MB	62.2 KB	9.6 MB
DAT	MPF300T, TL, TS, TLS	9.3 MB	7.6 KB	61.2 KB	9.6 MB	9.5 MB	66.3 KB	9.6 MB
SPI	MPF500T, TL, TS, TLS							
DAT	MPF500T, TL, TS, TLS							

7.6.4 Digest Cycles

Digests verify the integrity of the programmed non-volatile data. Digests are a cryptographic hash of various data areas. Any digest that reports back an error raises the digest tamper flag.

Table 74 • Maximum Number of Digest Cycles

Retention Since Programmed (N = Number Digests During that Time) ¹										
Digest T _i	Storage and Operating T _j	N ≤300	N = 500	N = 1000	N = 1500	N = 2000	N = 4000	N = 6000	Unit	Retention
–40 to 100	–40 to 100	20 × LF	17 × LF	12 × LF	10 × LF	8 × LF	4 × LF	2 × LF	°C	Years
–40 to 100	0 to 100	20 × LF	17 × LF	12 × LF	10 × LF	8 × LF	4 × LF	2 × LF	°C	Years
–40 to 85	–40 to 85	20 × LF	20 × LF	20 × LF	20 × LF	16 × LF	8 × LF	4 × LF	°C	Years
–40 to 55	–40 to 55	20 × LF	20 × LF	20 × LF	20 × LF	20 × LF	20 × LF	20 × LF	°C	Years

1. LF = Lifetime factor as defined by the number of programming cycles the device has seen under the conditions listed in the following table.

Table 75 • FPGA Programming Cycles Lifetime Factor

Programming T _J	Programming Cycles	LF
–40 °C to 100 °C	500	1
–40 °C to 85 °C	1000	0.8
–40 °C to 55 °C	2000	0.6

Notes:


- The maximum number of device digest cycles is 100K.
- Digests are operational only over the –40 °C to 100 °C temperature range.
- After a program cycle, an additional N digests cycles are allowed with the resultant retention characteristics for the total operating and storage temperature shown.
- Retention is specified for total device storage and operating temperature.
- All temperatures are junction temperatures (T_J).
- Example 1—500 digests cycles are performed between programming cycles. N = 500. The operating conditions are –40 °C to 85 °C T_J. 501 programming cycles have occurred. The retention under these operating conditions is $20 \times LF = 20 \times .8 = 16$ years.
- Example 2—one programming cycle has occurred, N = 1500 digest cycles have occurred. Temperature range is –40 °C to 100 °C. The resultant retention is $10 \times LF$ or 10 years over the industrial temperature range.

7.6.5**Digest Time**

The following table describes digest time.

Table 76 • Digest Times

Parameter	Devices	Typ	Max	Unit
Setup time	All	2		μs
Fabric digest run time	MPF100T, TL, TS, TLS			ms
	MPF200T, TL, TS, TLS	1005	1072	ms
	MPF300T, TL, TS, TLS	1503.9	1582	ms
	MPF500T, TL, TS, TLS			ms
UFS CC digest run time	MPF100T, TL, TS, TLS			μs
	MPF200T, TL, TS, TLS	33.2	35	μs
	MPF300T, TL, TS, TLS	33.2	35	μs
	MPF500T, TL, TS, TLS			μs
sNVM digest run time ¹	MPF100T, TL, TS, TLS			ms
	MPF200T, TL, TS, TLS	4.4	4.8	ms
	MPF300T, TL, TS, TLS	4.4	4.8	ms
	MPF500T, TL, TS, TLS			ms
UFS UL digest run time	MPF100T, TL, TS, TLS			μs
	MPF200T, TL, TS, TLS	46.6	48.8	μs
	MPF300T, TL, TS, TLS	46.6	48.8	μs
	MPF500T, TL, TS, TLS			μs
User key digest run time ²	MPF100T, TL, TS, TLS			μs
	MPF200T, TL, TS, TLS	525.4	543.3	μs
	MPF300T, TL, TS, TLS	525.4	543.3	μs
	MPF500T, TL, TS, TLS			μs

Figure 3 • UJTAG Timing Diagram

7.8.2 UJTAG_SEC Switching Characteristics

The following table describes characteristics of UJTAG_SEC switching.

Table 89 • UJTAG Security Performance Characteristics

Parameter	Symbol	Min	Typ	Max	Unit	Condition
TCK frequency	F _{TCK}				MHz	

7.8.3 USPI Switching Characteristics


The following section describes characteristics of USPI switching.

Table 90 • SPI Macro Interface Timing Characteristics

Parameter	Symbol	V _{DDI} = 3.3 V Max	V _{DDI} = 2.5 V Max	V _{DDI} = 1.8 V Max	V _{DDI} = 1.5 V Max	V _{DDI} = 1.2 V Max	Unit
Propagation delay from the fabric to pins ¹	TPD_MOSI	0.8	1	1.2	1.4	1.6	ns
	TPD_MISO	3.5	3.75	4	4.25	4.5	ns
	TPD_SS	3.5	3.75	4	4.25	4.5	ns
	TPD_SCK	3.5	3.75	4	4.25	4.5	ns
	TPD_MOSI_OE	3.5	3.75	4	4.25	4.5	ns
	TPD_SS_OE	3.5	3.75	4	4.25	4.5	ns
	TPD_SCK_OE	3.5	3.75	4	4.25	4.5	ns

1. Assumes CL of the relevant I/O standard as described in the input and output delay measurement tables.

Figure 6 • Warm Reset Timing



7.9.3 Power-On Reset Voltages

7.9.3.1 Main Supplies

The start of power-up to functional time (T_{PUFT}) is defined as the point at which the latest of the main supplies (VDD, VDD18, VDD25) reach the reference voltage levels specified in the following table. This starts the process of releasing the reset of the device and powering on the FPGA fabric and IOs.

Table 97 • POR Ref Voltages

Supply	Power-On Reset Start Point (V)	Note
VDD	0.95	Applies to both 1.0 V and 1.05 V operation.
VDD18	1.71	
VDD25	2.25	

7.9.3.2 I/O-Related Supplies

For the I/Os to become functional (for low speed, sub 400 MHz operation), the (per-bank) I/O supplies (VDDI, VDDAUX) must reach the trip point voltage levels specified in the following table and the main supplies above must also be powered on.

Table 98 • I/O-Related Supplies

Supply	I/O Power-Up Start Point (V)
VDDI	0.85
VDDAUX	1.6

There are no sequencing requirements for the power supplies. However, VDDI3 and must be valid at same time as the main supplies. The other IO supplies (VDDI, VDDAUX) have no effect on power-up of FPGA fabric (that is, the fabric still powers up even if the IO supplies of some IO banks remain powered off).

1. With DPA counter measures.

Table 115 • HMAC

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
HMAC-SHA-256 ¹ , 256-bit key	512	7477	2361
	64K	88367	2099
HMAC-SHA-384 ¹ , 384-bit key	1024	13049	2257
	64K	106103	2153

1. With DPA counter measures.

Table 116 • CMAC

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
AES-CMAC-256 ¹ (message is only authenticated)	128	446	9058
	64K	45494	111053

1. With DPA counter measures.

Table 117 • KEY TREE

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
128-bit nonce + 8-bit optype		102457	2751
256-bit nonce + 8-bit optype		103218	2089

Table 118 • SHA

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
SHA-1 ¹	512	2386	1579
	64K	77576	990
SHA-256 ¹	512	2516	884
	64K	84752	938
SHA-384 ¹	1024	4154	884
	64K	100222	938
SHA-512 ¹	1024	4154	881
	64K	100222	935

1. With DPA counter measures.

Table 119 • ECC

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
ECDSA SigGen, P-384/SHA-384 ¹	1024	12528912	6944
	8K	12540448	5643
ECDSA SigGen, P-384/SHA-384	1024	5502928	6155

ECDSA SigVer, P-384/SHA-384	1024	6421841	5759
	8K	6273510	5759
Key Agreement (KAS), P-384		5039125	6514
Point Multiply, P-256 ¹		5176923	4482
Point Multiply, P-384 ¹		12043199	5319
Point Multiply, P-521 ¹		26887187	6698
Point Addition, P-384		3018067	5779
KeyGen (PKG), P-384		12055368	6908
Point Verification, P-384		5091	3049

1. With DPA counter measures.

Table 120 • IFC (RSA)

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
Encrypt, RSA-2048, e=65537	2048	436972	8,972
Encrypt, RSA-3072, e=65537	3072	962162	12,583
Decrypt, RSA-2048 ¹ , CRT	2048	26862392	15900
Decrypt, RSA-3072 ¹ , CRT	3072	75153782	22015
Decrypt, RSA-4096, CRT	4096	89235615	23710
Decrypt, RSA-3072, CRT	3072	37880180	18638
SigGen, RSA-3072/SHA-384 ¹ , CRT, PKCS #1 V 1.1.5	1024	75197644	20032
	8K	75213653	19303
SigGen, RSA-3072/SHA-384, PKCS #1, V 1.5	1024	148090970	14642
	8K	148102576	13936
SigVer, RSA-3072/SHA-384, e = 65537, PKCS #1 V 1.5	1024	970991	12000
	8K	982011	11769
SigVer, RSA-2048/SHA-256, e = 65537, PKCS #1 V 1.5	1024	443493	8436
	8K	453007	8436
SigGen, RSA-3072/SHA-384, ANSI X9.31	1024	147138254	13945
	8K	147155896	13523
SigVer, RSA-3072/SHA-384, e = 65537, ANSI X9.31	1024	973269	11313
	8K	983255	11146

1. With DPA counter measures.

Table 121 • FFC (DH)

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
SigGen, DSA-3072/SHA-384 ¹	1024	27932907	13969
	8K	27942415	13501
SigGen, DSA-3072/SHA-384	1024	12086356	13602
SigVer, DSA-3072/SHA-384	1024	24597916	15662
	8K	24229420	15133