




Welcome to [E-XFL.COM](https://www.e-xfl.com)

Understanding [Embedded - FPGAs \(Field Programmable Gate Array\)](#)

Embedded - FPGAs, or Field Programmable Gate Arrays, are advanced integrated circuits that offer unparalleled flexibility and performance for digital systems. Unlike traditional fixed-function logic devices, FPGAs can be programmed and reprogrammed to execute a wide array of logical operations, enabling customized functionality tailored to specific applications. This reprogrammability allows developers to iterate designs quickly and implement complex functions without the need for custom hardware.

Applications of Embedded - FPGAs

The versatility of Embedded - FPGAs makes them indispensable in numerous fields. In telecommunications.

Details

Product Status	Active
Number of LABs/CLBs	-
Number of Logic Elements/Cells	300000
Total RAM Bits	21094400
Number of I/O	512
Number of Gates	-
Voltage - Supply	0.97V ~ 1.08V
Mounting Type	Surface Mount
Operating Temperature	0°C ~ 100°C (TJ)
Package / Case	1152-BBGA, FCBGA
Supplier Device Package	1152-FCBGA (35x35)
Purchase URL	https://www.e-xfl.com/product-detail/microchip-technology/mpf300t-1fcg1152e

Contents

1	Revision History	1
1.1	Revision 1.3	1
1.2	Revision 1.2	1
1.3	Revision 1.1	1
1.4	Revision 1.0	1
2	Overview	2
3	References	3
4	Device Offering	4
5	Silicon Status	5
6	DC Characteristics	6
6.1	Absolute Maximum Rating	6
6.2	Recommended Operating Conditions	6
6.2.1	DC Characteristics over Recommended Operating Conditions	8
6.2.2	Maximum Allowed Overshoot and Undershoot	8
6.3	Input and Output	12
6.3.1	DC Input and Output Levels	12
6.3.2	Differential DC Input and Output Levels	15
6.3.3	Complementary Differential DC Input and Output Levels	18
6.3.4	HSIO On-Die Termination	19
6.3.5	GPIO On-Die Termination	20
7	AC Switching Characteristics	22
7.1	I/O Standards Specifications	22
7.1.1	Input Delay Measurement Methodology Maximum PHY Rate for Memory Interface IP	22
7.1.2	Output Delay Measurement Methodology	25
7.1.3	Input Buffer Speed	27
7.1.4	Output Buffer Speed	29
7.1.5	Maximum PHY Rate for Memory Interface IP	31
7.1.6	User I/O Switching Characteristics	32
7.2	Clocking Specifications	35
7.2.1	Clocking	35
7.2.2	PLL	36
7.2.3	DLL	37
7.2.4	RC Oscillators	38
7.3	Fabric Specifications	40
7.3.1	Math Blocks	40

4 Device Offering

The following table lists the PolarFire FPGA device options using the MPF300T as an example. The MPF100T, MPF200T, and MPF500T device densities have identical offerings.

Table 1 • PolarFire FPGA Device Options

Device Options	Extended Commercial 0 °C–100 °C	Industrial –40 °C–100 °C	STD	–1	Transceivers T	Lower Static Power L	Data Security S
MPF300T	Yes	Yes	Yes	Yes	Yes		
MPF300TL	Yes	Yes	Yes		Yes	Yes	
MPF300TS		Yes	Yes	Yes	Yes		Yes
MPF300TLS		Yes	Yes		Yes	Yes	Yes

6.2.1 DC Characteristics over Recommended Operating Conditions

The following table lists the DC characteristics over recommended operating conditions.

Table 5 • DC Characteristics over Recommended Operating Conditions

Parameter	Symbol	Min	Max	Unit	Condition
Input pin capacitance ¹	C _{IN} (dedicated GPIO)		5.6	pf	
	C _{IN} (GPIO)		5.6	pf	
	C _{IN} (HSIO)		2.8	pf	
Input or output leakage current per pin	I _L (GPIO)		10	μA	I/O disabled, high – Z
	I _L (HSIO)		10	μA	I/O disabled, high – Z
Input rise time (10%–90% of V _{DDIX}) ^{2, 3, 4}	T _{RISE}	0.66	2.64	ns	V _{DDIX} = 3.3 V
Input rise time (10%–90% of V _{DDIX}) ^{2, 3, 4}		0.50	2.00	ns	V _{DDIX} = 2.5 V
Input rise time (10%–90% of V _{DDIX}) ^{2, 3, 4}		0.36	1.44	ns	V _{DDIX} = 1.8 V
Input rise time (10%–90% of V _{DDIX}) ^{2, 3, 4}		0.30	1.20	ns	V _{DDIX} = 1.5 V
Input rise time (10%–90% of V _{DDIX}) ^{2, 3, 4}		0.24	0.96	ns	V _{DDIX} = 1.2 V
Input fall time (90%–10% of V _{DDIX}) ^{2, 3, 4}	T _{FALL}	0.66	2.64	ns	V _{DDIX} = 3.3 V
Input fall time (90%–10% of V _{DDIX}) ^{2, 3, 4}		0.50	2.00	ns	V _{DDIX} = 2.5 V
Input fall time (90%–10% of V _{DDIX}) ^{2, 3, 4}		0.36	1.44	ns	V _{DDIX} = 1.8 V
Input fall time (90%–10% of V _{DDIX}) ^{2, 3, 4}		0.30	1.20	ns	V _{DDIX} = 1.5 V
Input fall time (90%–10% of V _{DDIX}) ^{2, 3, 4}		0.24	0.96	ns	V _{DDIX} = 1.2 V
Pad pull-up when V _{IN} = 0 ⁵	I _{PU}	137	220	μA	V _{DDIX} = 3.3 V
Pad pull-up when V _{IN} = 0 ⁵		102	166	μA	V _{DDIX} = 2.5 V
Pad pull-up when V _{IN} = 0		68	115	μA	V _{DDIX} = 1.8 V
Pad pull-up when V _{IN} = 0		51	88	μA	V _{DDIX} = 1.5 V
Pad pull-up when V _{IN} = 0 ⁶		29	73	μA	V _{DDIX} = 1.35 V
Pad pull-up when V _{IN} = 0	I _{PD}	16	46	μA	V _{DDIX} = 1.2 V
Pad pull-down when V _{IN} = 3.3 V ⁵		65	187	μA	V _{DDIX} = 3.3 V
Pad pull-down when V _{IN} = 2.5 V ⁵		63	160	μA	V _{DDIX} = 2.5 V
Pad pull-down when V _{IN} = 1.8 V		60	117	μA	V _{DDIX} = 1.8 V
Pad pull-down when V _{IN} = 1.5 V		57	95	μA	V _{DDIX} = 1.5 V
Pad pull-down when V _{IN} = 1.35 V		52	86	μA	V _{DDIX} = 1.35 V
Pad pull-down when V _{IN} = 1.2 V		47	79	μA	V _{DDIX} = 1.2 V

1. Represents the die input capacitance at the pad not the package.
2. Voltage ramp must be monotonic.
3. Numbers based on rail-to-rail input signal swing and minimum 1 V/ns and maximum 4 V/ns. These are to be used for input delay measurement consistency.
4. I/O signal standards with smaller than rail-to-rail input swings can use a nominal value of 200 ps 20%–80% of swing and maximum value of 500 ps 20%–80% of swing.
5. GPIO only.

6.2.2 Maximum Allowed Overshoot and Undershoot

During transitions, input signals may overshoot and undershoot the voltage shown in the following table. Input currents must be limited to less than 100 mA per latch-up specifications.

Note: The following dedicated pins do not support hot socketing: TMS, TDI, TRSTB, DEVRST_N, and FF_EXIT_N. Weak pull-up (as specified in GPIO) is always enabled.

6.3 Input and Output

The following section describes:

- DC I/O levels
- Differential and complementary differential DC I/O levels
- HSIO and GPIO on-die termination specifications
- LVDS specifications

6.3.1 DC Input and Output Levels

The following tables list the DC I/O levels.

Table 12 • DC Input Levels

I/O Standard	V _{DDI} Min (V)	V _{DDI} Typ (V)	V _{DDI} Max (V)	V _{IL} Min (V)	V _{IL} Max (V)	V _{IH} Min (V)	V _{IH} ¹ Max (V)
PCI	3.15	3.3	3.45	−0.3	0.3 x V _{DDI}	0.5 x V _{DDI}	3.45
LVTTL	3.15	3.3	3.45	−0.3	0.8	2	3.45
LVC MOS33	3.15	3.3	3.45	−0.3	0.8	2	3.45
LVC MOS25	2.375	2.5	2.625	−0.3	0.7	1.7	2.625
LVC MOS18	1.71	1.8	1.89	−0.3	0.35 x V _{DDI}	0.65 x V _{DDI}	1.89
LVC MOS15	1.425	1.5	1.575	−0.3	0.35 x V _{DDI}	0.65 x V _{DDI}	1.575
LVC MOS12	1.14	1.2	1.26	−0.3	0.35 x V _{DDI}	0.65 x V _{DDI}	1.26
SSTL25I ²	2.375	2.5	2.625	−0.3	V _{REF} − 0.15	V _{REF} + 0.15	2.625
SSTL25II ²	2.375	2.5	2.625	−0.3	V _{REF} − 0.15	V _{REF} + 0.15	2.625
SSTL18I ²	1.71	1.8	1.89	−0.3	V _{REF} − 0.125	V _{REF} + 0.125	1.89
SSTL18II ²	1.71	1.8	1.89	−0.3	V _{REF} − 0.125	V _{REF} + 0.125	1.89
SSTL15I	1.425	1.5	1.575	−0.3	V _{REF} − 0.1	V _{REF} + 0.1	1.575
SSTL15II	1.425	1.5	1.575	−0.3	V _{REF} − 0.1	V _{REF} + 0.1	1.575

I/O Standard	V _{DDI} Min (V)	V _{DDI} Typ (V)	V _{DDI} Max (V)	V _{IL} Min (V)	V _{IL} Max (V)	V _{IH} Min (V)	V _{IH} ¹ Max (V)
SSTL135I	1.283	1.35	1.418	-0.3	V _{REF} - 0.09	V _{REF} + 0.09	1.418
SSTL135II	1.283	1.35	1.418	-0.3	V _{REF} - 0.09	V _{REF} + 0.09	1.418
HSTL15I	1.425	1.5	1.575	-0.3	V _{REF} - 0.1	V _{REF} + 0.1	1.575
HSTL15II	1.425	1.5	1.575	-0.3	V _{REF} - 0.1	V _{REF} + 0.1	1.575
HSTL135I	1.283	1.35	1.418	-0.3	V _{REF} - 0.09	V _{REF} + 0.09	1.418
HSTL135II	1.283	1.35	1.418	-0.3	V _{REF} - 0.09	V _{REF} + 0.09	1.418
HSTL12I	1.14	1.2	1.26	-0.3	V _{REF} - 0.1	V _{REF} + 0.1	1.26
HSTL12II	1.14	1.2	1.26	-0.3	V _{REF} - 0.1	V _{REF} + 0.1	1.26
HSUL18I	1.71	1.8	1.89	-0.3	0.3 x V _{DDI}	0.7 x V _{DDI}	1.89
HSUL18II	1.71	1.8	1.89	-0.3	0.3 x V _{DDI}	0.7 x V _{DDI}	1.89
HSUL12I	1.14	1.2	1.26	-0.3	V _{REF} - 0.1	V _{REF} + 0.1	1.26
POD12I	1.14	1.2	1.26	-0.3	V _{REF} - 0.08	V _{REF} + 0.08	1.26
POD12II	1.14	1.2	1.26	-0.3	V _{REF} - 0.08	V _{REF} + 0.08	1.26

1. GPIO V_{IH} max is 3.45 V with PCI clamp diode turned off regardless of mode, that is, over-voltage tolerant.

2. For external stub-series resistance. This resistance is on-die for GPIO.

Note: 3.3 V and 2.5 V are only supported in GPIO banks.

I/O Standard	Bank Type	V _{OCM} ¹ Min (V)	V _{OCM} Typ (V)	V _{OCM} Max (V)	V _{OD} ² Min (V)	V _{OD} ² Typ (V)	V _{OD} ² Max (V)
MLVDSSE25 ³	GPIO		1.25		0.396	0.442	0.453
LVPECL33 ³	GPIO		1.65		0.664	0.722	0.755
MIPIE25 ³	GPIO		0.25		0.1	0.22	0.3

1. V_{OCM} is the output common mode voltage.
2. V_{OD} is the output differential voltage.
3. Emulated output only.



6.3.3 Complementary Differential DC Input and Output Levels

The following tables list the complementary differential DC I/O levels.

Table 16 • Complementary Differential DC Input Levels

I/O Standard	V _{DDI} Min (V)	V _{DDI} Typ (V)	V _{DDI} Max (V)	V _{ICM} ^{1,3} Min (V)	V _{ICM} ^{1,3} Typ (V)	V _{ICM} ^{1,3} Max (V)	V _{ID} ² Min (V)	V _{ID} Max (V)
SSTL25I	2.375	2.5	2.625	1.164	1.250	1.339	0.1	
SSTL25II	2.375	2.5	2.625	1.164	1.250	1.339	0.1	
SSTL18I	1.71	1.8	1.89	0.838	0.900	0.964	0.1	
SSTL18II	1.71	1.8	1.89	0.838	0.900	0.964	0.1	
SSTL15I	1.425	1.5	1.575	0.698	0.750	0.803	0.1	
SSTL15II	1.425	1.5	1.575	0.698	0.750	0.803	0.1	
SSTL135I	1.283	1.35	1.418	0.629	0.675	0.723	0.1	
SSTL135II	1.283	1.35	1.418	0.629	0.675	0.723	0.1	
HSTL15I	1.425	1.5	1.575	0.698	0.750	0.803	0.1	
HSTL15II	1.425	1.5	1.575	0.698	0.750	0.803	0.1	
HSTL135I	1.283	1.35	1.418	0.629	0.675	0.723	0.1	
HSTL135II	1.283	1.35	1.418	0.629	0.675	0.723	0.1	
HSTL12I	1.14	1.2	1.26	0.559	0.600	0.643	0.1	
HSUL18I	1.71	1.8	1.89	0.838	0.900	0.964	0.1	
HSUL18II	1.71	1.8	1.89	0.838	0.900	0.964	0.1	
HSUL12I	1.14	1.2	1.26	0.559	0.600	0.643	0.1	
POD12I	1.14	1.2	1.26	0.787	0.840	0.895	0.1	
POD12II	1.14	1.2	1.26	0.787	0.840	0.895	0.1	

1. V_{ICM} is the input common mode voltage.
2. V_{ID} is the input differential voltage.
3. V_{ICM} rules are as follows:
 - a. V_{ICM} must be less than V_{DDI} - 0.4V;
 - b. V_{ICM} + V_{ID}/2 must be < V_{DDI} + 0.4 V;
 - c. V_{ICM} - V_{ID}/2 must be > V_{SS} - 0.3 V.

Figure 1 • Output Delay Measurement—Single-Ended Test Setup

Figure 2 • Output Delay Measurement—Differential Test Setup


7.1.3 Input Buffer Speed

The following tables provide information about input buffer speed.

Table 24 • HSIO Maximum Input Buffer Speed

Standard	STD	-1	Unit
LVDS18	1250	1250	Mbps
RDS18	800	800	Mbps
MINILVDS18	800	800	Mbps
SUBLVDS18	800	800	Mbps
PPDS18	800	800	Mbps
SLVS18	800	800	Mbps
SSTL18I	800	1066	Mbps
SSTL18II	800	1066	Mbps
SSTL15I	1066	1333	Mbps
SSTL15II	1066	1333	Mbps
SSTL135I	1066	1333	Mbps
SSTL135II	1066	1333	Mbps

Standard	STD	–1	Unit
HSTL15I	900	1100	Mbps
HSTL15II	900	1100	Mbps
HSTL135I	1066	1066	Mbps
HSTL135II	1066	1066	Mbps
HSUL18I	400	400	Mbps
HSUL18II	400	400	Mbps
HSUL12	1066	1333	Mbps
HSTL12	1066	1266	Mbps
POD12I	1333	1600	Mbps
POD12II	1333	1600	Mbps
LVCMS18 (12 mA)	500	500	Mbps
LVCMS15 (10 mA)	500	500	Mbps
LVCMS12 (8 mA)	300	300	Mbps

1. Performance is achieved with $V_{ID} \geq 200$ mV.

Table 25 • GPIO Maximum Input Buffer Speed

Standard	STD	–1	Unit
LVDS25/LVDS33/LCMDS25/LCMDS33	1250	1600	Mbps
RSDS25/RSDS33	800	800	Mbps
MINILVDS25/MINILVDS33	800	800	Mbps
SUBLVDS25/SUBLVDS33	800	800	Mbps
PPDS25/PPDS33	800	800	Mbps
SLVS25/SLVS33	800	800	Mbps
SLVSE15	800	800	Mbps
HCSL25/HCSL33	800	800	Mbps
BUSLVDSE25	800	800	Mbps
MLVDSE25	800	800	Mbps
LVPECL33	800	800	Mbps
SSTL25I	800	800	Mbps
SSTL25II	800	800	Mbps
SSTL18I	800	800	Mbps
SSTL18II	800	800	Mbps
SSTL15I	800	1066	Mbps
SSTL15II	800	1066	Mbps
HSTL15I	800	900	Mbps
HSTL15II	800	900	Mbps
HSUL18I	400	400	Mbps
HSUL18II	400	400	Mbps
PCI	500	500	Mbps
LVTTTL33 (20 mA)	500	500	Mbps
LVCMS33 (20 mA)	500	500	Mbps
LVCMS25 (16 mA)	500	500	Mbps

7.1.5 Maximum PHY Rate for Memory Interface IP

The following tables provide information about the maximum PHY rate for memory interface IP.

Table 28 • Maximum PHY Rate for Memory Interfaces IP for HSIO Banks

Memory Standard	Gearing Ratio	V _{DDAUX}	V _{DDI}	STD (Mbps)	–1 (Mbps)	Fabric STD (MHz)	Fabric –1 (MHz)
DDR4	8:1	1.8 V	1.2 V	1333	1600	167	200
DDR3	8:1	1.8 V	1.5 V	1067	1333	133	167
DDR3L	8:1	1.8 V	1.35 V	1067	1333	133	167
LPDDR3	8:1	1.8 V	1.2 V	1067	1333	133	167
QDRII+	8:1	1.8 V	1.5 V	900	1100	112.5	137.5
RLDRAM3 ¹	8:1	1.8 V	1.35 V	1067	1067	133	133
RLDRAM3 ¹	4:1	1.8 V	1.35 V	667	800	167	200
RLDRAM3 ¹	2:1	1.8 V	1.35 V	333	400	167	200
RLDRAM2 ¹	8:1	1.8 V	1.8 V	800	1067	100	133
RLDRAM2 ¹	4:1	1.8 V	1.8 V	667	800	167	200
RLDRAM2 ¹	2:1	1.8 V	1.8 V	333	400	167	200

1. RLDRAM2 and RLDRAM3 are not supported with a soft IP controller currently.

Table 29 • Maximum PHY Rate for Memory Interfaces IP for GPIO Banks

Memory Standard	Gearing Ratio	V _{DDAUX}	V _{DDI}	STD (Mbps)	–1 (Mbps)	Fabric STD (MHz)	Fabric –1 (MHz)
DDR3	8:1	2.5 V	1.5 V	800	1067	100	133
QDRII+	8:1	2.5 V	1.5 V	900	900	113	113
RLDRAM2 ¹	4:1	2.5 V	1.8 V	800	800	200	200
RLDRAM2 ¹	2:1	2.5 V	1.8 V	400	400	200	200

1. RLDRAM2 is currently not supported with a soft IP controller.

Parameter	Symbol	Min	Typ	Max	Unit
Operating current (V_{DD18})	RC_{SCVPP}			0.1	μA
Operating current (V_{DD})	RC_{SCVDD}			60.7	μA

7.3 Fabric Specifications

The following section describes specifications for the fabric.

7.3.1 Math Blocks

The following tables describe math block performance.

Table 41 • Math Block Performance Extended Commercial Range (0 °C to 100 °C)

Parameter	Symbol	Modes	V _{DD} = 1.0 V – STD	V _{DD} = 1.0 V – 1	V _{DD} = 1.05 V – STD	V _{DD} = 1.05 V – 1	Unit
Maximum operating frequency	F _{MAX}	18 × 18 multiplication	370	470	440	500	MHz
		18 × 18 multiplication summed with 48-bit input	370	470	440	500	MHz
		18 × 19 multiplier pre-adder ROM mode	365	465	435	500	MHz
		Two 9 × 9 multiplication	370	470	440	500	MHz
		9 × 9 dot product (DOTP)	370	470	440	500	MHz
		Complex 18 × 19 multiplication	360	455	430	500	MHz

Table 42 • Math Block Performance Industrial Range (–40 °C to 100 °C)

Parameter	Symbol	Modes	V _{DD} = 1.0 V – STD	V _{DD} = 1.0 V – 1	V _{DD} = 1.05 V – STD	V _{DD} = 1.05 V – 1	Unit
Maximum operating frequency	F _{MAX}	18 × 18 multiplication	365	465	435	500	MHz
		18 × 18 multiplication summed with 48-bit input	365	465	435	500	MHz
		18 × 19 multiplier pre-adder ROM mode	355	460	430	500	MHz
		Two 9 × 9 multiplication	365	465	435	500	MHz
		9 × 9 DOTP	365	465	435	500	MHz
		Complex 18 × 19 multiplication	350	450	425	500	MHz

Table 48 • Transceiver Differential Reference Clock I/O Standards

I/O Standard	Comment
LVDS25	For DC input levels, see table Differential DC Input and Output Levels .
HCSL25 (for PCIe)	

Note: The transceiver reference clock differential receiver supports V_{CM} common mode.

7.4.4 Transceiver Interface Performance

The following table describes the single-ended I/O standards supported as transceiver reference clocks.

Table 49 • Transceiver Single-Ended Reference Clock I/O Standards

I/O Standard	Comment
LVC MOS25	For DC input levels, see table DC Input and Output Levels .

7.4.5 Transmitter Performance

The following tables describe performance of the transmitter.

Table 50 • Transceiver Reference Clock Input Termination

Parameter	Symbol	Min	Typ	Max	Unit
Single-ended termination	RefTerm		50		Ω
Single-ended termination	RefTerm		75		Ω
Single-ended termination	RefTerm		150		Ω
Differential termination	RefDiffTerm		115 ¹		Ω
Power-up termination			>50K		Ω

1. Measured at V_{CM} = 1.2 V and V_{ID} = 350 mV.

Note: All pull-ups are disabled at power-up to allow hot plug capability.

Table 51 • PolarFire Transceiver User Interface Clocks

Parameter	Modes ¹	STD Min	STD Max	-1 Min	-1 Max	Unit
Transceiver TX_CLK range (non- deterministic PCS mode with global or regional fabric clocks)	8-bit, max data rate = 1.6 Gbps		200		200	MHz
	10-bit, max data rate = 1.6 Gbps		160		160	MHz
	16-bit, max data rate = 4.8 Gbps		300		300	MHz
	20-bit, max data rate = 6.0 Gbps		300		300	MHz
	32-bit, max data rate = 10.3125 Gbps (–STD) / 12.7 Gbps (–1) ¹		325		325	MHz
	40-bit, max data rate = 10.3125 Gbps (–STD) / 12.7 Gbps (–1) ¹		260		320	MHz
	64-bit, max data rate = 10.3125 Gbps (–STD) / 12.7 Gbps (–1) ¹		165		160	MHz
	80-bit, max data rate = 10.3125 Gbps (–STD) / 12.7 Gbps (–1) ¹		130		130	MHz
	Fabric pipe mode 32-bit, max data rate = 6.0 Gbps		150		150	MHz
	8-bit, max data rate = 1.6 Gbps		200		200	MHz

7.6.1 FPGA Programming Cycle and Retention

The following table describes FPGA programming cycle and retention.

Table 68 • FPGA Programming Cycles vs Retention Characteristics

Programming T _i	Programming Cycles, Max	Retention Years	Retention Years at T _i
0 °C to 85 °C	1000	20	85 °C
0 °C to 100 °C	500	20	100 °C
–20 °C to 100 °C	500	20	100 °C
–40 °C to 100 °C	500	20	100 °C
–40 °C to 85 °C	1000	16	100 °C
–40 °C to 55 °C	2000	12	100 °C

Note: Power supplied to the device must be valid during programming operations such as programming and verify . Programming recovery mode is available only for in-application programming mode and requires an external SPI flash.

7.6.2 FPGA Programming Time

The following tables describe FPGA programming time.

Table 69 • Master SPI Programming Time (IAP)

Parameter	Symbol	Devices	Typ	Max	Unit
Programming time	T _{PROG}	MPF100T, TL, TS, TLS			s
		MPF200T, TL, TS, TLS	17	25	s
		MPF300T, TL, TS, TLS	26	32	s
		MPF500T, TL, TS, TLS			s

Table 70 • Slave SPI Programming Time

Parameter	Symbol	Devices	Typ	Max	Unit
Programming time	T _{PROG}	MPF100T, TL, TS, TLS			s
		MPF200T, TL, TS, TLS	41 ¹		s
		MPF300T, TL, TS, TLS	50 ¹	60	s
		MPF500T, TL, TS, TLS			s

1. SmartFusion2 with MSS running at 100 MHz, MSS_SPI_0 port running at 6.67 MHz. Bitstream stored in DDR. DirectC version 4.1.

Table 71 • JTAG Programming Time

Parameter	Symbol	Devices	Typ	Max	Unit
Programming time	T _{PROG}	MPF100T, TL, TS, TLS			s
		MPF200T, TL, TS, TLS		56	s
		MPF300T, TL, TS, TLS ¹		95	s
		MPF500T, TL, TS, TLS			s

1. Programmer: FlashPro5 with TCK 10 MHz. PC Configuration: Intel i7 at 3.6 GHz, 32 GB RAM, Windows 10.

Parameter	Typ	Max	Unit	Conditions
Time to destroy data in non-volatile memory (non-recoverable) ^{1, 4}			ms	One iteration of scrubbing
Time to scrub the fabric data ¹			s	Full scrubbing
Time to scrub the pNVM data (like new) ^{1, 2}			s	Full scrubbing
Time to scrub the pNVM data (recoverable) ^{1, 3}			s	Full scrubbing
Time to scrub the fabric data pNVM data (non-recoverable) ¹			s	Full scrubbing
Time to verify ⁵			s	

1. Total completion time after entering zeroization.
2. Like new mode—zeroizes user design security setting and sNVM content.
3. Recoverable mode—zeroizes user design security setting, sNVM and factory keys.
4. Non-recoverable mode—zeroizes user design security setting, sNVM and factory keys, and factory data required for programming.
5. Time to verify after scrubbing completes.

7.6.7 Verify Time

The following tables describe verify time.

Table 81 • Standalone Fabric Verify Times

Parameter	Devices	Max	Unit
Standalone verification over JTAG	MPF100T, TL, TS, TLS		s
	MPF200T, TL, TS, TLS	53 ¹	s
	MPF300T, TL, TS, TLS	90 ¹	s
	MPF500T, TL, TS, TLS		s
Standalone verification over SPI	MPF100T, TL, TS, TLS		s
	MPF200T, TL, TS, TLS	37 ²	s
	MPF300T, TL, TS, TLS	55 ²	s
	MPF500T, TL, TS, TLS		s

1. Programmer: FlashPro5, TCK 10 MHz; PC configuration: Intel i7 at 3.6 GHz, 32 GB RAM, Windows 10.
2. SmartFusion2 with MSS running at 100 MHz, MSS_SPI_0 port running at 6.67 MHz. DirectC version 4.1.

Notes:

- Standalone verify is limited to 2,000 total device hours over the industrial –40 °C to 100 °C temperature.
- Use the digest system service, for verify device time more than 2,000 hours.
- Standalone verify checks the programming margin on both the P and N gates of the push-pull cell.
- Digest checks only the P side of the push-pull gate. However, the push-pull gates work in tandem. Digest check is recommended if users believe they will exceed the 2,000-hour verify time specification.

Table 82 • Verify Time by Programming Hardware

Devices	IAP	FlashPro4	FlashPro5	BP	Silicon Sculptor	Units
MPF100T, TL, TS, TLS						
MPF200T, TL, TS, TLS	9	67	53			s
MPF300T, TL, TS, TLS	14	95	90			s

Devices	IAP	FlashPro4	FlashPro5	BP	Silicon Sculptor	Units
MPF500T, TL, TS, TLS						

Notes:

- FlashPro4 4 MHz TCK.
- FlashPro5 10 MHz TCK.
- PC configuration: Intel i7 at 3.6 GHz, 32 GB RAM, Windows 10.

Table 83 • Verify System Services

Parameter	Symbol	ServiceID	Devices	Typ	Max	Unit
In application verify by index	T _{IAP_Ver_Index}	44H	MPF100T, TL, TS, TLS			s
			MPF200T, TL, TS, TLS	8.2	9	s
			MPF300T, TL, TS, TLS	12.4	13	s
			MPF500T, TL, TS, TLS			s
In application verify by SPI address	T _{IAP_Ver_Addr}	45H	MPF100T, TL, TS, TLS			s
			MPF200T, TL, TS, TLS	8.2	9	s
			MPF300T, TL, TS, TLS	12.4	13	s
			MPF500T, TL, TS, TLS			s

7.6.8 Authentication Time

The following tables describe authentication system service time.

Table 84 • Authentication Services


Parameter	Symbol	ServiceID	Devices	Typ	Max	Unit
Bitstream Authentication	T _{BIT_AUTH}	22H	MPF100T, TL, TS, TLS			s
			MPF200T, TL, TS, TLS	3.3	3.7	s
			MPF300T, TL, TS, TLS	4.9	5.4	s
			MPF500T, TL, TS, TLS			s
IAP Image Authentication	T _{IAP_AUTH}	23H	MPF100T, TL, TS, TLS			s
			MPF200T, TL, TS, TLS	3.3	3.7	s
			MPF300T, TL, TS, TLS	4.9	5.4	s
			MPF500T, TL, TS, TLS			s

7.6.9 Secure NVM Performance

The following table describes secure NVM performance.

Table 85 • sNVM Read/Write Characteristics

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Plain text programming		7.0	7.2	7.9	ms	
Authenticated text programming		7.2	7.4	9.4	ms	
Authenticated and encrypted text programming		7.2	7.4	9.4	ms	
Authentication R/W 1st access from power-up overhead	T _{PUF_OVHD}		100	111	ms	From T _{FAB_READY}
Plain text read		7.67	7.79	8.2	μs	

Figure 3 • UJTAG Timing Diagram

7.8.2 UJTAG_SEC Switching Characteristics

The following table describes characteristics of UJTAG_SEC switching.

Table 89 • UJTAG Security Performance Characteristics

Parameter	Symbol	Min	Typ	Max	Unit	Condition
TCK frequency	F _{TCK}				MHz	

7.8.3 USPI Switching Characteristics

The following section describes characteristics of USPI switching.

Table 90 • SPI Macro Interface Timing Characteristics

Parameter	Symbol	V _{DDI} = 3.3 V Max	V _{DDI} = 2.5 V Max	V _{DDI} = 1.8 V Max	V _{DDI} = 1.5 V Max	V _{DDI} = 1.2 V Max	Unit
Propagation delay from the fabric to pins ¹	TPD_MOSI	0.8	1	1.2	1.4	1.6	ns
	TPD_MISO	3.5	3.75	4	4.25	4.5	ns
	TPD_SS	3.5	3.75	4	4.25	4.5	ns
	TPD_SCK	3.5	3.75	4	4.25	4.5	ns
	TPD_MOSI_OE	3.5	3.75	4	4.25	4.5	ns
	TPD_SS_OE	3.5	3.75	4	4.25	4.5	ns
	TPD_SCK_OE	3.5	3.75	4	4.25	4.5	ns

1. Assumes CL of the relevant I/O standard as described in the input and output delay measurement tables.

Table 101 • Cold and Warm Boot

Parameter	Symbol	Min	Typ	Max	Unit	Condition
The time from T _{FAB_READY} to ready to program through JTAG/SPI-Slave		0	0	0	ms	
The time from T _{FAB_READY} to auto-update start			T _{PUF_OVHD} ¹	T _{PUF_OVHD} ¹	ms	
The time from T _{FAB_READY} to programming recovery start			T _{PUF_OVHD} ¹	T _{PUF_OVHD} ¹	ms	
The time from T _{FAB_READY} to the tamper flags being available	T _{TAMPER_READY}	0	0	0	ms	
The time from T _{FAB_READY} to the Athena Crypto co-processor being available (for S devices only)	T _{CRYPTO_READY}	0	0	0	ms	

1. Programming depends on the PUF to power up. Refer to T_{PUF_OVHD} at section [Secure NVM Performance](#) (see page 58).

7.9.8 I/O Calibration

The following tables specify the initial I/O calibration time for the fastest and slowest supported VDDI ramp times of 0.2 ms to 50 ms, respectively. This only applies to I/O banks specified by the user to be auto-calibrated.

Table 102 • I/O Initial Calibration Time (TCALIB)

Ramp Time	Min (ms)	Max (ms)	Condition
0.2 ms	0.98	2.63	Applies to HSIO and GPIO banks
50 ms	41.62	62.19	Applies to HSIO and GPIO banks

Notes:

- The user may specify any VDDI ramp time in the range specified above. The nominal initial calibration time is given by the specified VDDI ramp time plus 2 ms.
- In order for IO calibration to start, VDDI and VDDAUX of the I/O bank must be higher than the trip point levels specified in [I/O-Related Supplies](#) (see page 66).

Table 103 • I/O Fast Recalibration Time (TRECALIB)

I/O Type	Min (ms)	Typ (ms)	Max (ms)	Condition
GPIO bank	0.16	0.20	0.24	GPIO configured for 3.3 V operation
HSIO bank	0.20	0.25	0.30	HSIO configured for 1.8 V operation

Note: In order to obtain fast re-calibration, the user must assert the relevant clock request signal from the FPGA fabric to the I/O bank controller.

The following table describes the time to enter Flash*Freeze Mode and to exit Flash*Freeze mode.

7.11 User Crypto

The following section describes user crypto.

7.11.1 TeraFire 5200B Switching Characteristics

The following table describes TeraFire 5200B switching characteristics.

Table 112 • TeraFire F5200B Switching Characteristics

Parameter	Symbol	VDD = 1.0 V STD	VDD = 1.0 V – 1	VDD = 1.05 V STD	VDD = 1.05 V – 1	Unit	Condition
Operating frequency	F _{MAX}	189		189		MHz	–40 °C to 100 °C

7.11.2 TeraFire 5200B Throughput Characteristics

The following tables for each algorithm describe the TeraFire 5200B throughput characteristics.

Note: Throughput cycle count collected with Athena TeraFire Core and RISCv running at 100 MHz.

Table 113 • AES

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
AES-ECB-128 encrypt ¹	128	515	1095
	64K	50157	933
AES-ECB-128 decrypt ¹	128	557	1760
	64K	48385	1524
AES-ECB-256 encrypt ¹	128	531	1203
	64K	58349	1203
AES-ECB-256 decrypt ¹	128	589	1676
	64K	56673	1671
AES-CBC-256 encrypt ¹	128	576	1169
	64K	52547	1169
AES-CBC-256 decrypt ¹	128	585	1744
	64K	48565	1652
AES-GCM-128 encrypt ¹ , 128-bit tag, (full message encrypted/authenticated)	128	1925	2740
	64K	60070	2158
AES-GCM-256 encrypt ¹ , 128-bit tag, (full message encrypted/authenticated)	128	1973	2268
	64K	60102	2151

1. With DPA counter measures.

Table 114 • GMAC

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock- Cycles	CAL Delay In CPU Clock- Cycles
AES-GCM-256 ¹ , 128-bit tag, (message is only authenticated)	128	1863	2211
	64K	49707	2128

1. With DPA counter measures.

Table 115 • HMAC

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
HMAC-SHA-256 ¹ , 256-bit key	512	7477	2361
	64K	88367	2099
HMAC-SHA-384 ¹ , 384-bit key	1024	13049	2257
	64K	106103	2153

1. With DPA counter measures.

Table 116 • CMAC

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
AES-CMAC-256 ¹ (message is only authenticated)	128	446	9058
	64K	45494	111053

1. With DPA counter measures.

Table 117 • KEY TREE

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
128-bit nonce + 8-bit optype		102457	2751
256-bit nonce + 8-bit optype		103218	2089

Table 118 • SHA

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
SHA-1 ¹	512	2386	1579
	64K	77576	990
SHA-256 ¹	512	2516	884
	64K	84752	938
SHA-384 ¹	1024	4154	884
	64K	100222	938
SHA-512 ¹	1024	4154	881
	64K	100222	935

1. With DPA counter measures.

Table 119 • ECC

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
ECDSA SigGen, P-384/SHA-384 ¹	1024	12528912	6944
	8K	12540448	5643
ECDSA SigGen, P-384/SHA-384	1024	5502928	6155

ECDSA SigVer, P-384/SHA-384	1024	6421841	5759
	8K	6273510	5759
Key Agreement (KAS), P-384		5039125	6514
Point Multiply, P-256 ¹		5176923	4482
Point Multiply, P-384 ¹		12043199	5319
Point Multiply, P-521 ¹		26887187	6698
Point Addition, P-384		3018067	5779
KeyGen (PKG), P-384		12055368	6908
Point Verification, P-384		5091	3049

1. With DPA counter measures.

Table 120 • IFC (RSA)

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
Encrypt, RSA-2048, e=65537	2048	436972	8,972
Encrypt, RSA-3072, e=65537	3072	962162	12,583
Decrypt, RSA-2048 ¹ , CRT	2048	26862392	15900
Decrypt, RSA-3072 ¹ , CRT	3072	75153782	22015
Decrypt, RSA-4096, CRT	4096	89235615	23710
Decrypt, RSA-3072, CRT	3072	37880180	18638
SigGen, RSA-3072/SHA-384 ¹ , CRT, PKCS #1 V 1.1.5	1024	75197644	20032
	8K	75213653	19303
SigGen, RSA-3072/SHA-384, PKCS #1, V 1.5	1024	148090970	14642
	8K	148102576	13936
SigVer, RSA-3072/SHA-384, e = 65537, PKCS #1 V 1.5	1024	970991	12000
	8K	982011	11769
SigVer, RSA-2048/SHA-256, e = 65537, PKCS #1 V 1.5	1024	443493	8436
	8K	453007	8436
SigGen, RSA-3072/SHA-384, ANSI X9.31	1024	147138254	13945
	8K	147155896	13523
SigVer, RSA-3072/SHA-384, e = 65537, ANSI X9.31	1024	973269	11313
	8K	983255	11146

1. With DPA counter measures.

Table 121 • FFC (DH)

Modes	Message Size (bits)	Athena TeraFire Crypto Core Clock-Cycles	CAL Delay In CPU Clock-Cycles
SigGen, DSA-3072/SHA-384 ¹	1024	27932907	13969
	8K	27942415	13501
SigGen, DSA-3072/SHA-384	1024	12086356	13602
SigVer, DSA-3072/SHA-384	1024	24597916	15662
	8K	24229420	15133