

Welcome to [E-XFL.COM](#)

### Understanding [Embedded - FPGAs \(Field Programmable Gate Array\)](#)


Embedded - FPGAs, or Field Programmable Gate Arrays, are advanced integrated circuits that offer unparalleled flexibility and performance for digital systems. Unlike traditional fixed-function logic devices, FPGAs can be programmed and reprogrammed to execute a wide array of logical operations, enabling customized functionality tailored to specific applications. This reprogrammability allows developers to iterate designs quickly and implement complex functions without the need for custom hardware.

### Applications of Embedded - FPGAs

The versatility of Embedded - FPGAs makes them indispensable in numerous fields. In telecommunications.

#### Details

|                                |                                                                                                                                     |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Product Status                 | Active                                                                                                                              |
| Number of LABs/CLBs            | 1840                                                                                                                                |
| Number of Logic Elements/Cells | 29440                                                                                                                               |
| Total RAM Bits                 | 1105920                                                                                                                             |
| Number of I/O                  | 72                                                                                                                                  |
| Number of Gates                | -                                                                                                                                   |
| Voltage - Supply               | 1.16V ~ 1.24V                                                                                                                       |
| Mounting Type                  | Surface Mount                                                                                                                       |
| Operating Temperature          | 0°C ~ 85°C (TJ)                                                                                                                     |
| Package / Case                 | 169-LBGA                                                                                                                            |
| Supplier Device Package        | 169-FBGA (14x14)                                                                                                                    |
| Purchase URL                   | <a href="https://www.e-xfl.com/product-detail/intel/ep4cgx30bf14c7n">https://www.e-xfl.com/product-detail/intel/ep4cgx30bf14c7n</a> |


 A DC signal is equivalent to 100% duty cycle. For example, a signal that overshoots to 4.3 V can only be at 4.3 V for 65% over the lifetime of the device; for a device lifetime of 10 years, this amounts to 65/10ths of a year.

**Table 1–2. Maximum Allowed Overshoot During Transitions over a 10-Year Time Frame for Cyclone IV Devices**

| Symbol | Parameter        | Condition (V) | Overshoot Duration as % of High Time | Unit |
|--------|------------------|---------------|--------------------------------------|------|
| $V_i$  | AC Input Voltage | $V_i = 4.20$  | 100                                  | %    |
|        |                  | $V_i = 4.25$  | 98                                   | %    |
|        |                  | $V_i = 4.30$  | 65                                   | %    |
|        |                  | $V_i = 4.35$  | 43                                   | %    |
|        |                  | $V_i = 4.40$  | 29                                   | %    |
|        |                  | $V_i = 4.45$  | 20                                   | %    |
|        |                  | $V_i = 4.50$  | 13                                   | %    |
|        |                  | $V_i = 4.55$  | 9                                    | %    |
|        |                  | $V_i = 4.60$  | 6                                    | %    |

Figure 1–1 shows the methodology to determine the overshoot duration. The overshoot voltage is shown in red and is present on the input pin of the Cyclone IV device at over 4.3 V but below 4.4 V. From Table 1–2, for an overshoot of 4.3 V, the percentage of high time for the overshoot can be as high as 65% over a 10-year period. Percentage of high time is calculated as  $([\Delta T]/T) \times 100$ . This 10-year period assumes that the device is always turned on with 100% I/O toggle rate and 50% duty cycle signal. For lower I/O toggle rates and situations in which the device is in an idle state, lifetimes are increased.

**Figure 1–1. Cyclone IV Devices Overshoot Duration**



## Recommended Operating Conditions

This section lists the functional operation limits for AC and DC parameters for Cyclone IV devices. Table 1–3 and Table 1–4 list the steady-state voltage and current values expected from Cyclone IV E and Cyclone IV GX devices. All supplies must be strictly monotonic without plateaus.

**Table 1–3. Recommended Operating Conditions for Cyclone IV E Devices <sup>(1)</sup>, <sup>(2)</sup> (Part 1 of 2)**

| Symbol                | Parameter                                          | Conditions                                   | Min        | Typ | Max        | Unit |
|-----------------------|----------------------------------------------------|----------------------------------------------|------------|-----|------------|------|
| $V_{CCINT}^{(3)}$     | Supply voltage for internal logic, 1.2-V operation | —                                            | 1.15       | 1.2 | 1.25       | V    |
|                       | Supply voltage for internal logic, 1.0-V operation | —                                            | 0.97       | 1.0 | 1.03       | V    |
| $V_{CCIO}^{(3), (4)}$ | Supply voltage for output buffers, 3.3-V operation | —                                            | 3.135      | 3.3 | 3.465      | V    |
|                       | Supply voltage for output buffers, 3.0-V operation | —                                            | 2.85       | 3   | 3.15       | V    |
|                       | Supply voltage for output buffers, 2.5-V operation | —                                            | 2.375      | 2.5 | 2.625      | V    |
|                       | Supply voltage for output buffers, 1.8-V operation | —                                            | 1.71       | 1.8 | 1.89       | V    |
|                       | Supply voltage for output buffers, 1.5-V operation | —                                            | 1.425      | 1.5 | 1.575      | V    |
|                       | Supply voltage for output buffers, 1.2-V operation | —                                            | 1.14       | 1.2 | 1.26       | V    |
| $V_{CCA}^{(3)}$       | Supply (analog) voltage for PLL regulator          | —                                            | 2.375      | 2.5 | 2.625      | V    |
| $V_{CCD\_PLL}^{(3)}$  | Supply (digital) voltage for PLL, 1.2-V operation  | —                                            | 1.15       | 1.2 | 1.25       | V    |
|                       | Supply (digital) voltage for PLL, 1.0-V operation  | —                                            | 0.97       | 1.0 | 1.03       | V    |
| $V_I$                 | Input voltage                                      | —                                            | –0.5       | —   | 3.6        | V    |
| $V_O$                 | Output voltage                                     | —                                            | 0          | —   | $V_{CCIO}$ | V    |
| $T_J$                 | Operating junction temperature                     | For commercial use                           | 0          | —   | 85         | °C   |
|                       |                                                    | For industrial use                           | –40        | —   | 100        | °C   |
|                       |                                                    | For extended temperature                     | –40        | —   | 125        | °C   |
|                       |                                                    | For automotive use                           | –40        | —   | 125        | °C   |
| $t_{RAMP}$            | Power supply ramp time                             | Standard power-on reset (POR) <sup>(5)</sup> | 50 $\mu$ s | —   | 50 ms      | —    |
|                       |                                                    | Fast POR <sup>(6)</sup>                      | 50 $\mu$ s | —   | 3 ms       | —    |

Example 1–1 shows how to calculate the change of 50-Ω I/O impedance from 25°C at 3.0 V to 85°C at 3.15 V.

#### Example 1–1. Impedance Change

$$\Delta R_V = (3.15 - 3) \times 1000 \times -0.026 = -3.83$$

$$\Delta R_T = (85 - 25) \times 0.262 = 15.72$$

Because  $\Delta R_V$  is negative,

$$MF_V = 1 / (3.83/100 + 1) = 0.963$$

Because  $\Delta R_T$  is positive,

$$MF_T = 15.72/100 + 1 = 1.157$$

$$MF = 0.963 \times 1.157 = 1.114$$

$$R_{\text{final}} = 50 \times 1.114 = 55.71 \, \Omega$$

## Pin Capacitance

Table 1–11 lists the pin capacitance for Cyclone IV devices.

**Table 1–11. Pin Capacitance for Cyclone IV Devices <sup>(1)</sup>**

| Symbol                     | Parameter                                                                                                           | Typical –<br>Quad Flat<br>Pack<br>(QFP) | Typical –<br>Quad Flat<br>No Leads<br>(QFN) | Typical –<br>Ball-Grid<br>Array<br>(BGA) | Unit |
|----------------------------|---------------------------------------------------------------------------------------------------------------------|-----------------------------------------|---------------------------------------------|------------------------------------------|------|
| C <sub>IOTB</sub>          | Input capacitance on top and bottom I/O pins                                                                        | 7                                       | 7                                           | 6                                        | pF   |
| C <sub>IOLR</sub>          | Input capacitance on right I/O pins                                                                                 | 7                                       | 7                                           | 5                                        | pF   |
| C <sub>LVDSLR</sub>        | Input capacitance on right I/O pins with dedicated LVDS output                                                      | 8                                       | 8                                           | 7                                        | pF   |
| C <sub>VREFLR</sub><br>(2) | Input capacitance on right dual-purpose V <sub>REF</sub> pin when used as V <sub>REF</sub> or user I/O pin          | 21                                      | 21                                          | 21                                       | pF   |
| C <sub>VREFTB</sub><br>(2) | Input capacitance on top and bottom dual-purpose V <sub>REF</sub> pin when used as V <sub>REF</sub> or user I/O pin | 23 (3)                                  | 23                                          | 23                                       | pF   |
| C <sub>CLKTB</sub>         | Input capacitance on top and bottom dedicated clock input pins                                                      | 7                                       | 7                                           | 6                                        | pF   |
| C <sub>CLKLR</sub>         | Input capacitance on right dedicated clock input pins                                                               | 6                                       | 6                                           | 5                                        | pF   |

#### Notes to Table 1–11:

- (1) The pin capacitance applies to FBGA, UBGA, and MBGA packages.
- (2) When you use the V<sub>REF</sub> pin as a regular input or output, you can expect a reduced performance of toggle rate and t<sub>CO</sub> because of higher pin capacitance.
- (3) C<sub>VREFTB</sub> for the EP4CE22 device is 30 pF.

## Internal Weak Pull-Up and Weak Pull-Down Resistor

Table 1-12 lists the weak pull-up and pull-down resistor values for Cyclone IV devices.

**Table 1-12. Internal Weak Pull-Up and Weak Pull-Down Resistor Values for Cyclone IV Devices <sup>(1)</sup>**

| Symbol          | Parameter                                                                                                                                          | Conditions                                         | Min | Typ | Max | Unit |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|-----|-----|-----|------|
| R <sub>PU</sub> | Value of the I/O pin pull-up resistor before and during configuration, as well as user mode if you enable the programmable pull-up resistor option | V <sub>CCIO</sub> = 3.3 V ± 5% <sup>(2), (3)</sup> | 7   | 25  | 41  | kΩ   |
|                 |                                                                                                                                                    | V <sub>CCIO</sub> = 3.0 V ± 5% <sup>(2), (3)</sup> | 7   | 28  | 47  | kΩ   |
|                 |                                                                                                                                                    | V <sub>CCIO</sub> = 2.5 V ± 5% <sup>(2), (3)</sup> | 8   | 35  | 61  | kΩ   |
|                 |                                                                                                                                                    | V <sub>CCIO</sub> = 1.8 V ± 5% <sup>(2), (3)</sup> | 10  | 57  | 108 | kΩ   |
|                 |                                                                                                                                                    | V <sub>CCIO</sub> = 1.5 V ± 5% <sup>(2), (3)</sup> | 13  | 82  | 163 | kΩ   |
|                 |                                                                                                                                                    | V <sub>CCIO</sub> = 1.2 V ± 5% <sup>(2), (3)</sup> | 19  | 143 | 351 | kΩ   |
| R <sub>PD</sub> | Value of the I/O pin pull-down resistor before and during configuration                                                                            | V <sub>CCIO</sub> = 3.3 V ± 5% <sup>(4)</sup>      | 6   | 19  | 30  | kΩ   |
|                 |                                                                                                                                                    | V <sub>CCIO</sub> = 3.0 V ± 5% <sup>(4)</sup>      | 6   | 22  | 36  | kΩ   |
|                 |                                                                                                                                                    | V <sub>CCIO</sub> = 2.5 V ± 5% <sup>(4)</sup>      | 6   | 25  | 43  | kΩ   |
|                 |                                                                                                                                                    | V <sub>CCIO</sub> = 1.8 V ± 5% <sup>(4)</sup>      | 7   | 35  | 71  | kΩ   |
|                 |                                                                                                                                                    | V <sub>CCIO</sub> = 1.5 V ± 5% <sup>(4)</sup>      | 8   | 50  | 112 | kΩ   |

### Notes to Table 1-12:

- (1) All I/O pins have an option to enable weak pull-up except the configuration, test, and JTAG pins. The weak pull-down feature is only available for JTAG TCK.
- (2) Pin pull-up resistance values may be lower if an external source drives the pin higher than V<sub>CCIO</sub>.
- (3)  $R_{PU} = (V_{CCIO} - V_I) / I_{R_{PU}}$   
Minimum condition: -40°C; V<sub>CCIO</sub> = V<sub>CC</sub> + 5%, V<sub>I</sub> = V<sub>CC</sub> + 5% - 50 mV;  
Typical condition: 25°C; V<sub>CCIO</sub> = V<sub>CC</sub>, V<sub>I</sub> = 0 V;  
Maximum condition: 100°C; V<sub>CCIO</sub> = V<sub>CC</sub> - 5%, V<sub>I</sub> = 0 V; in which V<sub>I</sub> refers to the input voltage at the I/O pin.
- (4)  $R_{PD} = V_I / I_{R_{PD}}$   
Minimum condition: -40°C; V<sub>CCIO</sub> = V<sub>CC</sub> + 5%, V<sub>I</sub> = 50 mV;  
Typical condition: 25°C; V<sub>CCIO</sub> = V<sub>CC</sub>, V<sub>I</sub> = V<sub>CC</sub> - 5%;  
Maximum condition: 100°C; V<sub>CCIO</sub> = V<sub>CC</sub> - 5%, V<sub>I</sub> = V<sub>CC</sub> - 5%; in which V<sub>I</sub> refers to the input voltage at the I/O pin.

## Hot-Socketing

Table 1-13 lists the hot-socketing specifications for Cyclone IV devices.

**Table 1-13. Hot-Socketing Specifications for Cyclone IV Devices**

| Symbol                  | Parameter                         | Maximum             |
|-------------------------|-----------------------------------|---------------------|
| I <sub>IOPIN(DC)</sub>  | DC current per I/O pin            | 300 μA              |
| I <sub>IOPIN(AC)</sub>  | AC current per I/O pin            | 8 mA <sup>(1)</sup> |
| I <sub>XCVRTX(DC)</sub> | DC current per transceiver TX pin | 100 mA              |
| I <sub>XCVRRX(DC)</sub> | DC current per transceiver RX pin | 50 mA               |

### Note to Table 1-13:

- (1) The I/O ramp rate is 10 ns or more. For ramp rates faster than 10 ns, |I<sub>IOPIN</sub>| = C dv/dt, in which C is the I/O pin capacitance and dv/dt is the slew rate.



During hot-socketing, the I/O pin capacitance is less than 15 pF and the clock pin capacitance is less than 20 pF.

## Schmitt Trigger Input

Cyclone IV devices support Schmitt trigger input on the TDI, TMS, TCK, nSTATUS, nCONFIG, nCE, CONF\_DONE, and DCLK pins. A Schmitt trigger feature introduces hysteresis to the input signal for improved noise immunity, especially for signals with slow edge rate. Table 1–14 lists the hysteresis specifications across the supported  $V_{CCIO}$  range for Schmitt trigger inputs in Cyclone IV devices.

**Table 1–14. Hysteresis Specifications for Schmitt Trigger Input in Cyclone IV Devices**

| Symbol        | Parameter                            | Conditions (V)   | Minimum | Unit |
|---------------|--------------------------------------|------------------|---------|------|
| $V_{SCHMITT}$ | Hysteresis for Schmitt trigger input | $V_{CCIO} = 3.3$ | 200     | mV   |
|               |                                      | $V_{CCIO} = 2.5$ | 200     | mV   |
|               |                                      | $V_{CCIO} = 1.8$ | 140     | mV   |
|               |                                      | $V_{CCIO} = 1.5$ | 110     | mV   |

## I/O Standard Specifications

The following tables list input voltage sensitivities ( $V_{IH}$  and  $V_{IL}$ ), output voltage ( $V_{OH}$  and  $V_{OL}$ ), and current drive characteristics ( $I_{OH}$  and  $I_{OL}$ ), for various I/O standards supported by Cyclone IV devices. Table 1–15 through Table 1–20 provide the I/O standard specifications for Cyclone IV devices.

**Table 1–15. Single-Ended I/O Standard Specifications for Cyclone IV Devices <sup>(1), (2)</sup>**

| I/O Standard                | $V_{CCIO}$ (V) |     |       | $V_{IL}$ (V) |                        | $V_{IH}$ (V)           |                  | $V_{OL}$ (V)           | $V_{OH}$ (V)           | $I_{OL}$ (mA)<br>(4) | $I_{OH}$ (mA)<br>(4) |
|-----------------------------|----------------|-----|-------|--------------|------------------------|------------------------|------------------|------------------------|------------------------|----------------------|----------------------|
|                             | Min            | Typ | Max   | Min          | Max                    | Min                    | Max              | Max                    | Min                    |                      |                      |
| 3.3-V LVTTTL <sup>(3)</sup> | 3.135          | 3.3 | 3.465 | —            | 0.8                    | 1.7                    | 3.6              | 0.45                   | 2.4                    | 4                    | –4                   |
| 3.3-V LVCMOS <sup>(3)</sup> | 3.135          | 3.3 | 3.465 | —            | 0.8                    | 1.7                    | 3.6              | 0.2                    | $V_{CCIO} - 0.2$       | 2                    | –2                   |
| 3.0-V LVTTTL <sup>(3)</sup> | 2.85           | 3.0 | 3.15  | –0.3         | 0.8                    | 1.7                    | $V_{CCIO} + 0.3$ | 0.45                   | 2.4                    | 4                    | –4                   |
| 3.0-V LVCMOS <sup>(3)</sup> | 2.85           | 3.0 | 3.15  | –0.3         | 0.8                    | 1.7                    | $V_{CCIO} + 0.3$ | 0.2                    | $V_{CCIO} - 0.2$       | 0.1                  | –0.1                 |
| 2.5 V <sup>(3)</sup>        | 2.375          | 2.5 | 2.625 | –0.3         | 0.7                    | 1.7                    | $V_{CCIO} + 0.3$ | 0.4                    | 2.0                    | 1                    | –1                   |
| 1.8 V                       | 1.71           | 1.8 | 1.89  | –0.3         | $0.35 \times V_{CCIO}$ | $0.65 \times V_{CCIO}$ | 2.25             | 0.45                   | $V_{CCIO} - 0.45$      | 2                    | –2                   |
| 1.5 V                       | 1.425          | 1.5 | 1.575 | –0.3         | $0.35 \times V_{CCIO}$ | $0.65 \times V_{CCIO}$ | $V_{CCIO} + 0.3$ | $0.25 \times V_{CCIO}$ | $0.75 \times V_{CCIO}$ | 2                    | –2                   |
| 1.2 V                       | 1.14           | 1.2 | 1.26  | –0.3         | $0.35 \times V_{CCIO}$ | $0.65 \times V_{CCIO}$ | $V_{CCIO} + 0.3$ | $0.25 \times V_{CCIO}$ | $0.75 \times V_{CCIO}$ | 2                    | –2                   |
| 3.0-V PCI                   | 2.85           | 3.0 | 3.15  | —            | $0.3 \times V_{CCIO}$  | $0.5 \times V_{CCIO}$  | $V_{CCIO} + 0.3$ | $0.1 \times V_{CCIO}$  | $0.9 \times V_{CCIO}$  | 1.5                  | –0.5                 |
| 3.0-V PCI-X                 | 2.85           | 3.0 | 3.15  | —            | $0.35 \times V_{CCIO}$ | $0.5 \times V_{CCIO}$  | $V_{CCIO} + 0.3$ | $0.1 \times V_{CCIO}$  | $0.9 \times V_{CCIO}$  | 1.5                  | –0.5                 |

**Notes to Table 1–15:**

- (1) For voltage-referenced receiver input waveform and explanation of terms used in Table 1–15, refer to “Glossary” on page 1–37.
- (2) AC load  $CL = 10$  pF
- (3) For more information about interfacing Cyclone IV devices with 3.3/3.0/2.5-V LVTTTL/LVCMOS I/O standards, refer to *AN 447: Interfacing Cyclone III and Cyclone IV Devices with 3.3/3.0/2.5-V LVTTTL/LVCMOS I/O Systems*.
- (4) To meet the  $I_{OL}$  and  $I_{OH}$  specifications, you must set the current strength settings accordingly. For example, to meet the **3.3-V LVTTTL** specification (4 mA), set the current strength settings to 4 mA or higher. Setting at lower current strength may not meet the  $I_{OL}$  and  $I_{OH}$  specifications in the handbook.

Table 1–21. Transceiver Specification for Cyclone IV GX Devices (Part 2 of 4)

| Symbol/<br>Description                                                               | Conditions                                                            | C6                              |           |                                                   | C7, I7 |           |                                                   | C8   |           |                                                   | Unit |
|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------|---------------------------------|-----------|---------------------------------------------------|--------|-----------|---------------------------------------------------|------|-----------|---------------------------------------------------|------|
|                                                                                      |                                                                       | Min                             | Typ       | Max                                               | Min    | Typ       | Max                                               | Min  | Typ       | Max                                               |      |
| Receiver                                                                             |                                                                       |                                 |           |                                                   |        |           |                                                   |      |           |                                                   |      |
| Supported I/O Standards                                                              | 1.4 V PCML,<br>1.5 V PCML,<br>2.5 V PCML,<br>LVPECL, LVDS             |                                 |           |                                                   |        |           |                                                   |      |           |                                                   |      |
| Data rate (F324 and smaller package) <sup>(15)</sup>                                 | —                                                                     | 600                             | —         | 2500                                              | 600    | —         | 2500                                              | 600  | —         | 2500                                              | Mbps |
| Data rate (F484 and larger package) <sup>(15)</sup>                                  | —                                                                     | 600                             | —         | 3125                                              | 600    | —         | 3125                                              | 600  | —         | 2500                                              | Mbps |
| Absolute V <sub>MAX</sub> for a receiver pin <sup>(3)</sup>                          | —                                                                     | —                               | —         | 1.6                                               | —      | —         | 1.6                                               | —    | —         | 1.6                                               | V    |
| Operational V <sub>MAX</sub> for a receiver pin                                      | —                                                                     | —                               | —         | 1.5                                               | —      | —         | 1.5                                               | —    | —         | 1.5                                               | V    |
| Absolute V <sub>MIN</sub> for a receiver pin                                         | —                                                                     | –0.4                            | —         | —                                                 | –0.4   | —         | —                                                 | –0.4 | —         | —                                                 | V    |
| Peak-to-peak differential input voltage V <sub>ID</sub> (diff p-p)                   | V <sub>ICM</sub> = 0.82 V setting, Data Rate = 600 Mbps to 3.125 Gbps | 0.1                             | —         | 2.7                                               | 0.1    | —         | 2.7                                               | 0.1  | —         | 2.7                                               | V    |
| V <sub>ICM</sub>                                                                     | V <sub>ICM</sub> = 0.82 V setting                                     | —                               | 820 ± 10% | —                                                 | —      | 820 ± 10% | —                                                 | —    | 820 ± 10% | —                                                 | mV   |
| Differential on-chip termination resistors                                           | 100–Ω setting                                                         | —                               | 100       | —                                                 | —      | 100       | —                                                 | —    | 100       | —                                                 | Ω    |
|                                                                                      | 150–Ω setting                                                         | —                               | 150       | —                                                 | —      | 150       | —                                                 | —    | 150       | —                                                 | Ω    |
| Differential and common mode return loss                                             | PIPE, Serial Rapid I/O SR, SATA, CPRI LV, SDI, XAUI                   | Compliant                       |           |                                                   |        |           |                                                   |      |           |                                                   | —    |
| Programmable ppm detector <sup>(4)</sup>                                             | —                                                                     | ± 62.5, 100, 125, 200, 250, 300 |           |                                                   |        |           |                                                   |      |           |                                                   | ppm  |
| Clock data recovery (CDR) ppm tolerance (without spread-spectrum clocking enabled)   | —                                                                     | —                               | —         | ±300 <sup>(5)</sup> ,<br>±350 <sup>(6), (7)</sup> | —      | —         | ±300 <sup>(5)</sup> ,<br>±350 <sup>(6), (7)</sup> | —    | —         | ±300 <sup>(5)</sup> ,<br>±350 <sup>(6), (7)</sup> | ppm  |
| CDR ppm tolerance (with synchronous spread-spectrum clocking enabled) <sup>(8)</sup> | —                                                                     | —                               | —         | 350 to –5350 <sup>(7), (9)</sup>                  | —      | —         | 350 to –5350 <sup>(7), (9)</sup>                  | —    | —         | 350 to –5350 <sup>(7), (9)</sup>                  | ppm  |
| Run length                                                                           | —                                                                     | —                               | 80        | —                                                 | —      | 80        | —                                                 | —    | 80        | —                                                 | UI   |
| Programmable equalization                                                            | No Equalization                                                       | —                               | —         | 1.5                                               | —      | —         | 1.5                                               | —    | —         | 1.5                                               | dB   |
|                                                                                      | Medium Low                                                            | —                               | —         | 4.5                                               | —      | —         | 4.5                                               | —    | —         | 4.5                                               | dB   |
|                                                                                      | Medium High                                                           | —                               | —         | 5.5                                               | —      | —         | 5.5                                               | —    | —         | 5.5                                               | dB   |
|                                                                                      | High                                                                  | —                               | —         | 7                                                 | —      | —         | 7                                                 | —    | —         | 7                                                 | dB   |

**Table 1–24. Clock Tree Performance for Cyclone IV Devices (Part 2 of 2)**

| Device    | Performance |       |     |                    |                    |       |                    |    | Unit |
|-----------|-------------|-------|-----|--------------------|--------------------|-------|--------------------|----|------|
|           | C6          | C7    | C8  | C8L <sup>(1)</sup> | C9L <sup>(1)</sup> | I7    | I8L <sup>(1)</sup> | A7 |      |
| EP4CE55   | 500         | 437.5 | 402 | 362                | 265                | 437.5 | 362                | —  | MHz  |
| EP4CE75   | 500         | 437.5 | 402 | 362                | 265                | 437.5 | 362                | —  | MHz  |
| EP4CE115  | —           | 437.5 | 402 | 362                | 265                | 437.5 | 362                | —  | MHz  |
| EP4CGX15  | 500         | 437.5 | 402 | —                  | —                  | 437.5 | —                  | —  | MHz  |
| EP4CGX22  | 500         | 437.5 | 402 | —                  | —                  | 437.5 | —                  | —  | MHz  |
| EP4CGX30  | 500         | 437.5 | 402 | —                  | —                  | 437.5 | —                  | —  | MHz  |
| EP4CGX50  | 500         | 437.5 | 402 | —                  | —                  | 437.5 | —                  | —  | MHz  |
| EP4CGX75  | 500         | 437.5 | 402 | —                  | —                  | 437.5 | —                  | —  | MHz  |
| EP4CGX110 | 500         | 437.5 | 402 | —                  | —                  | 437.5 | —                  | —  | MHz  |
| EP4CGX150 | 500         | 437.5 | 402 | —                  | —                  | 437.5 | —                  | —  | MHz  |

**Note to Table 1–24:**

(1) Cyclone IV E 1.0 V core voltage devices only support C8L, C9L, and I8L speed grades.


## PLL Specifications


Table 1–25 lists the PLL specifications for Cyclone IV devices when operating in the commercial junction temperature range (0°C to 85°C), the industrial junction temperature range (–40°C to 100°C), the extended industrial junction temperature range (–40°C to 125°C), and the automotive junction temperature range (–40°C to 125°C). For more information about the PLL block, refer to “Glossary” on page 1–37.

**Table 1–25. PLL Specifications for Cyclone IV Devices <sup>(1), (2)</sup> (Part 1 of 2)**

| Symbol                                                | Parameter                                                   | Min | Typ | Max   | Unit |
|-------------------------------------------------------|-------------------------------------------------------------|-----|-----|-------|------|
| $f_{IN}$ <sup>(3)</sup>                               | Input clock frequency (–6, –7, –8 speed grades)             | 5   | —   | 472.5 | MHz  |
|                                                       | Input clock frequency (–8L speed grade)                     | 5   | —   | 362   | MHz  |
|                                                       | Input clock frequency (–9L speed grade)                     | 5   | —   | 265   | MHz  |
| $f_{INPFD}$                                           | PFD input frequency                                         | 5   | —   | 325   | MHz  |
| $f_{VCO}$ <sup>(4)</sup>                              | PLL internal VCO operating range                            | 600 | —   | 1300  | MHz  |
| $f_{INDUTY}$                                          | Input clock duty cycle                                      | 40  | —   | 60    | %    |
| $t_{INJITTER\_CCJ}$ <sup>(5)</sup>                    | Input clock cycle-to-cycle jitter<br>$F_{REF} \geq 100$ MHz | —   | —   | 0.15  | UI   |
|                                                       | $F_{REF} < 100$ MHz                                         | —   | —   | ±750  | ps   |
| $f_{OUT\_EXT}$ (external clock output) <sup>(3)</sup> | PLL output frequency                                        | —   | —   | 472.5 | MHz  |
| $f_{OUT}$ (to global clock)                           | PLL output frequency (–6 speed grade)                       | —   | —   | 472.5 | MHz  |
|                                                       | PLL output frequency (–7 speed grade)                       | —   | —   | 450   | MHz  |
|                                                       | PLL output frequency (–8 speed grade)                       | —   | —   | 402.5 | MHz  |
|                                                       | PLL output frequency (–8L speed grade)                      | —   | —   | 362   | MHz  |
|                                                       | PLL output frequency (–9L speed grade)                      | —   | —   | 265   | MHz  |
| $t_{OUTDUTY}$                                         | Duty cycle for external clock output (when set to 50%)      | 45  | 50  | 55    | %    |
| $t_{LOCK}$                                            | Time required to lock from end of device configuration      | —   | —   | 1     | ms   |



 For more information about the supported maximum clock rate, device and pin planning, IP implementation, and device termination, refer to *Section III: System Performance Specifications* of the *External Memory Interfaces Handbook*.

 Actual achievable frequency depends on design- and system-specific factors. Perform HSPICE/IBIS simulations based on your specific design and system setup to determine the maximum achievable frequency in your system.

## High-Speed I/O Specifications

Table 1–31 through Table 1–36 list the high-speed I/O timing for Cyclone IV devices. For definitions of high-speed timing specifications, refer to “Glossary” on page 1–37.

**Table 1–31. RSDS Transmitter Timing Specifications for Cyclone IV Devices <sup>(1)</sup>, <sup>(2)</sup>, <sup>(4)</sup> (Part 1 of 2)**

| Symbol                                        | Modes                                         | C6  |     |     | C7, I7 |     |       | C8, A7 |     |       | C8L, I8L |     |       | C9L |     |       | Unit |
|-----------------------------------------------|-----------------------------------------------|-----|-----|-----|--------|-----|-------|--------|-----|-------|----------|-----|-------|-----|-----|-------|------|
|                                               |                                               | Min | Typ | Max | Min    | Typ | Max   | Min    | Typ | Max   | Min      | Typ | Max   | Min | Typ | Max   |      |
| $f_{\text{HSCLK}}$<br>(input clock frequency) | ×10                                           | 5   | —   | 180 | 5      | —   | 155.5 | 5      | —   | 155.5 | 5        | —   | 155.5 | 5   | —   | 132.5 | MHz  |
|                                               | ×8                                            | 5   | —   | 180 | 5      | —   | 155.5 | 5      | —   | 155.5 | 5        | —   | 155.5 | 5   | —   | 132.5 | MHz  |
|                                               | ×7                                            | 5   | —   | 180 | 5      | —   | 155.5 | 5      | —   | 155.5 | 5        | —   | 155.5 | 5   | —   | 132.5 | MHz  |
|                                               | ×4                                            | 5   | —   | 180 | 5      | —   | 155.5 | 5      | —   | 155.5 | 5        | —   | 155.5 | 5   | —   | 132.5 | MHz  |
|                                               | ×2                                            | 5   | —   | 180 | 5      | —   | 155.5 | 5      | —   | 155.5 | 5        | —   | 155.5 | 5   | —   | 132.5 | MHz  |
|                                               | ×1                                            | 5   | —   | 360 | 5      | —   | 311   | 5      | —   | 311   | 5        | —   | 311   | 5   | —   | 265   | MHz  |
| Device operation in Mbps                      | ×10                                           | 100 | —   | 360 | 100    | —   | 311   | 100    | —   | 311   | 100      | —   | 311   | 100 | —   | 265   | Mbps |
|                                               | ×8                                            | 80  | —   | 360 | 80     | —   | 311   | 80     | —   | 311   | 80       | —   | 311   | 80  | —   | 265   | Mbps |
|                                               | ×7                                            | 70  | —   | 360 | 70     | —   | 311   | 70     | —   | 311   | 70       | —   | 311   | 70  | —   | 265   | Mbps |
|                                               | ×4                                            | 40  | —   | 360 | 40     | —   | 311   | 40     | —   | 311   | 40       | —   | 311   | 40  | —   | 265   | Mbps |
|                                               | ×2                                            | 20  | —   | 360 | 20     | —   | 311   | 20     | —   | 311   | 20       | —   | 311   | 20  | —   | 265   | Mbps |
|                                               | ×1                                            | 10  | —   | 360 | 10     | —   | 311   | 10     | —   | 311   | 10       | —   | 311   | 10  | —   | 265   | Mbps |
| $t_{\text{DUTY}}$                             | —                                             | 45  | —   | 55  | 45     | —   | 55    | 45     | —   | 55    | 45       | —   | 55    | 45  | —   | 55    | %    |
| Transmitter channel-to-channel skew (TCCS)    | —                                             | —   | —   | 200 | —      | —   | 200   | —      | —   | 200   | —        | —   | 200   | —   | —   | 200   | ps   |
| Output jitter (peak to peak)                  | —                                             | —   | —   | 500 | —      | —   | 500   | —      | —   | 550   | —        | —   | 600   | —   | —   | 700   | ps   |
| $t_{\text{RISE}}$                             | 20 – 80%,<br>$C_{\text{LOAD}} = 5 \text{ pF}$ | —   | 500 | —   | —      | 500 | —     | —      | 500 | —     | —        | 500 | —     | —   | 500 | —     | ps   |
| $t_{\text{FALL}}$                             | 20 – 80%,<br>$C_{\text{LOAD}} = 5 \text{ pF}$ | —   | 500 | —   | —      | 500 | —     | —      | 500 | —     | —        | 500 | —     | —   | 500 | —     | ps   |

**Table 1-31. RSDS Transmitter Timing Specifications for Cyclone IV Devices <sup>(1), (2), (4)</sup> (Part 2 of 2)**

| Symbol                           | Modes | C6  |     |     | C7, I7 |     |     | C8, A7 |     |     | C8L, I8L |     |     | C9L |     |     | Unit |
|----------------------------------|-------|-----|-----|-----|--------|-----|-----|--------|-----|-----|----------|-----|-----|-----|-----|-----|------|
|                                  |       | Min | Typ | Max | Min    | Typ | Max | Min    | Typ | Max | Min      | Typ | Max | Min | Typ | Max |      |
| t <sub>LOCK</sub> <sup>(3)</sup> | —     | —   | —   | 1   | —      | —   | 1   | —      | —   | 1   | —        | —   | 1   | —   | —   | 1   | ms   |

**Notes to Table 1-31:**

- (1) Applicable for true RSDS and emulated RSDS\_E\_3R transmitter.
- (2) Cyclone IV E devices—true RSDS transmitter is only supported at the output pin of Row I/O Banks 1, 2, 5, and 6. Emulated RSDS transmitter is supported at the output pin of all I/O Banks.  
Cyclone IV GX devices—true RSDS transmitter is only supported at the output pin of Row I/O Banks 5 and 6. Emulated RSDS transmitter is supported at the output pin of I/O Banks 3, 4, 5, 6, 7, 8, and 9.
- (3) t<sub>LOCK</sub> is the time required for the PLL to lock from the end-of-device configuration.
- (4) Cyclone IV E 1.0 V core voltage devices only support C8L, C9L, and I8L speed grades. Cyclone IV E 1.2 V core voltage devices only support C6, C7, C8, I7, and A7 speed grades. Cyclone IV GX devices only support C6, C7, C8, and I7 speed grades.

**Table 1-32. Emulated RSDS\_E\_1R Transmitter Timing Specifications for Cyclone IV Devices <sup>(1), (3)</sup> (Part 1 of 2)**

| Symbol                                    | Modes                                 | C6  |     |     | C7, I7 |     |     | C8, A7 |     |     | C8L, I8L |     |     | C9L |     |      | Unit |
|-------------------------------------------|---------------------------------------|-----|-----|-----|--------|-----|-----|--------|-----|-----|----------|-----|-----|-----|-----|------|------|
|                                           |                                       | Min | Typ | Max | Min    | Typ | Max | Min    | Typ | Max | Min      | Typ | Max | Min | Typ | Max  |      |
| f <sub>HCLK</sub> (input clock frequency) | ×10                                   | 5   | —   | 85  | 5      | —   | 85  | 5      | —   | 85  | 5        | —   | 85  | 5   | —   | 72.5 | MHz  |
|                                           | ×8                                    | 5   | —   | 85  | 5      | —   | 85  | 5      | —   | 85  | 5        | —   | 85  | 5   | —   | 72.5 | MHz  |
|                                           | ×7                                    | 5   | —   | 85  | 5      | —   | 85  | 5      | —   | 85  | 5        | —   | 85  | 5   | —   | 72.5 | MHz  |
|                                           | ×4                                    | 5   | —   | 85  | 5      | —   | 85  | 5      | —   | 85  | 5        | —   | 85  | 5   | —   | 72.5 | MHz  |
|                                           | ×2                                    | 5   | —   | 85  | 5      | —   | 85  | 5      | —   | 85  | 5        | —   | 85  | 5   | —   | 72.5 | MHz  |
|                                           | ×1                                    | 5   | —   | 170 | 5      | —   | 170 | 5      | —   | 170 | 5        | —   | 170 | 5   | —   | 145  | MHz  |
| Device operation in Mbps                  | ×10                                   | 100 | —   | 170 | 100    | —   | 170 | 100    | —   | 170 | 100      | —   | 170 | 100 | —   | 145  | Mbps |
|                                           | ×8                                    | 80  | —   | 170 | 80     | —   | 170 | 80     | —   | 170 | 80       | —   | 170 | 80  | —   | 145  | Mbps |
|                                           | ×7                                    | 70  | —   | 170 | 70     | —   | 170 | 70     | —   | 170 | 70       | —   | 170 | 70  | —   | 145  | Mbps |
|                                           | ×4                                    | 40  | —   | 170 | 40     | —   | 170 | 40     | —   | 170 | 40       | —   | 170 | 40  | —   | 145  | Mbps |
|                                           | ×2                                    | 20  | —   | 170 | 20     | —   | 170 | 20     | —   | 170 | 20       | —   | 170 | 20  | —   | 145  | Mbps |
|                                           | ×1                                    | 10  | —   | 170 | 10     | —   | 170 | 10     | —   | 170 | 10       | —   | 170 | 10  | —   | 145  | Mbps |
| t <sub>DUTY</sub>                         | —                                     | 45  | —   | 55  | 45     | —   | 55  | 45     | —   | 55  | 45       | —   | 55  | 45  | —   | 55   | %    |
| TCCS                                      | —                                     | —   | —   | 200 | —      | —   | 200 | —      | —   | 200 | —        | —   | 200 | —   | —   | 200  | ps   |
| Output jitter (peak to peak)              | —                                     | —   | —   | 500 | —      | —   | 500 | —      | —   | 550 | —        | —   | 600 | —   | —   | 700  | ps   |
| t <sub>RISE</sub>                         | 20 – 80%,<br>C <sub>LOAD</sub> = 5 pF | —   | 500 | —   | —      | 500 | —   | —      | 500 | —   | —        | 500 | —   | —   | 500 | —    | ps   |
| t <sub>FALL</sub>                         | 20 – 80%,<br>C <sub>LOAD</sub> = 5 pF | —   | 500 | —   | —      | 500 | —   | —      | 500 | —   | —        | 500 | —   | —   | 500 | —    | ps   |

**Table 1-34. True LVDS Transmitter Timing Specifications for Cyclone IV Devices <sup>(1)</sup>, <sup>(3)</sup>**

| Symbol                                    | Modes | C6  |     | C7, I7 |       | C8, A7 |       | C8L, I8L |     | C9L |     | Unit |
|-------------------------------------------|-------|-----|-----|--------|-------|--------|-------|----------|-----|-----|-----|------|
|                                           |       | Min | Max | Min    | Max   | Min    | Max   | Min      | Max | Min | Max |      |
| f <sub>HCLK</sub> (input clock frequency) | ×10   | 5   | 420 | 5      | 370   | 5      | 320   | 5        | 320 | 5   | 250 | MHz  |
|                                           | ×8    | 5   | 420 | 5      | 370   | 5      | 320   | 5        | 320 | 5   | 250 | MHz  |
|                                           | ×7    | 5   | 420 | 5      | 370   | 5      | 320   | 5        | 320 | 5   | 250 | MHz  |
|                                           | ×4    | 5   | 420 | 5      | 370   | 5      | 320   | 5        | 320 | 5   | 250 | MHz  |
|                                           | ×2    | 5   | 420 | 5      | 370   | 5      | 320   | 5        | 320 | 5   | 250 | MHz  |
|                                           | ×1    | 5   | 420 | 5      | 402.5 | 5      | 402.5 | 5        | 362 | 5   | 265 | MHz  |
| HSIODR                                    | ×10   | 100 | 840 | 100    | 740   | 100    | 640   | 100      | 640 | 100 | 500 | Mbps |
|                                           | ×8    | 80  | 840 | 80     | 740   | 80     | 640   | 80       | 640 | 80  | 500 | Mbps |
|                                           | ×7    | 70  | 840 | 70     | 740   | 70     | 640   | 70       | 640 | 70  | 500 | Mbps |
|                                           | ×4    | 40  | 840 | 40     | 740   | 40     | 640   | 40       | 640 | 40  | 500 | Mbps |
|                                           | ×2    | 20  | 840 | 20     | 740   | 20     | 640   | 20       | 640 | 20  | 500 | Mbps |
|                                           | ×1    | 10  | 420 | 10     | 402.5 | 10     | 402.5 | 10       | 362 | 10  | 265 | Mbps |
| t <sub>DUTY</sub>                         | —     | 45  | 55  | 45     | 55    | 45     | 55    | 45       | 55  | 45  | 55  | %    |
| TCCS                                      | —     | —   | 200 | —      | 200   | —      | 200   | —        | 200 | —   | 200 | ps   |
| Output jitter (peak to peak)              | —     | —   | 500 | —      | 500   | —      | 550   | —        | 600 | —   | 700 | ps   |
| t <sub>LOCK</sub> <sup>(2)</sup>          | —     | —   | 1   | —      | 1     | —      | 1     | —        | 1   | —   | 1   | ms   |

**Notes to Table 1-34:**

- (1) Cyclone IV E—true LVDS transmitter is only supported at the output pin of Row I/O Banks 1, 2, 5, and 6. Cyclone IV GX—true LVDS transmitter is only supported at the output pin of Row I/O Banks 5 and 6.
- (2) t<sub>LOCK</sub> is the time required for the PLL to lock from the end-of-device configuration.
- (3) Cyclone IV E 1.0 V core voltage devices only support C8L, C9L, and I8L speed grades. Cyclone IV E 1.2 V core voltage devices only support C6, C7, C8, I7, and A7 speed grades. Cyclone IV GX devices only support C6, C7, C8, and I7 speed grades.

**Table 1-35. Emulated LVDS Transmitter Timing Specifications for Cyclone IV Devices <sup>(1)</sup>, <sup>(3)</sup> (Part 1 of 2)**

| Symbol                                    | Modes | C6  |       | C7, I7 |       | C8, A7 |       | C8L, I8L |     | C9L |     | Unit |
|-------------------------------------------|-------|-----|-------|--------|-------|--------|-------|----------|-----|-----|-----|------|
|                                           |       | Min | Max   | Min    | Max   | Min    | Max   | Min      | Max | Min | Max |      |
| f <sub>HCLK</sub> (input clock frequency) | ×10   | 5   | 320   | 5      | 320   | 5      | 275   | 5        | 275 | 5   | 250 | MHz  |
|                                           | ×8    | 5   | 320   | 5      | 320   | 5      | 275   | 5        | 275 | 5   | 250 | MHz  |
|                                           | ×7    | 5   | 320   | 5      | 320   | 5      | 275   | 5        | 275 | 5   | 250 | MHz  |
|                                           | ×4    | 5   | 320   | 5      | 320   | 5      | 275   | 5        | 275 | 5   | 250 | MHz  |
|                                           | ×2    | 5   | 320   | 5      | 320   | 5      | 275   | 5        | 275 | 5   | 250 | MHz  |
|                                           | ×1    | 5   | 402.5 | 5      | 402.5 | 5      | 402.5 | 5        | 362 | 5   | 265 | MHz  |
| HSIODR                                    | ×10   | 100 | 640   | 100    | 640   | 100    | 550   | 100      | 550 | 100 | 500 | Mbps |
|                                           | ×8    | 80  | 640   | 80     | 640   | 80     | 550   | 80       | 550 | 80  | 500 | Mbps |
|                                           | ×7    | 70  | 640   | 70     | 640   | 70     | 550   | 70       | 550 | 70  | 500 | Mbps |
|                                           | ×4    | 40  | 640   | 40     | 640   | 40     | 550   | 40       | 550 | 40  | 500 | Mbps |
|                                           | ×2    | 20  | 640   | 20     | 640   | 20     | 550   | 20       | 550 | 20  | 500 | Mbps |
|                                           | ×1    | 10  | 402.5 | 10     | 402.5 | 10     | 402.5 | 10       | 362 | 10  | 265 | Mbps |

**Table 1–35. Emulated LVDS Transmitter Timing Specifications for Cyclone IV Devices <sup>(1), (3)</sup> (Part 2 of 2)**

| Symbol                           | Modes | C6  |     | C7, I7 |     | C8, A7 |     | C8L, I8L |     | C9L |     | Unit |
|----------------------------------|-------|-----|-----|--------|-----|--------|-----|----------|-----|-----|-----|------|
|                                  |       | Min | Max | Min    | Max | Min    | Max | Min      | Max | Min | Max |      |
| t <sub>DUTY</sub>                | —     | 45  | 55  | 45     | 55  | 45     | 55  | 45       | 55  | 45  | 55  | %    |
| TCCS                             | —     | —   | 200 | —      | 200 | —      | 200 | —        | 200 | —   | 200 | ps   |
| Output jitter (peak to peak)     | —     | —   | 500 | —      | 500 | —      | 550 | —        | 600 | —   | 700 | ps   |
| t <sub>LOCK</sub> <sup>(2)</sup> | —     | —   | 1   | —      | 1   | —      | 1   | —        | 1   | —   | 1   | ms   |

**Notes to Table 1–35:**

- (1) Cyclone IV E—emulated LVDS transmitter is supported at the output pin of all I/O Banks.  
Cyclone IV GX—emulated LVDS transmitter is supported at the output pin of I/O Banks 3, 4, 5, 6, 7, 8, and 9.
- (2) t<sub>LOCK</sub> is the time required for the PLL to lock from the end-of-device configuration.
- (3) Cyclone IV E 1.0 V core voltage devices only support C8L, C9L, and I8L speed grades. Cyclone IV E 1.2 V core voltage devices only support C6, C7, C8, I7, and A7 speed grades. Cyclone IV GX devices only support C6, C7, C8, and I7 speed grades.

**Table 1–36. LVDS Receiver Timing Specifications for Cyclone IV Devices <sup>(1), (3)</sup>**

| Symbol                                    | Modes | C6  |       | C7, I7 |       | C8, A7 |       | C8L, I8L |     | C9L |     | Unit |
|-------------------------------------------|-------|-----|-------|--------|-------|--------|-------|----------|-----|-----|-----|------|
|                                           |       | Min | Max   | Min    | Max   | Min    | Max   | Min      | Max | Min | Max |      |
| f <sub>HCLK</sub> (input clock frequency) | ×10   | 10  | 437.5 | 10     | 370   | 10     | 320   | 10       | 320 | 10  | 250 | MHz  |
|                                           | ×8    | 10  | 437.5 | 10     | 370   | 10     | 320   | 10       | 320 | 10  | 250 | MHz  |
|                                           | ×7    | 10  | 437.5 | 10     | 370   | 10     | 320   | 10       | 320 | 10  | 250 | MHz  |
|                                           | ×4    | 10  | 437.5 | 10     | 370   | 10     | 320   | 10       | 320 | 10  | 250 | MHz  |
|                                           | ×2    | 10  | 437.5 | 10     | 370   | 10     | 320   | 10       | 320 | 10  | 250 | MHz  |
|                                           | ×1    | 10  | 437.5 | 10     | 402.5 | 10     | 402.5 | 10       | 362 | 10  | 265 | MHz  |
| HSIODR                                    | ×10   | 100 | 875   | 100    | 740   | 100    | 640   | 100      | 640 | 100 | 500 | Mbps |
|                                           | ×8    | 80  | 875   | 80     | 740   | 80     | 640   | 80       | 640 | 80  | 500 | Mbps |
|                                           | ×7    | 70  | 875   | 70     | 740   | 70     | 640   | 70       | 640 | 70  | 500 | Mbps |
|                                           | ×4    | 40  | 875   | 40     | 740   | 40     | 640   | 40       | 640 | 40  | 500 | Mbps |
|                                           | ×2    | 20  | 875   | 20     | 740   | 20     | 640   | 20       | 640 | 20  | 500 | Mbps |
|                                           | ×1    | 10  | 437.5 | 10     | 402.5 | 10     | 402.5 | 10       | 362 | 10  | 265 | Mbps |
| SW                                        | —     | —   | 400   | —      | 400   | —      | 400   | —        | 550 | —   | 640 | ps   |
| Input jitter tolerance                    | —     | —   | 500   | —      | 500   | —      | 550   | —        | 600 | —   | 700 | ps   |
| t <sub>LOCK</sub> <sup>(2)</sup>          | —     | —   | 1     | —      | 1     | —      | 1     | —        | 1   | —   | 1   | ms   |

**Notes to Table 1–36:**

- (1) Cyclone IV E—LVDS receiver is supported at all I/O Banks.  
Cyclone IV GX—LVDS receiver is supported at I/O Banks 3, 4, 5, 6, 7, 8, and 9.
- (2) t<sub>LOCK</sub> is the time required for the PLL to lock from the end-of-device configuration.
- (3) Cyclone IV E 1.0 V core voltage devices only support C8L, C9L, and I8L speed grades. Cyclone IV E 1.2 V core voltage devices only support C6, C7, C8, I7, and A7 speed grades. Cyclone IV GX devices only support C6, C7, C8, and I7 speed grades.

## External Memory Interface Specifications

The external memory interfaces for Cyclone IV devices are auto-calibrating and easy to implement.

Table 1–42 and Table 1–43 list the IOE programmable delay for Cyclone IV E 1.2 V core voltage devices.

**Table 1–42. IOE Programmable Delay on Column Pins for Cyclone IV E 1.2 V Core Voltage Devices <sup>(1), (2)</sup>**

| Parameter                                                       | Paths Affected              | Number of Setting | Min Offset | Max Offset  |       |       |             |       |       |       |       | Unit |
|-----------------------------------------------------------------|-----------------------------|-------------------|------------|-------------|-------|-------|-------------|-------|-------|-------|-------|------|
|                                                                 |                             |                   |            | Fast Corner |       |       | Slow Corner |       |       |       |       |      |
|                                                                 |                             |                   |            | C6          | I7    | A7    | C6          | C7    | C8    | I7    | A7    |      |
| Input delay from pin to internal cells                          | Pad to I/O dataout to core  | 7                 | 0          | 1.314       | 1.211 | 1.211 | 2.177       | 2.340 | 2.433 | 2.388 | 2.508 | ns   |
| Input delay from pin to input register                          | Pad to I/O input register   | 8                 | 0          | 1.307       | 1.203 | 1.203 | 2.19        | 2.387 | 2.540 | 2.430 | 2.545 | ns   |
| Delay from output register to output pin                        | I/O output register to pad  | 2                 | 0          | 0.437       | 0.402 | 0.402 | 0.747       | 0.820 | 0.880 | 0.834 | 0.873 | ns   |
| Input delay from dual-purpose clock pin to fan-out destinations | Pad to global clock network | 12                | 0          | 0.693       | 0.665 | 0.665 | 1.200       | 1.379 | 1.532 | 1.393 | 1.441 | ns   |

**Notes to Table 1–42:**

- (1) The incremental values for the settings are generally linear. For the exact values for each setting, use the latest version of the Quartus II software.
- (2) The minimum and maximum offset timing numbers are in reference to setting **0** as available in the Quartus II software.

**Table 1–43. IOE Programmable Delay on Row Pins for Cyclone IV E 1.2 V Core Voltage Devices <sup>(1), (2)</sup>**

| Parameter                                                       | Paths Affected              | Number of Setting | Min Offset | Max Offset  |       |       |             |       |       |       |       | Unit |
|-----------------------------------------------------------------|-----------------------------|-------------------|------------|-------------|-------|-------|-------------|-------|-------|-------|-------|------|
|                                                                 |                             |                   |            | Fast Corner |       |       | Slow Corner |       |       |       |       |      |
|                                                                 |                             |                   |            | C6          | I7    | A7    | C6          | C7    | C8    | I7    | A7    |      |
| Input delay from pin to internal cells                          | Pad to I/O dataout to core  | 7                 | 0          | 1.314       | 1.209 | 1.209 | 2.201       | 2.386 | 2.510 | 2.429 | 2.548 | ns   |
| Input delay from pin to input register                          | Pad to I/O input register   | 8                 | 0          | 1.312       | 1.207 | 1.207 | 2.202       | 2.402 | 2.558 | 2.447 | 2.557 | ns   |
| Delay from output register to output pin                        | I/O output register to pad  | 2                 | 0          | 0.458       | 0.419 | 0.419 | 0.783       | 0.861 | 0.924 | 0.875 | 0.915 | ns   |
| Input delay from dual-purpose clock pin to fan-out destinations | Pad to global clock network | 12                | 0          | 0.686       | 0.657 | 0.657 | 1.185       | 1.360 | 1.506 | 1.376 | 1.422 | ns   |

**Notes to Table 1–43:**

- (1) The incremental values for the settings are generally linear. For the exact values for each setting, use the latest version of the Quartus II software.
- (2) The minimum and maximum offset timing numbers are in reference to setting **0** as available in the Quartus II software.

## I/O Timing

Use the following methods to determine I/O timing:

- the Excel-based I/O Timing
- the Quartus II timing analyzer

The Excel-based I/O timing provides pin timing performance for each device density and speed grade. The data is typically used prior to designing the FPGA to get a timing budget estimation as part of the link timing analysis. The Quartus II timing analyzer provides a more accurate and precise I/O timing data based on the specifics of the design after place-and-route is complete.



The Excel-based I/O Timing spreadsheet is downloadable from Cyclone IV Devices Literature website.

## Glossary

Table 1-46 lists the glossary for this chapter.

**Table 1-46. Glossary (Part 1 of 5)**

| Letter | Term                                                   | Definitions                                                                                                                                                                                                                                                               |
|--------|--------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| A      | —                                                      | —                                                                                                                                                                                                                                                                         |
| B      | —                                                      | —                                                                                                                                                                                                                                                                         |
| C      | —                                                      | —                                                                                                                                                                                                                                                                         |
| D      | —                                                      | —                                                                                                                                                                                                                                                                         |
| E      | —                                                      | —                                                                                                                                                                                                                                                                         |
| F      | $f_{\text{HSCLK}}$                                     | High-speed I/O block: High-speed receiver/transmitter input and output clock frequency.                                                                                                                                                                                   |
| G      | GCLK                                                   | Input pin directly to Global Clock network.                                                                                                                                                                                                                               |
|        | GCLK PLL                                               | Input pin to Global Clock network through the PLL.                                                                                                                                                                                                                        |
| H      | HSIODR                                                 | High-speed I/O block: Maximum/minimum LVDS data transfer rate ( $\text{HSIODR} = 1/\text{TUI}$ ).                                                                                                                                                                         |
| I      | Input Waveforms for the SSTL Differential I/O Standard | <p>The diagram shows a differential signal waveform. The signal transitions between <math>V_{\text{IH}}</math> and <math>V_{\text{IL}}</math> levels, with a swing of <math>V_{\text{SWING}}</math>. A reference level <math>V_{\text{REF}}</math> is also indicated.</p> |

Table 1-46. Glossary (Part 2 of 5)

| Letter   | Term          | Definitions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|----------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>J</b> | JTAG Waveform | <p>The diagram illustrates the JTAG waveform with the following timing parameters:</p> <ul style="list-style-type: none"> <li><math>t_{JCP}</math>: JTAG Capture Period</li> <li><math>t_{JCH}</math>: JTAG Capture Hold</li> <li><math>t_{JCL}</math>: JTAG Capture Low</li> <li><math>t_{JPSU\_TDI}</math>: JTAG Setup Time for TDI</li> <li><math>t_{JPSU\_TMS}</math>: JTAG Setup Time for TMS</li> <li><math>t_{JPH}</math>: JTAG Period High</li> <li><math>t_{JPZX}</math>: JTAG Period Zero</li> <li><math>t_{JPCO}</math>: JTAG Period Count Out</li> <li><math>t_{JSSU}</math>: JTAG Setup Time for Signal to be Captured</li> <li><math>t_{JSH}</math>: JTAG Setup Hold</li> <li><math>t_{JSZX}</math>: JTAG Setup Zero</li> <li><math>t_{JSCO}</math>: JTAG Setup Count Out</li> <li><math>t_{JSXZ}</math>: JTAG Setup Zero</li> </ul>                                                                                                                                                                                                                                                                                                                                                           |
| <b>K</b> | —             | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>L</b> | —             | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>M</b> | —             | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>N</b> | —             | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>O</b> | —             | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>P</b> | PLL Block     | <p>The following highlights the PLL specification parameters:</p> <p>The diagram shows the PLL block architecture with the following components and signals:</p> <ul style="list-style-type: none"> <li><b>CLK</b>: Input clock signal.</li> <li><b>Core Clock</b>: Input clock signal.</li> <li><b>Switchover</b>: A block that selects between CLK and Core Clock.</li> <li><b><math>f_{IN}</math></b>: Input frequency to the PFD.</li> <li><b>N</b>: Divider block.</li> <li><b><math>f_{INPFD}</math></b>: Input frequency to the PFD.</li> <li><b>PFD</b>: Phase-Frequency Divider.</li> <li><b>CP</b>: Charge Pump.</li> <li><b>LF</b>: Loop Filter.</li> <li><b>VCO</b>: Voltage-Controlled Oscillator.</li> <li><b><math>f_{VCO}</math></b>: Output frequency of the VCO.</li> <li><b>Phase tap</b>: A block that provides a phase tap to the VCO.</li> <li><b>M</b>: Divider block.</li> <li><b>Counters C0..C4</b>: Counters that provide a digital output.</li> <li><b><math>f_{OUT\_EXT}</math></b>: Output frequency to the CLKOUT Pins.</li> <li><b>GCLK</b>: Global Clock output.</li> </ul> <p><b>Key</b></p> <ul style="list-style-type: none"> <li>Reconfigurable in User Mode</li> </ul> |
| <b>Q</b> | —             | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

Table 1-46. Glossary (Part 3 of 5)



| Letter | Term                                         | Definitions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| R      | $R_L$                                        | Receiver differential input discrete resistor (external to Cyclone IV devices).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|        | Receiver Input Waveform                      | <p>Receiver input waveform for LVDS and LVPECL differential standards:</p>  <p>Single-Ended Waveform</p> <p>Differential Waveform (Mathematical Function of Positive &amp; Negative Channel)</p>                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|        | Receiver input skew margin (RSKM)            | High-speed I/O block: The total margin left after accounting for the sampling window and TCCS. $RSKM = (TUI - SW - TCCS) / 2$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| S      | Single-ended voltage-referenced I/O Standard |  <p>The JEDEC standard for SSTI and HSTL I/O standards defines both the AC and DC input signal values. The AC values indicate the voltage levels at which the receiver must meet its timing specifications. The DC values indicate the voltage levels at which the final logic state of the receiver is unambiguously defined. After the receiver input crosses the AC value, the receiver changes to the new logic state. The new logic state is then maintained as long as the input stays beyond the DC threshold. This approach is intended to provide predictable receiver timing in the presence of input waveform <i>ringing</i>.</p> |
|        | SW (Sampling Window)                         | High-speed I/O block: The period of time during which the data must be valid to capture it correctly. The setup and hold times determine the ideal strobe position in the sampling window.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |



Table 1-46. Glossary (Part 4 of 5)

| Letter | Term                           | Definitions                                                                                                                                                                                 |
|--------|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| T      | $t_C$                          | High-speed receiver and transmitter input and output clock period.                                                                                                                          |
|        | Channel-to-channel-skew (TCCS) | High-speed I/O block: The timing difference between the fastest and slowest output edges, including $t_{CO}$ variation and clock skew. The clock is included in the TCCS measurement.       |
|        | $t_{cin}$                      | Delay from the clock pad to the I/O input register.                                                                                                                                         |
|        | $t_{CO}$                       | Delay from the clock pad to the I/O output.                                                                                                                                                 |
|        | $t_{cout}$                     | Delay from the clock pad to the I/O output register.                                                                                                                                        |
|        | $t_{DUTY}$                     | High-speed I/O block: Duty cycle on high-speed transmitter output clock.                                                                                                                    |
|        | $t_{FALL}$                     | Signal high-to-low transition time (80–20%).                                                                                                                                                |
|        | $t_H$                          | Input register hold time.                                                                                                                                                                   |
|        | Timing Unit Interval (TUI)     | High-speed I/O block: The timing budget allowed for skew, propagation delays, and data sampling window. (TUI = $1/(\text{Receiver Input Clock Frequency Multiplication Factor}) = t_C/w$ ). |
|        | $t_{INJITTER}$                 | Period jitter on the PLL clock input.                                                                                                                                                       |
|        | $t_{OUTJITTER\_DEDCLK}$        | Period jitter on the dedicated clock output driven by a PLL.                                                                                                                                |
|        | $t_{OUTJITTER\_IO}$            | Period jitter on the general purpose I/O driven by a PLL.                                                                                                                                   |
|        | $t_{pllcin}$                   | Delay from the PLL inclk pad to the I/O input register.                                                                                                                                     |
|        | $t_{pllcout}$                  | Delay from the PLL inclk pad to the I/O output register.                                                                                                                                    |
|        | Transmitter Output Waveform    | <p>Transmitter output waveforms for the LVDS, mini-LVDS, PPDS and RSDS Differential I/O Standards:</p>                                                                                      |
|        | $t_{RISE}$                     | Signal low-to-high transition time (20–80%).                                                                                                                                                |
|        | $t_{SU}$                       | Input register setup time.                                                                                                                                                                  |
| U      | —                              | —                                                                                                                                                                                           |

Table 1-46. Glossary (Part 5 of 5)

| Letter   | Term            | Definitions                                                                                                                                                                                    |
|----------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>V</b> | $V_{CM(DC)}$    | DC common mode input voltage.                                                                                                                                                                  |
|          | $V_{DIF(AC)}$   | AC differential input voltage: The minimum AC input differential voltage required for switching.                                                                                               |
|          | $V_{DIF(DC)}$   | DC differential input voltage: The minimum DC input differential voltage required for switching.                                                                                               |
|          | $V_{ICM}$       | Input common mode voltage: The common mode of the differential signal at the receiver.                                                                                                         |
|          | $V_{ID}$        | Input differential voltage swing: The difference in voltage between the positive and complementary conductors of a differential transmission at the receiver.                                  |
|          | $V_{IH}$        | Voltage input high: The minimum positive voltage applied to the input that is accepted by the device as a logic high.                                                                          |
|          | $V_{IH(AC)}$    | High-level AC input voltage.                                                                                                                                                                   |
|          | $V_{IH(DC)}$    | High-level DC input voltage.                                                                                                                                                                   |
|          | $V_{IL}$        | Voltage input low: The maximum positive voltage applied to the input that is accepted by the device as a logic low.                                                                            |
|          | $V_{IL(AC)}$    | Low-level AC input voltage.                                                                                                                                                                    |
|          | $V_{IL(DC)}$    | Low-level DC input voltage.                                                                                                                                                                    |
|          | $V_{IN}$        | DC input voltage.                                                                                                                                                                              |
|          | $V_{OCM}$       | Output common mode voltage: The common mode of the differential signal at the transmitter.                                                                                                     |
|          | $V_{OD}$        | Output differential voltage swing: The difference in voltage between the positive and complementary conductors of a differential transmission at the transmitter. $V_{OD} = V_{OH} - V_{OL}$ . |
|          | $V_{OH}$        | Voltage output high: The maximum positive voltage from an output that the device considers is accepted as the minimum positive high level.                                                     |
|          | $V_{OL}$        | Voltage output low: The maximum positive voltage from an output that the device considers is accepted as the maximum positive low level.                                                       |
|          | $V_{OS}$        | Output offset voltage: $V_{OS} = (V_{OH} + V_{OL}) / 2$ .                                                                                                                                      |
|          | $V_{OX(AC)}$    | AC differential output cross point voltage: the voltage at which the differential output signals must cross.                                                                                   |
|          | $V_{REF}$       | Reference voltage for the SSTL and HSTL I/O standards.                                                                                                                                         |
|          | $V_{REF(AC)}$   | AC input reference voltage for the SSTL and HSTL I/O standards. $V_{REF(AC)} = V_{REF(DC)} + \text{noise}$ . The peak-to-peak AC noise on $V_{REF}$ must not exceed 2% of $V_{REF(DC)}$ .      |
|          | $V_{REF(DC)}$   | DC input reference voltage for the SSTL and HSTL I/O standards.                                                                                                                                |
|          | $V_{SWING(AC)}$ | AC differential input voltage: AC input differential voltage required for switching. For the SSTL differential I/O standard, refer to Input Waveforms.                                         |
|          | $V_{SWING(DC)}$ | DC differential input voltage: DC input differential voltage required for switching. For the SSTL differential I/O standard, refer to Input Waveforms.                                         |
|          | $V_{TT}$        | Termination voltage for the SSTL and HSTL I/O standards.                                                                                                                                       |
|          | $V_X(AC)$       | AC differential input cross point voltage: The voltage at which the differential input signals must cross.                                                                                     |
| <b>W</b> | —               | —                                                                                                                                                                                              |
| <b>X</b> | —               | —                                                                                                                                                                                              |
| <b>Y</b> | —               | —                                                                                                                                                                                              |
| <b>Z</b> | —               | —                                                                                                                                                                                              |

## Document Revision History

Table 1–47 lists the revision history for this chapter.

**Table 1–47. Document Revision History**

| Date          | Version | Changes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| March 2016    | 2.0     | Updated note (5) in Table 1–21 to remove support for the N148 package.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| October 2014  | 1.9     | Updated maximum value for $V_{CCD\_PLL}$ in Table 1–1.<br>Removed extended temperature note in Table 1–3.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| December 2013 | 1.8     | Updated Table 1–21 by adding Note (15).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| May 2013      | 1.7     | Updated Table 1–15 by adding Note (4).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| October 2012  | 1.6     | <ul style="list-style-type: none"> <li>■ Updated the maximum value for <math>V_I</math>, <math>V_{CCD\_PLL}</math>, <math>V_{CCIO}</math>, <math>V_{CC\_CLKIN}</math>, <math>V_{CCH\_GXB}</math>, and <math>V_{CCA\_GXB}</math> in Table 1–1.</li> <li>■ Updated Table 1–11 and Table 1–22.</li> <li>■ Updated Table 1–21 to include peak-to-peak differential input voltage for the Cyclone IV GX transceiver input reference clock.</li> <li>■ Updated Table 1–29 to include the typical <math>DCLK</math> value.</li> <li>■ Updated the minimum <math>f_{HCLK}</math> value in Table 1–31, Table 1–32, Table 1–33, Table 1–34, and Table 1–35.</li> </ul> |
| November 2011 | 1.5     | <ul style="list-style-type: none"> <li>■ Updated “Maximum Allowed Overshoot or Undershoot Voltage”, “Operating Conditions”, and “PLL Specifications” sections.</li> <li>■ Updated Table 1–2, Table 1–3, Table 1–4, Table 1–5, Table 1–8, Table 1–9, Table 1–15, Table 1–18, Table 1–19, and Table 1–21.</li> <li>■ Updated Figure 1–1.</li> </ul>                                                                                                                                                                                                                                                                                                            |
| December 2010 | 1.4     | <ul style="list-style-type: none"> <li>■ Updated for the Quartus II software version 10.1 release.</li> <li>■ Updated Table 1–21 and Table 1–25.</li> <li>■ Minor text edits.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| July 2010     | 1.3     | <p>Updated for the Quartus II software version 10.0 release:</p> <ul style="list-style-type: none"> <li>■ Updated Table 1–3, Table 1–4, Table 1–21, Table 1–25, Table 1–28, Table 1–30, Table 1–40, Table 1–41, Table 1–42, Table 1–43, Table 1–44, and Table 1–45.</li> <li>■ Updated Figure 1–2 and Figure 1–3.</li> <li>■ Removed SW Requirement and TCCS for Cyclone IV Devices tables.</li> <li>■ Minor text edits.</li> </ul>                                                                                                                                                                                                                          |
| March 2010    | 1.2     | <p>Updated to include automotive devices:</p> <ul style="list-style-type: none"> <li>■ Updated the “Operating Conditions” and “PLL Specifications” sections.</li> <li>■ Updated Table 1–1, Table 1–8, Table 1–9, Table 1–21, Table 1–26, Table 1–27, Table 1–31, Table 1–32, Table 1–33, Table 1–34, Table 1–35, Table 1–36, Table 1–37, Table 1–38, Table 1–40, Table 1–42, and Table 1–43.</li> <li>■ Added Table 1–5 to include ESD for Cyclone IV devices GPIOs and HSSI I/Os.</li> <li>■ Added Table 1–44 and Table 1–45 to include IOE programmable delay for Cyclone IV E 1.2 V core voltage devices.</li> <li>■ Minor text edits.</li> </ul>         |

**Table 1–47. Document Revision History**

| Date          | Version | Changes                                                                                                                                                                                                                                       |
|---------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| February 2010 | 1.1     | <ul style="list-style-type: none"><li>■ Updated Table 1–3 through Table 1–44 to include information for Cyclone IV E devices and Cyclone IV GX devices for Quartus II software version 9.1 SP1 release.</li><li>■ Minor text edits.</li></ul> |
| November 2009 | 1.0     | Initial release.                                                                                                                                                                                                                              |

