



Welcome to **E-XFL.COM**

Understanding Embedded - Microprocessors

Embedded microprocessors are specialized computing chips designed to perform specific tasks within an embedded system. Unlike general-purpose microprocessors found in personal computers, embedded microprocessors are tailored for dedicated functions within larger systems, offering optimized performance, efficiency, and reliability. These microprocessors are integral to the operation of countless electronic devices, providing the computational power necessary for controlling processes, handling data, and managing communications.

Applications of Embedded - Microprocessors

Embedded microprocessors are utilized across a broad spectrum of applications, making them indispensable in

| Details | | |
|---------------------------------|---|--|
| Product Status | Discontinued at Digi-Key | |
| Core Processor | Pentium G4400TE | |
| Number of Cores/Bus Width | 2 Core, 64-Bit | |
| Speed | 2.4GHz | |
| Co-Processors/DSP | - | |
| RAM Controllers | - | |
| Graphics Acceleration | Yes | |
| Display & Interface Controllers | - | |
| Ethernet | - | |
| SATA | - | |
| USB | - | |
| Voltage - I/O | - | |
| Operating Temperature | - | |
| Security Features | - | |
| Package / Case | 1151-LGA Module | |
| Supplier Device Package | 1151-LGA | |
| Purchase URL | https://www.e-xfl.com/product-detail/advantech/96mpps-2-4-3m11t | |

Email: info@E-XFL.COM

Address: Room A, 16/F, Full Win Commercial Centre, 573 Nathan Road, Mongkok, Hong Kong



96MPPS-2.4-3M11T

Intel® Pentium® Processor G4400TE (3M Cache, 2.40 GHz)



Features:

- Intel Pentium G4400TE Processor
- 2 Cores
- Processor Base Frequency 2.4GHz
- 3MB cache
- 14nm
- Thermal Design Power 35W
- HD Graphics 510
- Support DDR4-1866/2133, DDR3L-1333/19
 1.35V

Specifications

| Advantech PN | 96MPPS-2.4-3M11T |
|----------------------|------------------|
| Intel Ordering Code | CM8066201938702 |
| Intel Launch Date | Q4 / 2015 |
| Code Name | Skylake |
| SPEC Code | SR2LT |
| Processor Number | G4400TE |
| # of Cores | 2 |
| # of Threads | 2 |
| Cache | 3MB |
| Clock Speed | 2.4GHz |
| FSB (Front Side Bus) | N/A |
| Tech. in Nanometer | 14nm |
| Max Design Power | 35W |

| Direct Media Interface | 8 GT/s |
|--|--|
| Socket Type | FCLGA1151 |
| Max Memory Size | 64GB |
| Tcase | N/A |
| Memory Type | DDR4-1866/2133, DDR3L-1333/1600 @ 1.35V |
| | |
| Intel® Graphic Processor | HD Graphics 510 |
| Intel® Graphic Processor Graphic Base Frequency | HD Graphics 510 350MHz |
| | · |
| Graphic Base Frequency | 350MHz |
| Graphic Base Frequency 64-bits Support | 350MHz YES |
| Graphic Base Frequency 64-bits Support Package | 350MHz YES Tray |

Compatible Motherboard

| Model Number | Description | |
|---------------------|-------------|----------------------------|
| | | Learn more on PAPS Website |

AD\ANTECH Peripheral Allied Procurement Services - Global Sourcing Local Supports-

All product specification and compatible chipset are subject to change without notice.

Last updated: 12-Jan-2016

Rev. 1.0