



Welcome to E-XFL.COM

What is "Embedded - Microcontrollers"?

"Embedded - Microcontrollers" refer to small, integrated circuits designed to perform specific tasks within larger systems. These microcontrollers are essentially compact computers on a single chip, containing a processor core, memory, and programmable input/output peripherals. They are called "embedded" because they are embedded within electronic devices to control various functions, rather than serving as standalone computers. Microcontrollers are crucial in modern electronics, providing the intelligence and control needed for a wide range of applications.

Applications of "<u>Embedded -</u> <u>Microcontrollers</u>"

Details

Product Status	Active
Core Processor	ARM® Cortex®-M3
Core Size	32-Bit Single-Core
Speed	64MHz
Connectivity	I ² C, IrDA, Memory Card, SPI, SSC, UART/USART, USB
Peripherals	Brown-out Detect/Reset, DMA, I ² S, POR, PWM, WDT
Number of I/O	47
Program Memory Size	512KB (512K x 8)
Program Memory Type	FLASH
EEPROM Size	-
RAM Size	64K x 8
Voltage - Supply (Vcc/Vdd)	1.62V ~ 3.6V
Data Converters	A/D 10x10/12b; D/A 2x12b
Oscillator Type	Internal
Operating Temperature	-40°C ~ 85°C (TA)
Mounting Type	Surface Mount
Package / Case	64-LQFP
Supplier Device Package	64-LQFP (10x10)
Purchase URL	https://www.e-xfl.com/product-detail/microchip-technology/atsam3sd8ba-aur

Email: info@E-XFL.COM

Address: Room A, 16/F, Full Win Commercial Centre, 573 Nathan Road, Mongkok, Hong Kong





Atmel SMART SAM3S Series MCU ARM Cortex-M3 Flash Microcontroller Delivers High Integration and Low Power

Benefits

- ARM[®] Cortex[®]-M3 technology
- Pin-to-pin compatible with best-selling Atmel[®] | SMART SAM7S series MCU
- Highly-integrated peripheral set, including Full Speed USB device
- Native Atmel QTouch[®] capacitive touch support
- Low power consumption
- Simplified PCB design and low system cost
- Parallel input/output (I/O) signal capture
- Safety features

Key Features

- 1.62V to 3.6V supply
- ARM Cortex-M3 rev 2.0 processor running at up to 64MHz
- Memory protection unit (MPU)
- Optional dual-bank Flash
- Native 4-layer AHB bus matrix, 21 DMA channels
- Embedded regulator, power-on reset, brown-out detection and multiple clock sources, including 32kHz oscillator and factory-trimmed RC
- High-speed peripherals, including USB2.0 FS device, HS SD/SDIO/MMC, USART, SPI
- Up to 16-channel 12-bit 1Msps ADC with PGA stage and differential inputs, 2-channel 12-bit 1Msps DAC, analog comparator
- Powerful and flexible 16-bit timers with quadrature decoder and gray counter. Powerful PWM unit, calendar RTC, watchdog timer
- Power consumption 2.3mW@1MHz, 1.3mW@500kHz, backup mode down to 1.8µA
- ECC on Flash, independent watchdog, dual-bank Flash, clock failure detection. On-the-fly external memory scrambling.
- 8-bit parallel data capture on PIO controller
- Up to 79 I/O lines with integrated serial resistors (on-die termination)
- 48-, 64- and 100-pin packages



Application Areas

- Consumer goods and toys
- Industrial control
- Metering
- Medical
- Test and measurement
- 802.15.4 wireless networking
- PC, cell phone, gaming peripherals



Atmel

Atmel | SMART SAM3S Series MCU ARM Cortex-M3 Flash Microcontroller Delivers

RM Cortex-M3 Flash Microcontroller Delivers High Integration and Low Power

Evaluation Kit and Ecosystem

- · Full-featured evaluation board and software library
- Atmel BitCloud[®] (ZigBee PRO) stack available
- · QTouch library support for buttons, sliders and wheels
- Worldwide support ecosystem of industry-leading suppliers of development tools, real-time operating systems and middleware products
- Kit Ordering Code ATSAM3S-EK2



Device Ordering Information

Ordering Code	Flash	Package
ATSAM3S8CA-AU	512kB	LQFP100
ATSAM3S8CA-CU	512kB	BGA100
ATSAM3S8BA-AU	512kB	LQFP64
ATSAM3S8BA-MU	512kB	QFN64
ATSAM3SD8CA-AU	512kB*	LQFP100
ATSAM3SD8CA-CU	512kB*	BGA100
ATSAM3SD8BA-AU	512kB*	LQFP64
ATSAM3SD8BA-MU	512kB*	QFN64
ATSAM3S4CA-AU	256kB	LQFP100
ATSAM3S4CA-CU	256kB	BGA100
ATSAM3S4BA-AU	256kB	LQFP64
ATSAM3S4BA-MU	256kB	QFN64
ATSAM3S4AA-AU	256kB	LQFP48

Ordering Code	Flash	Package
ATSAM3S4AA-MU	256kB	QFN48
ATSAM3S2CA-AU	128kB	LQFP100
ATSAM3S2CA-CU	128kB	BGA100
ATSAM3S2BA-AU	128kB	LQFP64
ATSAM3S2BA-MU	128kB	QFN64
ATSAM3S2AA-AU	128kB	LQFP48
ATSAM3S2AA-MU	128kB	QFN48
ATSAM3S1CA-AU	64kB	LQFP100
ATSAM3S1CA-CU	64kB	BGA100
ATSAM3S1BA-AU	64kB	LQFP64
ATSAM3S1BA-MU	64kB	QFN64
ATSAM3S1AA-AU	64kB	LQFP48
ATSAM3S1AA-MU	64kB	QFN48

* 2x256kB dual-bank Flash

f 🛗 in 🐼 궁

F: (+1)(408) 436, 4200



Atmel Corporation

Enabling Unlimited Possibilities®

1600 Technology Drive, San Jose, CA 95110 USA

T: (+1)(408) 441.0311

www.atmel.com

© 2015 Atmel Corporation. / Rev.: Atmel-11075F-SAM3S_E_US_122015

Atmel,[®] Atmel logo and combinations thereof, Enabling Unlimited Possibilities,[®] and others are registered trademarks or trademarks of Atmel Corporation in U.S. and other countries. ARM,[®] ARM Connected[®] logo and others are the registered trademarks or trademarks of ARM Ltd. Other terms and product names may be trademarks of others.

Disclaimer: The information in this document is provided in connection with Atmel products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of Atmel products. EXCEPT AS SET FORTH IN THE ATMEL TERMS AND CONDITIONS OF SALES LOCATED ON THE ATMEL WEBSITE, ATMEL ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL ATMEL BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAVIAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS AND PROFITS, BUSINESS INTERRUPTION, OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF ATMEL HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES Armel makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and products are not intended, authorized, or warranted for use as components in applications intended to support or sustain life.