Welcome to E-XFL.COM

What is "Embedded - Microcontrollers"?

"Embedded - Microcontrollers" refer to small, integrated circuits designed to perform specific tasks within larger systems. These microcontrollers are essentially compact computers on a single chip, containing a processor core, memory, and programmable input/output peripherals. They are called "embedded" because they are embedded within electronic devices to control various functions, rather than serving as standalone computers. Microcontrollers are crucial in modern electronics, providing the intelligence and control needed for a wide range of applications.

Applications of "Embedded - Microcontrollers"

Details	
Product Status	Obsolete
Core Processor	Z8
Core Size	8-Bit
Speed	8MHz
Connectivity	-
Peripherals	HLVD, POR, WDT
Number of I/O	16
Program Memory Size	32KB (32K x 8)
Program Memory Type	OTP
EEPROM Size	-
RAM Size	237 x 8
Voltage - Supply (Vcc/Vdd)	2V ~ 5.5V
Data Converters	-
Oscillator Type	Internal
Operating Temperature	0°C ~ 70°C (TA)
Mounting Type	Surface Mount
Package / Case	20-SSOP (0.209", 5.30mm Width)
Supplier Device Package	-
Purchase URL	https://www.e-xfl.com/product-detail/zilog/zgp323hsh2032c

Table of Contents

Revision History iii
Development Features 1
General Description 2
Pin Description 4
Absolute Maximum Ratings 10
Standard Test Conditions 10
DC Characteristics 11
AC Characteristics 16
Pin Functions 18
XTAL1 Crystal 1 (Time-Based Input) 18
XTAL2 Crystal 2 (Time-Based Output) 18
Port 0 (P07–P00) 18
Port 1 (P17–P10) 19
Port 2 (P27–P20) 20
Port 3 (P37–P30) 21
RESET (Input, Active Low) 25
Functional Description 25
Program Memory 25
RAM 25
Expanded Register File 26
Register File 30
Stack 31
Timers 32
Counter/Timer Functional Blocks 40
Expanded Register File Control Registers (0D) 66
Expanded Register File Control Registers (0F) 71
Standard Control Registers 75
Package Information 81
Ordering Information 90

Figure 34. SCLK Circuit 58
Figure 35. Stop Mode Recovery Source 59
Figure 36. Stop Mode Recovery Register 2 ((0F)DH:D2–D4, D6 Write Only) . . 61
Figure 37. Watch-Dog Timer Mode Register (Write Only) 62
Figure 38. Resets and WDT 63
Figure 39. TC8 Control Register ((0D)O0H: Read/Write Except Where Noted) 66
Figure 40. T8 and T16 Common Control Functions ((0D)01H: Read/Write) . . . 67
Figure 41. T16 Control Register ((0D) 2H: Read/Write Except Where Noted) . 69
Figure 42. T8/T16 Control Register (0D)03H: Read/Write (Except Where Noted) 70
Figure 43. Voltage Detection Register 71
Figure 44. Port Configuration Register (PCON)(0F)00H: Write Only) 72
Figure 45. Stop Mode Recovery Register ((0F)0BH: D6–D0=Write Only, D7=Read Only) 73
Figure 46. Stop Mode Recovery Register 2 ((0F)0DH:D2–D4, D6 Write Only) 74
Figure 47. Watch-Dog Timer Register ((0F) 0FH: Write Only). 75
Figure 48. Port 2 Mode Register (F6H: Write Only). 75
Figure 49. Port 3 Mode Register (F7H: Write Only) 76
Figure 50. Port 0 and 1 Mode Register (F8H: Write Only) 77
Figure 51. Interrupt Priority Register (F9H: Write Only) 78
Figure 52. Interrupt Request Register (FAH: Read/Write) 79
Figure 53. Interrupt Mask Register (FBH: Read/Write) 79
Figure 54. Flag Register (FCH: Read/Write) 80
Figure 55. Register Pointer (FDH: Read/Write) 80
Figure 56. Stack Pointer High (FEH: Read/Write) 81
Figure 57. Stack Pointer Low (FFH: Read/Write) 81
Figure 58. 20-Pin CDIP Package 82
Figure 59. 20-Pin PDIP Package Diagram 82
Figure 60. 20-Pin SOIC Package Diagram 83
Figure 61. 20-Pin SSOP Package Diagram 84
Figure 62. 28-Pin SOIC Package Diagram 85
Figure 63. 28-Pin CDIP Package Diagram 86
Figure 64. 28-Pin PDIP Package Diagram 86
Figure 65. 28-Pin SSOP Package Diagram. 87
Figure 66. 40-Pin PDIP Package Diagram 87
Figure 67. 40-Pin CDIP Package Diagram 88