

Welcome to E-XFL.COM

Understanding Embedded - Microprocessors

Embedded microprocessors are specialized computing chips designed to perform specific tasks within an embedded system. Unlike general-purpose microprocessors found in personal computers, embedded microprocessors are tailored for dedicated functions within larger systems, offering optimized performance, efficiency, and reliability. These microprocessors are integral to the operation of countless electronic devices, providing the computational power necessary for controlling processes, handling data, and managing communications.

Applications of **Embedded - Microprocessors**

Embedded microprocessors are utilized across a broad spectrum of applications, making them indispensable in

Details

Product Status	Active
Core Processor	PowerPC e500
Number of Cores/Bus Width	1 Core, 32-Bit
Speed	800MHz
Co-Processors/DSP	Signal Processing; SC3850, Security; SEC 4.4
RAM Controllers	DDR3, DDR3L
Graphics Acceleration	No
Display & Interface Controllers	-
Ethernet	10/100/1000Mbps (2)
SATA	-
USB	USB 2.0 (1)
Voltage - I/O	1.8V, 2.5V, 3.3V
Operating Temperature	-40°C ~ 105°C (TA)
Security Features	Boot Security, Cryptography, Random Number Generator
Package / Case	520-FBGA, FCBGA
Supplier Device Package	520-FCBGA (21x21)
Purchase URL	https://www.e-xfl.com/pro/item?MUrl=&PartUrl=bsc9131nje1hhhb

Email: info@E-XFL.COM

Address: Room A, 16/F, Full Win Commercial Centre, 573 Nathan Road, Mongkok, Hong Kong



Target Applications

Femtocell: Home or small office cellular base stations supporting the following standards:

- LTE-FDD/TDD
- WCDMA (HSPA+)
- CDMA2K
- TD-SCDMA

QorlQ Qonverge Platform

QorlQ Qonverge BSC9131 for Femtocell Base Station Solutions

A new dimension in wireless processing

Overview

The QorlQ Qonverge BSC9131 processor is a highly integrated device that targets evolving femto and enterprise femto applications. The BSC9131 combines Power Architecture® e500 and StarCore SC3850 core technologies with MAPLE-B2F baseband acceleration processing, addressing the need for a high-performance, cost-effective, integrated solution that handles all the digital baseband processing required for femtocells.

The programmable BSC9131 device, targeted at LTE/FDD/TDD, WCDMA (HSPA+) and CDMA2K, supports multiple air interface standards and can support two concurrent standards.

QorlQ Qonverge BSC9131 Processor







QorlQ Qonverge Features

The BSC9131 is a highly integrated device combining Power, StarCore and MAPLE architectures. The device includes the following features:

Core	 Power Architecture[®] subsystem including one e500 processor and 256 KB shared L2 cache
DSP	StarCore SC3850 DSP subsystem including 512 KB private L2 cache
Baseband Acceleration	 MAPLE-B2F multi-accelerator platform engine supports functions that enable LTE-FDD/TDD, WCDMA (HSPA+) and CDMA2K wireless standards
Memory	 DDR3 memory interface with 32-bit data width (40 bits including ECC), up to 800 MHz data rate
	Integrated flash controller for NOR, NAND and FPGA support
Security	Dedicated security engine featuring trusted boot
RF Interface	Antenna interface controller supporting three industry standard JESD207/three custom ADI RF interfaces (two dual port and one single port)
	Two pulse width modulators (PWM) for control of external components
	Three MAXIMs MaxPhy serial interfaces
Connectivity	 Two triple-speed Gigabit-Ethernet controllers featuring network acceleration including IEEE[®] Std 1588v2[™] hardware support
	USB 2.0 host and device controller
	DMA controller with four bidirectional channels that serves both Power Architecture cores and DSP domains
	 UART, SPI, eSDHC, USIM and I²C controllers
	GPIO, 16 32-bit timers

Freescale will provide commercial L1 and transport software. L2, L3 will be provided through our partner stack vendors:

- LTE-FDD/TDD and WCDMA (HSPA+) L1 software–licensed by Freescale
- L2/L3 software for LTE-FDD/TDD and WCDMA (HSPA+)-via partners
- Development tools and operating system software through Freescale and its ecosystem partners







BSC9131 Reference Design Board

For more information about the QorlQ Qonverge BSC913x family, visit freescale.com/QorlQQonverge

Freescale, the Freescale logo, QorlQ and StarCore are trademarks of Freescale Semiconductor, Inc., Reg. U.S. Pat. & Tm. Off. QorlQ Qonverge is a trademark of Freescale Semiconductor, Inc. All other product or service names are the property of their respective owners. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org. © 2012 Freescale Semiconductor, Inc.

Freescale

Document Number: QORIQPSC9131FS REV 2