



Welcome to [E-XFL.COM](#)

What is "[Embedded - Microcontrollers](#)"?

"[Embedded - Microcontrollers](#)" refer to small, integrated circuits designed to perform specific tasks within larger systems. These microcontrollers are essentially compact computers on a single chip, containing a processor core, memory, and programmable input/output peripherals. They are called "embedded" because they are embedded within electronic devices to control various functions, rather than serving as standalone computers. Microcontrollers are crucial in modern electronics, providing the intelligence and control needed for a wide range of applications.

Applications of "[Embedded - Microcontrollers](#)"

Details

Product Status	Obsolete
Core Processor	ST7
Core Size	8-Bit
Speed	16MHz
Connectivity	I ² C, SCI, SPI
Peripherals	LVD, POR, PWM, WDT
Number of I/O	22
Program Memory Size	8KB (8K x 8)
Program Memory Type	FLASH
EEPROM Size	-
RAM Size	256 x 8
Voltage - Supply (Vcc/Vdd)	2.7V ~ 5.5V
Data Converters	A/D 6x10b
Oscillator Type	Internal
Operating Temperature	-40°C ~ 85°C (TA)
Mounting Type	Surface Mount
Package / Case	36-LFBGA
Supplier Device Package	-
Purchase URL	https://www.e-xfl.com/product-detail/stmicroelectronics/st72f264g2h6

Table of Contents

1 INTRODUCTION	5
2 PIN DESCRIPTION	6
3 REGISTER & MEMORY MAP	10
4 FLASH PROGRAM MEMORY	14
4.1 INTRODUCTION	14
4.2 MAIN FEATURES	14
4.3 PROGRAMMING MODES	14
4.4 ICC INTERFACE	15
4.5 MEMORY PROTECTION	16
4.6 RELATED DOCUMENTATION	16
4.7 REGISTER DESCRIPTION	16
5 CENTRAL PROCESSING UNIT	17
5.1 INTRODUCTION	17
5.2 MAIN FEATURES	17
5.3 CPU REGISTERS	17
6 SUPPLY, RESET AND CLOCK MANAGEMENT	20
6.1 PHASE LOCKED LOOP	20
6.2 MULTI-OSCILLATOR (MO)	21
6.3 RESET SEQUENCE MANAGER (RSM)	22
6.4 SYSTEM INTEGRITY MANAGEMENT (SI)	24
7 INTERRUPTS	28
7.1 INTRODUCTION	28
7.2 MASKING AND PROCESSING FLOW	28
7.3 INTERRUPTS AND LOW POWER MODES	30
7.4 CONCURRENT & NESTED MANAGEMENT	30
7.5 INTERRUPT REGISTER DESCRIPTION	31
8 POWER SAVING MODES	33
8.1 INTRODUCTION	33
8.2 SLOW MODE	33
8.3 WAIT MODE	34
8.4 ACTIVE-HALT AND HALT MODES	35
8.5 HALT MODE	36
9 I/O PORTS	38
9.1 INTRODUCTION	38
9.2 FUNCTIONAL DESCRIPTION	38
9.3 I/O PORT IMPLEMENTATION	41
9.4 UNUSED I/O PINS	41
9.5 LOW POWER MODES	41
9.6 INTERRUPTS	41
9.7 DEVICE-SPECIFIC I/O PORT CONFIGURATION	42
9.8 I/O PORT REGISTER DESCRIPTION	43
10 MISCELLANEOUS REGISTERS	45

Table of Contents

10.1 I/O PORT INTERRUPT SENSITIVITY	45
10.2 I/O PORT ALTERNATE FUNCTIONS	45
10.3 MISCELLANEOUS REGISTER DESCRIPTION	46
11 ON-CHIP PERIPHERALS	48
11.1 WATCHDOG TIMER (WDG)	48
11.2 MAIN CLOCK CONTROLLER WITH REAL TIME CLOCK (MCC/RTC)	53
11.3 16-BIT TIMER	55
11.4 SERIAL PERIPHERAL INTERFACE (SPI)	75
11.5 SERIAL COMMUNICATIONS INTERFACE (SCI)	87
11.6 I2C BUS INTERFACE (I2C)	103
11.7 10-BIT A/D CONVERTER (ADC)	116
12 INSTRUCTION SET	120
12.1 CPU ADDRESSING MODES	120
12.2 INSTRUCTION GROUPS	123
13 ELECTRICAL CHARACTERISTICS	126
13.1 PARAMETER CONDITIONS	126
13.2 ABSOLUTE MAXIMUM RATINGS	127
13.3 OPERATING CONDITIONS	128
13.4 SUPPLY CURRENT CHARACTERISTICS	131
13.5 CLOCK AND TIMING CHARACTERISTICS	135
13.6 MEMORY CHARACTERISTICS	140
13.7 EMC CHARACTERISTICS	141
13.8 I/O PORT PIN CHARACTERISTICS	144
13.9 CONTROL PIN CHARACTERISTICS	150
13.10 TIMER PERIPHERAL CHARACTERISTICS	152
13.11 COMMUNICATION INTERFACE CHARACTERISTICS	153
13.12 10-BIT ADC CHARACTERISTICS	157
14 PACKAGE CHARACTERISTICS	159
14.1 PACKAGE MECHANICAL DATA	159
14.2 THERMAL CHARACTERISTICS	160
14.3 LEAD-FREE PACKAGE INFORMATION	161
15 DEVICE CONFIGURATION AND ORDERING INFORMATION	162
15.1 OPTION BYTES	162
15.2 DEVICE ORDERING INFORMATION AND TRANSFER OF CUSTOMER CODE	164
15.3 DEVELOPMENT TOOLS	166
16 KNOWN LIMITATIONS	168
16.1 ALL FLASH AND ROM DEVICES	168
16.2 FLASH DEVICES ONLY	168
17 REVISION HISTORY	171

