

Welcome to E-XFL.COM

What is "Embedded - Microcontrollers"?

"Embedded - Microcontrollers" refer to small, integrated circuits designed to perform specific tasks within larger systems. These microcontrollers are essentially compact computers on a single chip, containing a processor core, memory, and programmable input/output peripherals. They are called "embedded" because they are embedded within electronic devices to control various functions, rather than serving as standalone computers. Microcontrollers are crucial in modern electronics, providing the intelligence and control needed for a wide range of applications.

Applications of "<u>Embedded -</u> <u>Microcontrollers</u>"

Details

E·XFI

Betails	
Product Status	Obsolete
Core Processor	8051
Core Size	8-Bit
Speed	40MHz
Connectivity	EBI/EMI, UART/USART
Peripherals	POR, WDT
Number of I/O	36
Program Memory Size	16KB (16K x 8)
Program Memory Type	FLASH
EEPROM Size	-
RAM Size	256 x 8
Voltage - Supply (Vcc/Vdd)	4.5V ~ 5.5V
Data Converters	-
Oscillator Type	Internal
Operating Temperature	0°C ~ 70°C (TA)
Mounting Type	Surface Mount
Package / Case	44-BQFP
Supplier Device Package	-
Purchase URL	https://www.e-xfl.com/product-detail/nuvoton-technology-corporation-america/w78e054c40fl

Email: info@E-XFL.COM

Address: Room A, 16/F, Full Win Commercial Centre, 573 Nathan Road, Mongkok, Hong Kong

		winbond see	
	8.1	Program Fetch Cycle	. 18
	8.2	Data Read Cycle	. 18
	8.3	Data Write Cycle	. 19
	8.4	Port Access Cycle	. 19
9.	TYPIC	AL APPLICATION CIRCUITS	. 20
	9.1	Expanded External Program Memory and Crystal	. 20
	9.2	Expanded External Data Memory and Oscillator	. 21
10.	PACK	AGE DIMENSIONS	. 22
	10.1	40-pin DIP	. 22
	10.2	44-pin PLCC	. 22
	10.3	44-pin PQFP	. 23
11.	REVIS	ION HISTORY	. 24

1. GENERAL DESCRIPTION

The W78E054C is an 8-bit microcontroller which can accommodate a wider frequency range with low power consumption. The instruction set for the W78E054C is fully compatible with the standard 8051. The W78E054C contains an 16K bytes Flash EPROM; a 256 bytes RAM; four 8-bit bi-directional and bit-addressable I/O ports; an additional 4-bit I/O port P4; three 16-bit timer/counters; a hardware watchdog timer and a serial port. These peripherals are supported by eight sources two-level interrupt capability. To facilitate programming and verification, the Flash EPROM inside the W78E054C allows the program memory to be programmed and read electronically. Once the code is confirmed, the user can protect the code for security.

The W78E054C microcontroller has two power reduction modes, idle mode and power-down mode, both of which are software selectable. The idle mode turns off the processor clock but allows for continued peripheral operation. The power-down mode stops the crystal oscillator for minimum power consumption. The external clock can be stopped at any time and in any state without affecting the processor.

2. FEATURES

- Fully static design 8-bit CMOS microcontroller
- Wide supply voltage of 4.5V to 5.5V
- 256 bytes of on-chip scratchpad RAM
- 16 KB electrically erasable/programmable Flash EPROM
- 64 KB program memory address space
- 64 KB data memory address space
- Four 8-bit bi-directional ports
- One extra 4-bit bit-addressable I/O port, additional INT2 / INT3 (available on 44-pin PLCC/QFP package)
- Three 16-bit timer/counters
- One full duplex serial port(UART)
- Watchdog Timer
- Eight sources, two-level interrupt capability
- EMI reduction mode
- Built-in power management
- Code protection mechanism
- Packages:
 - Lead Free (RoHS) DIP 40: W78E054C40DL
 - Lead Free (RoHS) PLCC 44: W78E054C40PL
 - Lead Free (RoHS) PQFP 44: W78E054C40FL



3. PIN CONFIGURATIONS

40-Pin DIP P10 1 P11 2 P12 3 P13 4 P14 5 P15 6 P16 7 P17 8 RST 9 RXD,P31 11 INTT,P32 12 INTT,P33 13 TD,P34 14 T1,P35 15 WR,P35 16 RD,P37 17 XTAL2 18 XTAL1 19 VSS 20	40 $\forall VDD$ 39 PDD, ADD 38 $PD1, AD1$ 37 $PD2, AD2$ 36 $PD3, AD3$ 37 $PD5, AD4$ 34 $PD5, AD6$ 32 $PD7, AD7$ 31 EA 32 $PD7, AD7$ 31 EA 32 $PD7, AD7$ 33 $PD5, AD6$ 32 $PD7, AD7$ 31 EA 32 $PD2, A16$ 23 $P22, A15$ 24 $P25, A13$ 25 $P22, A11$ 24 $P22, A11$ 23 $P22, A11$ 24 $P22, A11$ 25 $P21, A9$ 21 $P2D, A8$
44-Pin PLCC	44-Pin QFP
/ / N A A A N D D D D 3 0 1 2 3 P	/ A A A A Y D D D D D Y D D D D D D Y D D D D D D D Y D

4. PIN DESCRIPTION

SYMBOL	DESCRIPTIONS
ĒĀ	EXTERNAL ACCESS ENABLE : This pin forces the processor to execute out of external ROM. It should be kept high to access internal ROM. The ROM address and
	data will not be presented on the bus if EA pin is high and the program counter is within on-chip ROM area.
PSEN	PROGRAM STORE ENABLE : PSEN enables the external ROM data onto the Port 0 address/ data bus during fetch and MOVC operations. When internal ROM access is performed, no PSEN strobe signal outputs from this pin.
ALE	ADDRESS LATCH ENABLE : ALE is used to enable the address latch that separates the address from the data on Port 0.
RST	RESET : A high on this pin for two machine cycles while the oscillator is running resets the device.
XTAL1	CRYSTAL1 : This is the crystal oscillator input. This pin may be driven by an external clock.
XTAL2	CRYSTAL2: This is the crystal oscillator output. It is the inversion of XTAL1.
Vss	GROUND: Ground potential
Vdd	POWER SUPPLY: Supply voltage for operation.
P0.0-P0.7	PORT 0 : Port 0 is a bi-directional I/O port which also provides a multiplexed low order address/data bus during accesses to external memory. The Port 0 is also an open-drain port and external pull-ups need to be connected while in programming.
	PORT 1 : Port 1 is a bi-directional I/O port with internal pull-ups. The bits have alternate functions which are described below:
P1.0–P1.7	T2(P1.0): Timer/Counter 2 external count input
	T2EX(P1.1): Timer/Counter 2 Reload/Capture control
P2.0-P2.7	PORT 2 : Port 2 is a bi-directional I/O port with internal pull-ups. This port also provides the upper address bits for accesses to external memory.
	PORT 3 : Port 3 is a bi-directional I/O port with internal pull-ups. All bits have alternate functions, which are described below:
	RXD(P3.0) : Serial Port receiver input
	TXD(P3.1) : Serial Port transmitter output
P3.0-P3.7	INT0 (P3.2) : External Interrupt 0
1 0.0 1 0.7	INT1(P3.3) : External Interrupt 1
	T0(P3.4) : Timer 0 External Input T1(P3.5) : Timer 1 External Input
	\overline{WR} (P3.6) :External Data Memory Write Strobe
	\overline{RD} (P3.7) : External Data Memory Read Strobe
	PORT 4: Another bit-addressable bidirectional I/O port P4. P4.3 and P4.2 are alternative
P4.0-P4.3	function pins. It can be used as general I/O port or external interrupt input sources $(\overline{INT2} / \overline{INT3})$.



5. FUNCTIONAL DESCRIPTION

The W78E054C architecture consists of a core controller surrounded by various registers, five general purpose I/O ports, 256 bytes of RAM, three timer/counters, and a serial port. The processor supports 111 different opcodes and references both a 64K program address space and a 64K data storage space.

5.1 Timers 0, 1, and 2

Timers 0, 1, and 2 each consist of two 8-bit data registers. These are called TL0 and TH0 for Timer 0, TL1 and TH1 for Timer 1, and TL2 and TH2 for Timer 2. The TCON and TMOD registers provide control functions for timers 0 and 1. The T2CON register provides control functions for Timer 2. RCAP2H and RCAP2L are used as reload/capture registers for Timer 2.

The operations of Timer 0 and Timer 1 are the same as in the W78C51. Timer 2 is a special feature of the W78E054C: it is a 16-bit timer/counter that is configured and controlled by the T2CON register. Like Timers 0 and 1, Timer 2 can operate as either an external event counter or as an internal timer, depending on the setting of bit C/T2 in T2CON. Timer 2 has three operating modes: capture, autoreload, and baud rate generator. The clock speed at capture or auto-reload mode is the same as that of Timers 0 and 1.

5.2 New Defined Peripheral

In order to be more suitable for I/O, an extra 4-bit bit-addressable port P4 and two external interrupt $\overline{INT2}$, $\overline{INT3}$ has been added to either the PLCC or QFP 44-pin package. And description follows:

5.2.1 INT2/ INT3

Two additional external interrupts, INT2 and INT3, whose functions are similar to those of external interrupt 0 and 1 in the standard 80C52. The functions/status of these interrupts are determined/shown by the bits in the XICON (External Interrupt Control) register. The XICON register is bit-addressable but is not a standard register in the standard 80C52. Its address is at 0C0H. To set/clear bits in the XICON register, one can use the "SETB (/CLR) bit" instruction. For example, "SETB 0C2H" sets the EX2 bit of XICON.

XICON - external interrupt control (C0H)

PX3 EX3 IE3 IT3 PX2	EX2 IE2 IT2
---------------------	-------------

PX3: External interrupt 3 priority high if set

EX3: External interrupt 3 enable if set

IE3: If IT3 = 1, IE3 is set/cleared automatically by hardware when interrupt is detected/serviced

IT3: External interrupt 3 is falling-edge/low-level triggered when this bit is set/cleared by software

PX2: External interrupt 2 priority high if set

EX2: External interrupt 2 enable if set

IE2: If IT2 = 1, IE2 is set/cleared automatically by hardware when interrupt is detected/serviced

IT2: External interrupt 2 is falling-edge/low-level triggered when this bit is set/cleared by software

Eight-source interrupt information

INTERRUPT SOURCE	VECTOR ADDRESS	POLLING SEQUENCE WITHIN PRIORITY LEVEL	ENABLE REQUIRED SETTINGS	INTERRUPT TYPE EDGE/LEVEL
External Interrupt 0	03H	0 (highest)	IE.0	TCON.0
Timer/Counter 0	0BH	1	IE.1	-
External Interrupt 1	13H	2	IE.2	TCON.2
Timer/Counter 1	1BH	3	IE.3	-
Serial Port	23H	4	IE.4	-
Timer/Counter 2	2BH	5	IE.5	-
External Interrupt 2	33H	6	XICON.2	XICON.0
External Interrupt 3	3BH	7 (lowest)	XICON.6	XICON.3

5.2.2 PORT4

Another bit-addressable port P4 is also available and only 4 bits (P4<3:0>) can be used. This port address is located at 0D8H with the same function as that of port P1, except the P4.3 and P4.2 are alternative function pins. It can be used as general I/O pins or external interrupt input sources ($\overline{INT2}$, $\overline{INT3}$).

Example:

P4	REG 0D8	H
MOV	P4, #0AH	; Output data "A" through P4.0–P4.3.
MOV	A, P4	; Read P4 status to Accumulator.
SETB	P4.0	; Set bit P4.0
CLR	P4.1	; Clear bit P4.1

5.2.3 Reduce EMI Emission

Because of on-chip Flash EPROM, when a program is running in internal ROM space, the ALE will be unused. The transition of ALE will cause noise, so it can be turned off to reduce the EMI emission if it is useless. Turning off the ALE signal transition only requires setting the bit 0 of the AUXR SFR, which is located at 08Eh. When ALE is turned off, it will be reactivated when the program accesses external ROM/RAM data or jumps to execute an external ROM code. The ALE signal will turn off again after it has been completely accessed or the program returns to internal ROM code space. The AO bit in the AUXR register, when set, disables the ALE output. In order to reduce EMI emission from oscillation circuitry, W78E054C allows user to diminish the gain of on-chip oscillator amplifiers by using programmer to clear the B7 bit of security register. Once B7 is set to 0, a half of gain will be decreased. Care must be taken if user attempts to diminish the gain of oscillator amplifier, reducing a half of gain may affect the external crystal operating improperly at high frequency above 24 MHz. The value of R and C1, C2 may need some adjustment while running at lower gain.



***AUXR - Auxiliary register (8EH)

AO

AO: Turn off ALE output.

5.3 Power-off Flag

***PCON - Power control (87H)

POF GF1 GF0 PD IDL

POF: Power off flag. Bit is set by hardware when power on reset. It can be cleared by software to determine chip reset is a warm boot or cold boot.

GF1, GF0: These two bits are general-purpose flag bits for the user.

PD: Power down mode bit. Set it to enter power down mode.

IDL: Idle mode bit. Set it to enter idle mode.

The power-off flag is located at PCON.4. This bit is set when VDD has been applied to the part. It can be used to determine if a reset is a warm boot or a cold boot if it is subsequently reset by software.

5.4 Watchdog Timer

The Watchdog timer is a free-running timer which can be programmed by the user to serve as a system monitor, a time-base generator or an event timer. It is basically a set of dividers that divide the system clock. The divider output is selectable and determines the time-out interval. When the time-out occurs, a system reset can also be caused if it is enabled. The main use of the Watchdog timer is as a system monitor. This is important in real-time control applications. In case of power glitches or electromagnetic interference, the processor may begin to execute errant code. If this is left unchecked the entire system may crash. The watchdog time-out selection will result in different time-out values depending on the clock speed. The Watchdog timer will be disabled on reset. In general, software should restart the Watchdog timer to put it into a known state. The control bits that support the Watchdog timer are discussed below.

Watchdog Timer Control Register

Bit:	7	6	5	4	3	2	1	0
	ENW	CLRW	WIDL	-	-	PS2	PS1	PS0

Mnemonic: WDTC

Address: 8FH

ENW : Enable watch-dog if set.

CLRW : Clear watch-dog timer and prescaler if set. This flag will be cleared automatically


WIDL : If this bit is set, watch-dog is enabled under IDLE mode. If cleared, watch-dog is disabled under IDLE mode. Default is cleared.

PS2, PS1, PS0: Watch-dog prescaler timer select. Prescaler is selected when set PS2~0 as follows:

6. SECURITY BITS

During the on-chip Flash EPROM operation mode, the Flash EPROM can be programmed and verified repeatedly. Until the code inside the Flash EPROM is confirmed OK, the code can be protected. The protection of Flash EPROM and those operations on it are described below.

The W78E054C has a Security Register which can not be accessed in normal mode. These registers can only be accessed from the Flash EPROM operation mode. Those bits of the Security Register can not be changed once they have been programmed from high to low. They can only be reset through erase-all operation. The Security Register is addressed in the Flash EPROM operation mode by address #0FFFFh.



6.1 Lock Bit

This bit is used to protect the customer's program code in the W78E054C. It may be set after the programmer finishes the programming and verifies sequence. Once this bit is set to logic 0, both the Flash EPROM data and Special Setting Register can not be accessed again.



6.2 MOVC Inhibit

This bit is used to restrict the accessible region of the MOVC instruction. It can prevent the MOVC instruction in external program memory from reading the internal program code. When this bit is set to logic 0, a MOVC instruction in external program memory space will be able to access code only in the external memory, not in the internal memory. A MOVC instruction in internal program memory space will always be able to access the ROM data in both internal and external memory. If this bit is logic 1, there are no restrictions on the MOVC instruction.

6.3 Encryption

This bit is used to enable/disable the encryption logic for code protection. Once encryption feature is enabled, the data presented on port 0 will be encoded via encryption logic. Only whole chip erase will reset this bit.

The second second

DC Characteristics, continued

PARAMETER	SYMBOL TEST CONDITIONS		PECIFICATION		UNIT
FARAMETER	STMBOL	TEST CONDITIONS	MIN. MAX.		UNIT
Output High Voltage	Vон2	VDD = 4.5V	2.4		V
ALE, \overline{PSEN} , P0 ^(*3)	V OH2	IOH2 = -400 μA	2.4	-	v
Input Low Voltage	VIL1	VDD = 4.5V	0	0.8	V
(Except RST)	VILI	VDD = 4.5V	0	0.0	v
Input Low Voltage	VIL2	VDD = 4.5V	0	0.8	V
RST ^(*4)	VILZ	VDD = 4.5V	0	0.0	v
Input Low Voltage	VIL3	Vdd = 4.5V	0	0.8	V
XTAL1 ^(*4)	VILS	VDD = 4.5V	0	0.8	v
Input High Voltage	VIH1	VDD = 4.5V	2.4	Vdd	V
(Except RST)	VIIII	100 - 4.01	2.7	+0.2	v
Sink Current	ISK1	VDD = 4.5V	4	12	mA
P1, P2, P3, P4		Vs = 0.45V	•	12	
Input High Voltage	VIH2	VDD = 4.5V	0.67	Vdd	V
RST ^(*4)	VIIIZ	100 - 4.01	Vdd	+0.2	v
Input High Voltage	Vінз	VDD = 4.5V	0.67	Vdd	V
XTAL1 ^(*4)	VINS	VDD = 4.5V	Vdd	+0.2	v
Sink Current	lowe	VDD = 4.5V	0	10	A
P0, ALE, PSEN ^(*3)	ISK2	Vs = 0.45V	8	16	mA
Source Current	ISR1	VDD = 4.5V	-100	250	
P1, P2, P3, P4	15K1	Vs = 2.4V	-100	-250	uA
Source Current	lopa	VDD = 4.5V	-8	-14	m۸
P0, ALE, PSEN ^(*3)	ISR2	Vs = 2.4V	-0	-14	mA

Notes:

*1. Pins P1, P2 and P3 source a transition current when they are being externally driven from 1 to 0. The transition current reaches its maximum value when VIN is approximately 2V.

*2. RST pin has an internal pull-down resistor.


*3. P0, ALE, PSEN are in the external access memory mode.

*4. XTAL1 is a CMOS input and RST is a Schmitt trigger input.

7.3 A.C. Characteristics

The AC specifications are a function of the particular process used to manufacture the part, the ratings of the I/O buffers, the capacitive load, and the internal routing capacitance. Most of the specifications can be expressed in terms of multiple input clock periods (TCP), and actual parts will usually experience less than a ± 20 nS variation. The numbers below represent the performance expected from a 0.6micron CMOS process when using 2 and 4 mA output buffers.

7.3.1 Clock Input Waveform



PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	NOTES
Operating Speed	Fop	0	-	40	MHz	1
Clock Period	Тср	25	-	-	nS	2
Clock High	Тсн	10	-	-	nS	3
Clock Low	Tc∟	10	-	-	nS	3

Notes:

1. The clock may be stopped indefinitely in either state.

2. The TCP specification is used as a reference in other specifications.

3. There are no duty cycle requirements on the XTAL1 input.

7.3.2 Program Fetch Cycle

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	NOTES
Address Valid to ALE Low	TAAS	1 TCP - Δ	-	-	nS	4
Address Hold from ALE Low	Таан	1 TCP - Δ	-	-	nS	1, 4
ALE Low to PSEN Low	TAPL	1 TCP - Δ	-	-	nS	4
PSEN Low to Data Valid	Tpda	-	-	2 Тср	nS	2
Data Hold after PSEN High	TPDH	0	-	1 TCP	nS	3
Data Float after PSEN High	Tpdz	0	-	1 TCP	nS	
ALE Pulse Width	TALW	2 Tcp -Δ	2 TCP	-	nS	4
PSEN Pulse Width	Tpsw	3 TCP - Δ	3 Тср	-	nS	4

Notes:

1. P0.0-P0.7, P2.0-P2.7 remain stable throughout entire memory cycle.

2. Memory access time is 3 $\ensuremath{\mathsf{TCP}}$.

3. Data have been latched internally prior to PSEN going high.

4. " Δ " (due to buffer driving delay and wire loading) is 20 nS.

7.3.3 Data Read Cycle

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	NOTES
ALE Low to RD Low	TDAR	3 Tcp - Δ	-	3 TCP + Δ	nS	1, 2
RD Low to Data Valid	Tdda	-	-	4 TCP	nS	1
Data Hold from RD High	Tddh	0	-	2 Тср	nS	
Data Float from RD High	Tddz	0	-	2 TCP	nS	
RD Pulse Width	Tdrd	6 Tcp -Δ	6 Тср	-	nS	2

Notes:

1. Data memory access time is 8 TCP.

2. " Δ " (due to buffer driving delay and wire loading) is 20 nS.

7.3.4 Data Write Cycle

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
ALE Low to WR Low	TDAW	3 TCP - Δ	-	3 TCP + Δ	nS
Data Valid to WR Low	Tdad	1 Tcp -Δ	-	-	nS
Data Hold from WR High	Towd	1 Tcp -Δ	-	-	nS
WR Pulse Width	Tdwr	6 TCP - Δ	6 Тср	-	nS

Note: $^{"}\Delta"$ (due to buffer driving delay and wire loading) is 20 nS.

7.3.5 Port Access Cycle

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
Port Input Setup to ALE Low	TPDS	1 TCP	-	-	nS
Port Input Hold from ALE Low	Трдн	0	-	-	nS
Port Output to ALE	Tpda	1 Тср	-	-	nS

Note: Ports are read during S5P2, and output data becomes available at the end of S6P2. The timing data are referenced to ALE, since it provides a convenient reference.

7.3.6 Program Operation


PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
VPP Setup Time	TVPS	2.0	-	-	μS
Data Setup Time	TDS	2.0	-	-	μS
Data Hold Time	Трн	2.0	-	-	μS
Address Setup Time	TAS	2.0	-	-	μS
Address Hold Time	Тан	0	-	-	μS
CE Program Pulse Width for Program Operation	TPWP	290	300	310	μS
OECTRL Setup Time	Tocs	2.0	-	-	μS
OECTRL Hold Time	Тосн	2.0	-	-	μS
OE Setup Time	TOES	2.0	-	-	μS
OE High to Output Float	Tdfp	0	-	130	nS
Data Valid from \overline{OE}	TOEV	-	-	150	nS

Note: Flash data can be accessed only in flash mode. The RST pin must pull in VIH status, the ALE pin must pull in VIL status, and the $\overrightarrow{\text{PSEN}}$ pin must pull in VIH status.




8. TIMING WAVEFORMS

8.1 Program Fetch Cycle




8.2 Data Read Cycle






Timing Waveforms, continued

8.3 Data Write Cycle



8.4 Port Access Cycle





9. TYPICAL APPLICATION CIRCUITS

9.1 Expanded External Program Memory and Crystal




Figure	A
--------	---

CRYSTAL	C1	C2	R
16 MHz	30P	30P	-
24 MHz	15P	15P	-
33 MHz	10P	10P	6.8K
40 MHz	5P	5P	4.7K

Above table shows the reference values for crystal applications (full gain).

Note: C1, C2, R components refer to Figure A.



Typical Application Circuits, continued

9.2 Expanded External Data Memory and Oscillator





Figure B




10. PACKAGE DIMENSIONS

10.1 40-pin DIP




10.2 44-pin PLCC





Package Dimensions, continued

10.3 44-pin PQFP



11. REVISION HISTORY

VERSION	DATE	PAGE	DESCRIPTION
A1	Nov. 26, 2004	-	Formerly issued
A2	April 20, 2005	24	Add Important Notice
A3	May 17, 2005	3	Add Lead Free (RoHS) parts
		Remove block diagram	
A4	October 3, 2006	3	Remove all Leaded parts

Important Notice

Winbond products are not designed, intended, authorized or warranted for use as components in systems or equipment intended for surgical implantation, atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, or for other applications intended to support or sustain life. Further more, Winbond products are not intended for applications wherein failure of Winbond products could result or lead to a situation wherein personal injury, death or severe property or environmental damage could occur.

Winbond customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Winbond for any damages resulting from such improper use or sales.

Please note that all data and specifications are subject to change without notice. All the trademarks of products and companies mentioned in this datasheet belong to their respective owners.